

STUCCO SEALER

Product description

Stucco sealer is a solvent-free product designed to protect plasters, lime and cement against water and stains. This water-based product works by sealing the pores to create a waterproof surface whilst still allowing for breathability, remaining permeable to air and water vapour.

Application Instructions

Stucco sealer is ready to use and does not require dilution. It can be applied on to horizontal or vertical surfaces, indoors or out. Shake well before use and apply 2 coats of Stucco sealer by foam or mohair roller wet on wet. Start from the bottom, moving upwards and do not over apply, making sure to eliminate any extra product before drying. The recommended drying time is approx. 24 hours.

Surface Preparation

Ensure the surface is completely dry, dust-free, grease-free and all impurities have been removed. Also make certain that the lime has perfectly carbonated before applying Stucco sealer.

Cleaning of tools

Tools should be cleaned immediately after use with water.

Technical Specifications

Each litre of Stucco sealer covers approx. 5msq depended on application and absorption of surface.

Recommendations:

For best results it is recommended that Stucco sealer is applied when the temperature of the surface is between 10°C and 30°C. Do not apply during rain or very hot weather, recommended air temperature is between 5°C and 30°C.

Storage

Storage temperature: 5°C - 30 ° C. Stucco sealer should be used preferably within 12 months from production date and should be stored in the original container, under the appropriate temperature conditions.