


**COB HIGH UNIFORMITY+ STRIP IP20 5M PACK 4000K 24V 10W/M 1156LM/M
CRI80 480LED/M 8MM WIDTH 115 BEAM**

ILSTWHIA367E



This new generation of LED strips utilises ultra-small LEDs arranged in a close formation to effectively eliminate the visible shadow present in many LED strips. This creates the effect of one continuous line of light, without the need of installation in a profile with frosted diffuser - ideal for any project where the strip is installed in a line of direct sight. Each 5m reel is supplied with an easy-to-follow installation guide and one extra connector to power the strip if it is cut into two lengths. A suitable constant voltage driver is required, depending on the total power requirement of the connected strip(s). Additional accessories are available to purchase (see suggested products below).

Details

Quick Order Code:	622786
Barcode:	5055788287995
Category:	Strips
Range Name:	High Uniformity Plus
Product Type:	White strip
Market Segment:	Commercial indoor, Residential indoor
Features:	Spotless
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Width (mm):	8
Material:	PCB
Construction:	LED integrated into strip PCB
Max Run Length (m):	5
Placement / Application:	Decorative indoor
Strip length (M):	5
Strip Width (mm):	8

Electrical Data

Power Consumption per meter (W/m):	10
Voltage (V):	24
Voltage Range (v):	24
Watts per metre:	6.1w - 10w

Dimming:	Dimmable
Driver Included:	No
Electric Current:	DC
EN:	IEC 60598, IEC 62031
LVD Certified:	Yes

Light Data

Luminous efficacy (lm/W):	116
Lumens per meter (lm/m):	1156
Correlated Colour Temperature (CCT) (K):	4000
Colour Temperature Name:	Cool White
Beam Angle:	140
Colour Rendering Index (CRI):	80
Colour Type:	White
LEDs per meter:	480
Lifetime (hours):	25000

Environment

EN:	IEC 60598, IEC 62031
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-25
Maximum Operating Temperature (°C):	50

Packaging

Package Weight (g):	165
Package Length (mm):	245
Package Width (mm):	215
Package Depth (mm):	10