

4H-SI WATER FILTERS 08/12/21 Item # 13598

| Item #:_ |  |
|----------|--|
| Project: |  |
| Qty:     |  |
| Qty      |  |

## **Dimensions** (WxDxH)

7.91" x 5.25" x 18.1"





H9320-54

H9655-08

### **Single Configuration** 18.1" H

\*height includes manifold and cartridge

| Model    | Filter | Max Flow<br>Rate | Working<br>Pressure | Temperature | Capacity    |
|----------|--------|------------------|---------------------|-------------|-------------|
| H9655-08 | 4\$1   | 2 gpm            | 10-125 psi          | 35-100°F    | 15,000 gal* |

\*Estimated. Actual capacity may vary depending on volume of particulate in incoming water

### Weight

Shipping: 4 lbs Operating: 7 lbs

Inlet/Outlet Connections: Single: (2) 3/8" FNPT

**Plumbing** 

# Warranty:

One Year replaceable elements\* One Year the entire system




| Std. No. | 42 - Aesthetic effects                                       |
|----------|--|
| Standard | I 42 and 53 for the reduction of:                            |
| System i | s tested and certified by NSF International against NSF/ANSI |

Mechanical Filtration- Nominal Particulate Class I Std. No. 53 - Heath effects

Mechanical Filtration Cyst

# **Features**

- Effectively filters dirt and particles as small as 1/2 mircron size by mechanical means
- Utilizes depth filtration and Fibredyne™ media for superior dirt-holding capability
- NSF/ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means
- Leaves chlorine and chloramines within water that is supplied to equipment which helps to reduce slime growth in ice machine and ice bin
- Reduces ice machine maintenance, service costs and downtime caused by scale buildup which can result in the clogging of distribution lines, malfunction of probes, floats, pumps, solenoids and valves, and higher energy consumption (as tested by Pentair Everpure)
- Sanitary cartridge replacement is simple, quick and clean; internal filter parts are never exposed to handling or contamination
- Designed for use with Hoshizaki 4H-SI Single Manifold Systems






\* Warranty applies to material defects in materials & workmanship only.

| Model<br>Number | Description<br>Flow Rate<br>(Gal. per min.) | Undercounter<br>KMs                                    | KM Cubers  | IM Cubers   | Cubelets<br>& Flakers | DCM/DBs    |
|-----------------|---|--|--|-------------|-----------------------|------------|
| H9655-08        | Single<br>(2 GPM)                           | AM-50<br>KM-81<br>KM-116<br>KM-161<br>KM-231<br>KM-301 | KM-350, 520, 660<br>KML-325, 500, 700<br>KMD-410, 460, 530<br>KMS-830<br>DKM-500 | IM-200, 500 | All Models            | All Models |

# Single



Recommended water filter configurations based on average ice machine usage and regular filter replacement. If your operation has challenging water conditions or higher usage, then it may be necessary to use an additional filter or prefilter.