

USER INSTRUCTIONS

RIDGELINE SIDE DOOR SCREEN - YKK ZIP CLOSURE SYSTEM



Thank you for purchasing our premium side door screen. Please read the instructions below carefully before attempting to install and use the screen.

WARNINGS

LIABILITY

RidgeLine Van Equipment does not accept responsibility for damage or injury caused by improper installation, use or handling of the RidgeLine Side Door Screen. With the purchase of this product, you confirm that you have read, understand and will act on the warnings outlined in these instructions.



The RidgeLine Side Door Screen must be kept away from open flames and other sources of extreme heat or fire (e.g. cooking areas, BBQs, etc.). Be aware of embers or flying ash carried by wind from nearby camp fires.

VEHICLE ACCESS / EGRESS

The RidgeLine Side Door Screen is designed to be installed in the side doorway of panel vans. Take care to plan safe escape from the van in an emergency.

INCORRECT INSTALLATION

It is important that the door screen is installed properly to reduce the risk of the door seal letting any water through during wet weather. If in doubt, get in touch and we will try our best to assist – email – info@ridgelinevan.co.uk

PRODUCT DESCRIPTION

The RidgeLine Side Door Screen is designed to be installed in the side doorway of panel vans to prevent small insects from entering the van when the sliding door is open. The small holes in the fly mesh allow the free flow of air but are too small for insects such as midges, noseeums, flys, wasps, bees etc. to pass through. Zips help to keep the screen closed up after you pass through. The screen can be rolled up and stored out of the way when not in use.

INSTALLATION GUIDELINES

There are two options to install the RidgeLine Side Door Screen:

 Install by trapping in the rubber door seal (Search RidgeLine Van Equipment on Youtube for a useful guide)



2. Install by attaching to the inside of the door surround using suitable fasteners

The best option for you will depend on the layout of the van and your personal preference. The screens were developed so that they could be installed using either method.



If you decide to go with Option 2 and install by fastening to the inside of the door surround then we leave it up to you to use a suitable fixing method. You could look into press studs, Velcro, or roofing screws (the self-drilling ones with the rubber washers work well), but we don't make any specific recommendations as there are so many ways to achieve a good result, and it really depends on the layout of your van.

If you decide to go with Option 1, we have included a list of steps that will take you through the installation.

OPTION 1 – TRAPPING IN THE DOOR SEAL

TOOLS AND SETUP

No specialist tools are required to install the RidgeLine Side Door Screen; however, the following may be useful:

- A second pair of hands it is possible to install the screen on your own but if you can have someone assist then it will make things much easier
- Step ladder this will help you to reach the upper parts of the door when installing the screen
- Clamps if you don't have a second person to help, then a couple of clamps might be useful
- Rubber mallet you can use your hands to knock the rubber door seal back on; however, a rubber mallet can be useful to get the seal securely back on

DURATION

You will likely need 30 mins to 1 hour to fit the screen and make any required adjustments.

INSTALLATION STEPS

- Remove the upper middle part of the rubber door seal by pulling it off. It should come off
 easily. Don't remove the whole top and sides in one go as this can be a pain to get back on in
 the right place. Clean in and around the seal if required.
- Hold the screen up and align centrally the top corners of the mesh part of the screen can help with getting it centred.
- Tuck the screen up from under the door seal and push the door seal back into position, trapping the screen material.
- Work from the top to the bottom, removing the door seal and trapping the screen material as you go. Doing a short section at a time works well here.
- Try to get the fabric to sit without any creases or folds.
- Once you have trapped the screen in the upper and side sections of the door rubber, stand back and check for good vertical and horizontal alignment.
- Adjust the tension in the screen fabric to get screen sitting well in the doorway. You can adjust
 the tension by removing short sections of the side rubber seal and allowing more or less fabric
 through.
- Once you are happy with the alignment and the tension in the screen, then you are good to go. We also include some metal clips which can be fitted as shown below to increase the strength of the connection. These are not always needed and it is up to you whether to use them or not. As the clips are quite strong, it is recommended to get the screen in a good position before fitting the clips as they can be tough to remove when you come to make final adjustments to the screen. To remove the clips, bend them open before pulling off to prevent scratching any paint or ripping the fabric.





OPTION 2 – ATTACHING TO INSIDE OF DOOR SURROUND

As we said above, this is up to you. Feel free to get in touch if you have any queries – info@ridgelinevan.co.uk

USE GUIDELINES

Using the door screens is very simple. To walk through the screen simply unzip one or both sides and push through. When you are through and let go, the screen should return to the centre and you can re-close the zip.

To roll the screen up and store out of the way, unzip both zips to the top and roll the screen up from the bottom. Use the adjustable straps and buckles at the top to secure the screen.

You can close the door with the screen either rolled up or when it is down. When closing the door, check that the material is not in the way of the door locks and catch hardware as this could damage the screen.

CONTACT INFO

If you need to get in touch for any reason, then please do not hesitate to email — info@ridgelinevan.co.uk and we will get back to you asap.

THANK YOU

Thanks again for your purchase of a RidgeLine Door Screen. We hope you can now enjoy fresh air flow, without the worry of the van filling up with pesky midges!