

e-STUDIO4515AC

e-STUDIO5015AC

- > Multifunction Laser Printer
- > 45 or 50 ppm print speed
- > Copy, Print, Scan, Fax
- > Beautiful 5-bit Colour Depth
- > Up to 12x18" or 12x47" paper size
- > Solutions-ready Touch Screen with Apps



CONNECT. INTEGRATE. SIMPLIFY.

Technology for every office, delivering advanced functionality, ease of use and peace of mind.

Every industry has unique workflow needs. Toshiba has developed customizable MFPs to make your job easier. Intuitive and smartly integrated, these products simplify complex tasks and give you control while providing the reliability Toshiba is known for.

Toshiba's latest series delivers on their promise of Together Information – commitment to collaborate with clients in order to provide tailored, cost-effective solutions that meet your print, document management and content needs while helping you meet your green objectives.

- 45 or 50 pages per minute
- High-resolution true 5-bit colour
- High-volume black & white
- Advanced e-BRIDGE Next technology
- Fast dual-core processor

Toshiba's latest e-BRIDGE Next controller delivers exceptional color quality.

Don't restrict yourself to black and white when you can print with impactful colour. And not just any colour, either. It's Toshiba's new, multi-beam laser colour with higher resolution for top-notch image quality.

- 1,200 dpi x 1,200 dpi (PostScript 3) for exceptional laser quality
- Toshiba e-BRIDGE Colour Profile Tool allows for the creation of profiles to adjust colour for varying media types, lighting or even to match Pantone colors, unique spot colors or output from another device
- 256 gradations for smooth transitions in photographs and illustrations
- Auto-calibration ensures consistency of colour across small and large print jobs



Simple, smart and stylish.

A new 10" tablet-style touch screen with an embedded web browser is easy to use and customizable to meet your needs. And, it is part of the bold new look being introduced across the e-STUDIO series.



SMALL FOOTPRINT, BIG BUSINESS.

Even with a relatively small footprint, the Toshiba e-STUDIO 4515AC / 5015AC is packed with industry-leading technology and innovations designed to help workgroups connect, integrate and simplify.

Dual-Scan Document Feeder option holds an amazing 300 originals and boasts an impressive 240 images per minute (IPM) by scanning both sides of the page in a single pass.

Multi-Station Print Enabler allows you to retrieve your print job from a series of networked MFPs via simple authentication.

Print Around eliminates printing bottlenecks by allowing other print jobs to go around one job that's held-up due to requiring a specific paper size or type or, in some cases, even colored toner.

Limitless Job Reservation will queue up multiple copy or print jobs so users can send jobs when convenient.

Embedded Optical Character Recognition (OCR) simplifies the creation of searchable PDFs or editable document formats such as Microsoft Word®.

Exclusive AquaAce Media water and tear resistant media up to 12" x 47" banner size.

Saddle/Fold Capabilities offer saddle-stitch finishing and the option to fold without stapling.

12" x 18" Cassette provides the ability to print stunning 11" x 17" color bleeds on 12" x 18" paper.

Scan-to and Print-from USB lets you print straight from your USB drive or scan documents to it.

Notifications Feature takes the hassle out of checking for depleted supplies or maintenance needs.

Paper Volume Indicators on the front panel make it easy to see the paper sizes, types and levels in each cassette.

Context-Sensitive Help Button provides instant, thorough explanations straight from the manual to help as needed.

Service Module Design significantly reduces the cost and time spent servicing the MFP.



TOSHIBA TECHNOLOGY NEVER LOOKED BETTER.

Keeping small to medium to large workgroups in mind, the e-STUDIO 4515AC / 5015AC is easily integrated, customizable and solutions ready, with an open platform.

Flexible integration with third-party solutions applications, an embedded web browser brings the workflow to one location, at your fingertips.

Toshiba's exclusive e-BRIDGE Print & Capture application enables mobile device users to take advantage of the broad feature set when they're in the office and on the go.

A universal driver along with PCL 6, PS3, and XPS support provide fast and easy connectivity to Windows®, Macintosh® and more.

The universal print driver works for all users. Tandem print comes standard, and you can choose from a variety of time-saving, function-adding plug-ins that enable productivity from the driver. For instance:

- Job Point—quickly split up large jobs with up to 10 Toshiba MFPs
- Job Replicator—use multi-part form replacement (3 prints)
- Job Separator—perform batch printing easily using any Windows app
- Job Build—conveniently print different document types all together as a single job
- NFC (Near Field Communication - users can connect wirelessly without wifi (option)

Tight Security

Along with all of the new and innovative Toshiba technologies, we keep the security of your business top of mind.

- A 320GB Self-Encrypting Drive (SED) with Automatic Drive Invalidation (ADI) & Data Overwrite capability provides top level security
- FIPS 140-2 Validated SED meets and exceeds government requirements
- IPsec is available to securely encrypt data sent to and from the MFP

Environmental Protection

Innovation that is truly innovative makes certain that your environment is part of the equation, which is precisely what Toshiba does.

- RoHS compliance, the use of recycled plastics, and Low-Power (0.6W) Super Sleep Mode work to help the environment
- EPEAT Gold Registered in the global registry for greener electronics, designed to help purchasers choose products that reduce environmental impact
- Energy Star V2.0 meets the latest, more stringent requirements



GO CONFIGURE, WITH FEATURES & BENEFITS.

1 Document Feeder Options

- MR4000B Dual-Scan Document Feeder (DSDF)
- MR3031B Reversing Automatic Document Feeder (RADF)
- KA5005PC Platen Cover

2 Accessory Tray & Options

- GR1330 Accessory Tray
- GR9000 Bluetooth Keyboard
- GR1340 10-Key Numeric Keypad

3 Finishing Options

- MJ1042B 50-Sheet Inner Finisher
- MJ1109B 50-Sheet Console Finisher
- MJ1110B 50-Sheet Saddle-Stitch Finisher
- MJ5015 Job Separator

4 Additional Paper Options

- KD1058B Paper Feed Pedestal
- KD1059LTB 2,000-Sheet Large Capacity Feeder
- MY1048B Additional Drawer Module for PFP
- MY1049B Envelope Cassette



Additional Option Highlights

- Embedded OCR Enabler
- Multi-Station Print Enabler
- Wireless LAN/Bluetooth
- IPsec Security Enabler
- Single & Dual-Line Facsimile
- Near Field Communication
- Hidden Card Reader Pocket
- Expansive Third-Party Solutions List

The Toshiba e-STUDIO4515AC / 5015AC can increase the efficiency of your workgroups, improve the professionalism of your presentations, and streamline the workflow of your organization. And, that's just for starters.

Double the Scan Speed

A 300-sheet high-speed, high-capacity Dual-Scan Document Feeder (DSDF) produces up to 120 IPM simplex and 240 IPM duplex. A conventional RADF is available for less scan-intensive businesses.

Envelopes—the Perfect Fit

A special envelope cassette is available to hold up to 60 envelopes, making sure each one is fed and printed in the same place, every time.

Volumes and Volumes

A high monthly copy volume is up to 210,000 for monochrome and 105,000 for colour printing. Toner yields are 33,600 CMY and 38,400 K (at 5%) respectively.

Multi-Station Print Enabler

Toshiba's internally developed Multi-Station Print Enabler allows users to send print jobs from their desktop and retrieve them at up to 50 e-Studio devices by simply swiping their card and authenticating at any convenient device.

Advanced e-BRIDGE Next Technology

Built on Linux®, this latest generation e-BRIDGE Next architecture features an Embedded Web Browser, a fast dual-core processor, 4GB RAM and a 320GB FIPS 140-2 Validated SED enabling the MFP to easily drive Toshiba's internally developed solutions or even third-party applications.

Main Specifications

Copy System	Indirect Electrostatic Photographic Method/OPC/Laser Printing/ Heat Roller Fusing
Display	10.1" Colour WVGA Touch Screen Tilting Display
Copy Speed	45 or 50 PPM (LT)
First Copy Out	Colour: 5.7 seconds Monochrome: 4.4 seconds
Warm-Up Time	Approx. 20 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	3.9" x 5.8" to 12" x 18", 12" x 47" Banner, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 1,200 Sheets/Max. 3,200 Sheets
Original Feed	Optional 300-Sheet DSDf or 100-Sheet RADF
Scan Speed & Weights	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour), Simplex: 9.3-110 lb Bond, Duplex: 9.3-110 lb Bond RADF Scan: Up to 73 IPM (Monochrome or Colour), Simplex: 9.3-41.8 lb Bond, Duplex: 13.3-41.8 lb Bond
Max. Original Size	LD
Paper Feed Sizes	Drawer 1: 550 Sheets-ST-R to LD Drawer 2: 550 Sheets-ST-R to 12" x 18" Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to 12" x 18", 12" x 47" Banner Opt. 550-Sheet Paper Feed Pedestal-ST-R to 12" x 18" Opt. 550-Sheet Drawer for PFP-ST-R to 12" x 18" Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Standard: 550 Sheets x 2-16 lb Bond-140 lb Index Stack Feed Bypass: 100 Sheets-14 lb Bond-100 lb Cover Opt. 550-Sheet Paper Feed Pedestal-16 lb Bond-140 lb Index Opt. 550 Sheets Drawer for PFP-16 lb Bond-140 lb Index Opt. Envelope Cassette for PFP-16 lb Bond-140 lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-17 lb-28 lb Bond Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
Paper Weights	Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
Duplex	25% to 400%
Reproduction Ratio	Max. 105K/ Month (Colour: 100%) Max. 210K/ Month (Monochrome: 100%)
Max Duty Cycle	Approx. 172 lb
Weight	23" (W) x 25.2" (D) x 31" (H)
Approx. Dimensions	CMY: 33.6K, K: 38.4K @ 5%
CMYK Toner Yield	120 Volts, 50/60 Hz, 12 Amps
Power Source	Maximum 1.5kW (120V)
Power Consumption	Intel Atom™ 1.33 GHz (Dual-Core)
CPU	4GB
Memory	320GB Self-Encrypting Drive
Hard Disk Drive	

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	45 or 50 Pages Per Minute (LT)
Print Resolution	600 x 600 dpi (5 bit), 1,200 x 1,200 dpi (Colour/2 bit) or 3,600 x 1,200 dpi (BW/with Smoothing) PS3 Only
Operating Systems	Windows Server® 2008 R2, R2 SP1, 2008/SP2, Windows® 7, 8.1, 10, Windows Server® 2012/R2, Windows Server® 2016, Macintosh® (macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13, Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk® for Macintosh Environments
Printing Protocols	SMB, LPR/LPD, IPP (Ver.2.) w/Authentication, AppleTalk PAP or EtherTalk, Port 9100 (bi-directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
Print Drivers	Windows Server 2008 SP2 (32-bit, 64-bit) Windows Server 2008 R2 SP1 (64-bit), Windows 7 SP1 (32-bit, 64-bit) Windows 8.1 (32-bit, 64-bit), Windows Server 2012/R2 (64-bit), Windows Server 2016, Windows 10 (32bit, 64-bit), macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed) Optional
Wireless Device	802.11b/g/n, Wireless LAN, Optional Bluetooth
Device Management	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple App Store or Google Play)
Account Control	TopAccess Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



Security Features	User Authentication, On-Board Data Scramble, SCEP, Disable e-Fileing/Copy, Disk Overwrite, IP/MAC Address Filtering (10Sets), Network Service Control, Address Filter (10sets), Network Service/Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS SYSLOG), IPsec (IKEv1, IKEv2), CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Dig Sign for Client Utilities, Password Policy, Password Lock and Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Dig Sign for firmware update, Integrity Check function, Image Log, Card/NFC Auth
Environmental Stds.	Energy Star (V2.0), EPEAT Gold, Blue Angel Mark (RAL UZ-205 MFD), Nordic Swan, RoHS
Certification	WHQL (Windows 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell, Citrix, SAP

Scan Specifications

Scan Speed	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour) RADF Scan: Up to 73 IPM (Monochrome or Colour)
Scan Modes	Standard: Full Colour, Auto Colour, Monochrome, Grayscale
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Colour/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
Image Compression	Colour/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Colour Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Platen & Document Feeder Options			
DSDf	MR-4000-B	Panel 10-Key Option	GR-1240
RADF	MR-3031-B	Card Reader Holder	GR-1320
Platen Cover	KA-5005PC	Meta Scan Enabler	GS-1010
		IPsec Enabler	GP-1080
Additional Paper Options		Unicode Font Enabler	GS-1007
Paper Feed Pedestal	KD-1058-B	Embedded OCR Enabler	GS-1080
Drawer Module	MY-1048-B	Multi-Station Print Enabler	GS-1090
Envelope Cassette Option	MY-1049-B	Monotype Font Option	GB-2050L
Large Capacity Feeder	KD-1059LT-B	Office365® App	GB-365Node
		Includes: OneDrive® 365 App	
		SharePoint® 365 App	
		Exchange® 365 App	
Finishing Options		Miscellaneous Options	
Inner Finisher	MJ-1042-B	Stand	ST-5005
50-Sheet Staple Finisher	MJ-1109-B	Accessible Arm	KK-2560
Saddle-Stitch Finisher	MJ-1110-B	Harness Kit for Coin Controller	GQ-1280
Hole Punch Unit for MJ-1042-B	MJ-6011N		
Hole Punch Unit for MJ-1109-B/1110-B	MJ-6105N		
Bridge Kit	KN-5005		
Job Separator	MJ-5015		
Connectivity/Security Options			
FAX Unit/2nd Line for FAX Unit	GD-1370NA-N		
Wireless LAN/Bluetooth	GN-4020		
Hardcopy Security Printing	GP-1190A		
Bluetooth Keyboard	GR-9000		
Accessory Tray	GR-1330		

Designs and specifications subject to change without notice. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact Steelhead for availability. Toner yields are estimates based on 5% coverage using letter-size page. Driver and connectivity features and support may vary based on the clients network operating system. Product names may be trademarks of their respective companies. This is a Class 1 laser product complying with IEC60825-1.