# Material Safety Data Sheet

Material Name	: Helix HX5 15W-40
Uses Product Code	: Engine oil. : 001C8216
	. 00100210
Manufacturer/Supplier	<ul> <li>Shell Downstream South Africa (Pty) Ltd The Campus Twickenham</li> <li>57 Sloane Street Bryanston</li> <li>2021</li> <li>South Africa</li> </ul>
Telephone Fax Email Contact for MSDS	: (+27) 08604674355 : (+27) 0214211308 : enquiries-ZA@shell.com
Emergency Telephone Number	: 011 608 3300 (including poison information). Netcare (for life-threatening emergencies) - 082 911.
. HAZARDS IDENTIFICATION	1
EC Classification	: Not classified as dangerous under EC criteria.
Health Hazards	: Not expected to be a health hazard when used under normal conditions. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.
Signs and Symptoms	<ul> <li>Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.</li> </ul>
Safety Hazards Environmental Hazards	<ul> <li>Not classified as flammable but will burn.</li> <li>Not classified as dangerous for the environment.</li> </ul>
3. COMPOSITION/INFORMAT	ION ON INGREDIENTS
Preparation description	: Highly refined mineral oils and additives.
Additional Information	: The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.
4. FIRST AID MEASURES	
General Information	: Not expected to be a health hazard when used under normal conditions.

according to EC directive 2001/58/EC

### **Material Safety Data Sheet**

Inhalation	<ul> <li>No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.</li> </ul>
Skin Contact	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
Eye Contact	: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
Ingestion	<ul> <li>In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.</li> </ul>
Advice to Physician	: Treat symptomatically.

#### 5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Specific Hazards	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Suitable Extinguishing Media Unsuitable Extinguishing Media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not use water in a jet.
Protective Equipment for Firefighters	:	Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

#### 6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

Protective measures Clean Up Methods Additional Advice	:	Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages cannot be contained.
7. HANDLING AND STORAGE		
General Precautions	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
		2/7

according to EC directive 2001/58/EC

# Material Safety Data Sheet

Handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
Storage	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Storage Temperature: $0 - 50^{\circ}$ C / $32 - 122^{\circ}$ F
Recommended Materials	:	For containers or container linings, use mild steel or high density polyethylene.
Unsuitable Materials	:	PVC.
Additional Information	:	Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Occupational Exposure Limits**

Material	Source	Туре	ppm	mg/m3	Notation
Oil mist, mineral	ACGIH	TWA		5 mg/m3	
		[Mist.]			
	ACGIH	STEL		10 mg/m3	
		[Mist.]			
Exposure Contro Personal Protect Equipment Respiratory P	tive : Protection :	depending upor based on a risk Appropriate mea airborne concer mist formed, the concentrations of Personal protect recommended r No respiratory p conditions of us practices, preca material. If engi concentrations of health, select re specific conditio Check with resp air-filtering resp combination of r combined partic >65°C(149 °F)]. Where hand con gloves approve US: F739) made suitable chemic gloves. Suitabili usage, e.g. freq resistance of glo seek advice from	a potential e assessmen asures inclu trations. Where is greate to be general tive equipm national star protection is e. In accord utions shou neering con to a level where spiratory protection intact with the d to relevant e from the for al protection ty and dural uency and do pove material m glove sup	xposure condition t of local circums ide: Adequate ver here material is h er potential for airl ated. ent (PPE) should ndards. Check wit ordinarily require lance with good in ild be taken to av- trols do not main nich is adequate t otection equipment otection equipment suitable, select an iter. Select a filter ic gases and vap e product may ou t standards (e.g. billowing materials n: PVC, neoprene billity of a glove is duration of contact , glove thickness	ntilation to control eated, sprayed or borne I meet th PPE suppliers. ed under normal ndustrial hygiene oid breathing of tain airborne to protect worker ent suitable for the ant legislation. suppliers. Where appropriate suitable for ours [boiling point ccur the use of Europe: EN374, a may provide e or nitrile rubber dependent on ct, chemical , dexterity. Always ated gloves should

according to EC directive 2001/58/EC

## Material Safety Data Sheet

	hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
Eye Protection	Wear safety glasses or full face shield if splashes are likely to occur.
Protective Clothing	Skin protection not ordinarily required beyond standard issue work clothes.
Monitoring Methods	Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.
Environmental Exposure	Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odour pH Initial Boiling Point and Boiling Range	<ul> <li>Amber. Liquid at room temperature.</li> <li>Slight hydrocarbon.</li> <li>Not applicable.</li> <li>&gt; 280 °C / 536 °F estimated value(s)</li> </ul>
Pour point	: Typical -30 °C / -22 °F
Flash point	: Typical 220 °C / 428 °F (COC)
Upper / lower Flammability or Explosion limits	: Typical 1 - 10 %(V) (based on mineral oil)
Auto-ignition temperature	: > 320 °C / 608 °F
Vapour pressure Density Water solubility	<ul> <li>&lt; 0,5 Pa at 20 °C / 68 °F (estimated value(s))</li> <li>Typical 885 kg/m3 at 15 °C / 59 °F</li> <li>Negligible.</li> </ul>
n-octanol/water partition coefficient (log Pow)	<ul> <li>Negligible.</li> <li>&gt; 6 (based on information on similar products)</li> </ul>
Kinematic viscosity Vapour density (air=1) Evaporation rate (nBuAc=1)	

### **10. STABILITY AND REACTIVITY**

### **11. TOXICOLOGICAL INFORMATION**

Basis for Assessment	:	Information given is based on data on the components and the toxicology of similar products.
Acute Oral Toxicity Acute Dermal Toxicity Acute Inhalation Toxicity	:	Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat Expected to be of low toxicity: LD50 > 5000 mg/kg , Rabbit Not considered to be an inhalation hazard under normal conditions of use.

according to EC directive 2001/58/EC

### **Material Safety Data Sheet**

Skin Irritation	:	Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
Eye Irritation	:	Expected to be slightly irritating.
Respiratory Irritation	:	Inhalation of vapours or mists may cause irritation.
Sensitisation	:	Not expected to be a skin sensitiser.
Repeated Dose Toxicity	:	Not expected to be a hazard.
Mutagenicity	:	Not considered a mutagenic hazard.
Carcinogenicity	:	Product contains mineral oils of types shown to be non- carcinogenic in animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.
Reproductive and Developmental Toxicity	:	Not expected to be a hazard.
Additional Information	:	Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible. Continuous contact with used engine oils has caused skin cancer in animal tests.

### **12. ECOLOGICAL INFORMATION**

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity	:	Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.
Mobility	:	Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.
Persistence/degradability	:	Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
Bioaccumulation	:	Contains components with the potential to bioaccumulate.
Other Adverse Effects	:	Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

### **13. DISPOSAL CONSIDERATIONS**

Material Disposal	:	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper
		5/7

### **Material Safety Data Sheet**

	waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
Container Disposal	Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
Local Legislation	Disposal should be in accordance with applicable regional, national, and local laws and regulations.

### **14. TRANSPORT INFORMATION**

#### ADR

This material is not classified as dangerous under ADR regulations.

#### RID

This material is not classified as dangerous under RID regulations.

#### ADNR

This material is not classified as dangerous under ADNR regulations.

#### IMDG

This material is not classified as dangerous under IMDG regulations.

#### IATA (Country variations may apply)

This material is not classified as dangerous under IATA regulations.

#### 15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EC Classification	:	Not classified as dangerous under EC criteria.
EC Symbols	:	No Hazard Symbol required
EC Risk Phrases	:	Not classified.
EC Safety Phrases	:	Not classified.
EINECS	:	All components
		listed or polymer
		exempt.
TSCA	:	All components
		listed.

#### **16. OTHER INFORMATION**

R-phrase(s)

Not classified.

MSDS Version Number : 2.0

according to EC directive 2001/58/EC

# Material Safety Data Sheet

MSDS Effective Date	: 24.05.2010	
MSDS Revisions	: A vertical bar ( ) in the left margin indicates an amendment from the previous version.	
MSDS Regulation	<ul> <li>The content and format of this safety data sheet is in accordance with Commission Directive 2001/58/EC of 27 July 2001, amending for the second time Commission Directive 91/155/EEC.</li> </ul>	
MSDS Distribution	: The information in this document should be made available to all who may handle the product.	
Disclaimer	This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.	