

HWI-T241H

4 Megapixel Hikvision IP Camera

1/3" Progressive Scan CMOS

Compression

H.265+/H.265/H.264+/H.264

2.8 mm Lens

EXIR IR LEDs range 30 m

WEB, CMS Software, Smartphone

and NVR



Hikvision

IP camera

1/3" Progressive Scan CMOS

4 Megapixel (2560x1440)

2.8 mm Lens

0 Lux

IR Range 30 m

H.265+/H.265/H.264+/H.264

Dual stream

Weatherproof IP67

IR Cut

RJ-45 10/100 BaseT

PoE IEEE802.3af

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

Specifications

Brand	Hikvision
Range	HiWatch Series
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Main Stream rate	4Mpx / 1080p / 720p (20 FPS)
Extra Stream rate	D1 / CIF (1 ~ 25 FPS)
Compression	H.265+/H.265/H.264+/H.264
Bitrate	32 Kbps ~ 8 Mbps
Lens	2.8 mm
Minimum illumination	Colour 0.028 Lux @ F2.0
Infrared lighting	0 Lux / EXIR LEDs IR (30 m)
Image improvements	DWDR, BLC, 3D-DNR, AGC, Motion detection
Day / Night	Removable mechanical ICR filter
Alarms	No
Audio	No
Network interface	Ethernet 10/100 BaseT
Internal memory	No
Remote access	Web Browser, Smartphone App IVMS 4500 and PC Software IVMS 4200
Interoperability	ONVIF, PSIA, CGI, ISAPI
Lens positioning	3 axis
Power	DC 12 V / 340 mA, PoE IEEE802.3af
Degree of protection	Weatherproof IP67
Material	Metal and Plastic
Temp. operation	-30° C ~ +60° C
Dimensions	94.4 mm (D) x 110 (Ø) mm
Weight	360 g