WESTERN CAMPFYRE LOG PLACEMENT INSTRUCTIONS

CAUTION.....WARNING.....IMPORTANT

USE ONLY PETERSON REAL FYRE <u>BURNERS AND VALVES</u> WITH THIS REAL FYRE LOG SET.



WCF-24 shown



LOG SET IMPORTANT INFORMATION

This instruction contains recommended log placement for these Real Fyre logs which will promote good combustion and provide superior flame pattern and appearance. **Use these logs only with a Peterson burner system**.

Adequate ventilation is absolutely necessary! Provided significant, noticeable sooting does not occur, some flexibility is possible in log placement to suit your individual preference (see Important below). If you experience a continued accumulation of black carbon (soot) on your logs it is an indication of incomplete combustion and you should move the effected log(s) so as to minimize the flame contact on the effected log(s). If significant sooting continues, stop using this gas log set.

Please read these instructions completely and carefully.

Important: Adequate ventilation is absolutely necessary. Adequate spacing between the logs is NECESSARY and MUST be maintained. Some carbon build up (sooting) may occur where flames strike the logs. If carbon build up (sooting) continues, rearrange top logs to allow more opening(s) for flame(s) before sooting becomes worse. If any sooting occurs outside of the firebox (i.e. on the walls), turn off unit immediately and contact a qualified professional service technician. WARNING: Use ONLY Peterson Real Fyre <u>burners</u> <u>and valves</u> with this Real Fyre gas log set. Failure to do so may result in property damage or personal injury, and will void listings, certifications, and invalidate claims made to RHP. Contact your local Real Fyre dealer if you need more information.

This product is only warranted when used as part of a Robert H. Peterson Co. vented burner system.

ROBERT H. PETERSON CO. • 14724 East Proctor Avenue • City of Industry, CA 91746

WARNING: This gas log set is for use with <u>R.H. Peterson Co</u> burners (and parts) <u>ONLY.</u>

CAUTION: Burn hazard! Logs will remain hot for some time after use. If you need to reposition any log to maintain the proper layout, use heat resistant gloves or allow logs adequate time to cool before handling.

Failure to use Peterson burners and valves may result in a **DANGEROUS** situation and in property damage, personal injury or even death; will void listings and certifications; and will void any insurance coverage by R.H. Peterson Co or our insurers.

Important: Disregard the ember screen installation information in your burner system owner's manual.

This log set uses a unique screen different from the screen shown in your burner system owner's manual. Follow these instructions for ember and screen placement.

EMBER SCREEN PLACEMENT

After filling the burner pan with sand, securely fit the ember screen over the rear of the pan, so that it rests on it with approximately two inches (2") of screen overhanging beyond the back of the pan (see Fig. 1-2). Spread your glowing embers on the screen and over the sand. Continue with the log placement as shown on the following pages.

LOG PLACEMENT

These log sets feature notches and indentations to assist in log placement and provide stability. The following pages will have detailed placement instructions for your specific log set.







Fig. 3-2

Western Campfyre Log Placement Instructions (18" model)









Western Campfyre Log Placement Instructions (24" model)







CAUTION: Burn hazard! Logs will remain

All items for this log set are included in one (1) box.

hot for some time after use.



Final Log Placement





Western Campfyre Log Placement Instructions (30" model)



Π

IV

2



[3]

6