



Announcing the launch of the ViewSmart 1600+, a sophisticated upgrade to our 16 channel controller with the latest technology. Check out the reliable, new and advanced features the ViewSmart 1600+ controller offers below and learn why this is the controller to purchase for your next application. Contact sales@rcsystemsco.com for more information.

		ViewSmart 1600		ViewSmart 1600+
FEATURES				
Analog Inputs	\checkmark	12 bit, 8/16, 0(4)-20mA	\checkmark	12 bit, 8/16, 0(4)-20mA
Analog Outputs		0 bit 4-20mA output. Max load 800 ohms with nominal 24VDC power supply	NEW	16 bit 4-20mA output. Max load 800 ohms with nominal 24VDC power supply
Alarm Level Functionality		3 independent alarm levels with relay acknowledge	NEW	4 independent alarm levels with relay acknowledge
Communication Ports	S	Standard dual Modbus RS-485 master/slave ports	NEW	Standard dual Modbus RS-485 master or slave ports and Modbus TCP server/client port
Graphic Display	5	5 inch standard monochrome graphic backlit LCD	NEW	5.7 inch bright QVGA color screen displaying data as trends, bar graphs, and engineering units
Standard Relays		4 Standard, partially programmable SPDT common alarm relays	NEW	5 Standard, fully programmable SPDT alarm relays. 4 standard programmable digital outputs
Optional Relays		Standard discrete relays	NEW	Standard discrete relays plus truly programmable relays
Wireless Functionality		Support wireless Modbus RS-485	NEW	RC Systems' WaveNet wireless and upgraded wireless Modbus RS-485
Isolated Modbus Options		Not available	NEW	Two additional isolated and programmable Modbus RS-485 ports available
Data Logging Capability		Not available	NEW	Data logging on SD card allows recording of input, values and events
Web Server		Not available	NEW	Configuration and monitoring available via embedded web server
E-mail Service		Not available	NEW	Event notification with daily/weekly summary via e-mail