





B10531M Braille Endurance Advanced AGM Battery For Marine Applications

At only 69 lbs, the B10531M Braille Endurance Advanced AGM Battery For Marine Applications is a high-performance upgrade from a traditional lead acid battery. Offering weight reduction, more power output and lasting up to 2 times longer than traditional lead acid batteries!

BENEFITS:

- Superior starting capabilities with high cranking amp output per kg
- Fast and efficient recharge, up to 2 times faster than traditional lead acid batteries
- Can be used in "Total Loss" (no alternator) applications
- Engineered for high shock and vibration applications
- Up to 2/3 weight reduction for equivalent cranking performance



PRODUCT INFORMATION

Physical Specs

Battery Chemistry LFP
Length (in) 12.9"
Width (in) 6.8"
Height (in) 9.4"
Weight (lbs) 69

Terminal Type Steel stud and needle

Polarity Left

Technical Specs

5 Second Pulse Cranking Amps	2905	Charging Temperature Discharge Temperature Range	0C to 50C
10 Second Pulse Discharge Current (A)	261		-40C to +60C
Voltage	12		400101000
Capacity (Ah)	105.0	Storage Temperature	-40C to +60C
Capacity (Wh)	1260	·	

Charging

Recharge Voltage 14.4V - 14.6V
Maintenance Charge Voltage 13.8V











Rev 05-23









