



Braille Battery™ MICRO-LiTE™ Lithium Technology

Lighter. Stronger. Faster.

Part Number: B128L
Model Name: Braille MICRO-LiTE B128L Lithium Technology Racing Battery




- MORE CRANKING POWER, LOWER IMPEDANCE DESIGN
- Easy Install: Built in a Direct Replacement Size
- Safe: Sealed Safe Design, Proven Performance
- Fast Power: Rapid Recharge, Stable Voltage Output
- Greener: Modular Design For Longer Life
- Exclusive Braille Lithium Racing Warranty

PHYSICAL SPECS

BCI Group: Same Length as Group 24, 27 & 34
 Length: 10.15" / 258 mm
 Width: 3.15" / 80 mm
 Height: 6.14" / 156 mm
 Minimum Weight: 8.8 lbs / 4 kg
 Post Type: Braille True Torque SAE Auto Posts, 3/8" bolt top. Threaded Stud
 Also Available
 Recommended Mount: Secure Mounting with Vibration padding.



New Stud Terminal



Optional OEM Terminal

PERFORMANCE

Voltage : 12 volts
 Full Charge Range: 13.6 - 13.8 volts
 Cranking Amps : 1698
 Lead-Acid Equivalent Capacity: 68 Lithium AH (LAH)
 Nominal Capacity (C/20 rate): 23 AH
 Impedance: < 4.0 milliohms
 Life Cycle @ 10% DOD: Up to 5000 cycles
 Life Cycle @ 80% DOD: Up to 2000 cycles

CHARGING & USAGE INFORMATION

Alternator: Automotive & Marine Compatible
 Battery charger: Model # 12310L & 12325L
 Rapid Recharge: 50 AH electronically controlled
 Recommended Charge Voltage: 14.4 - 14.8 Volts
 Do Not Exceed Charge Voltage: Up to 15 Volts
 Minimum Recommended Voltage: 8.0 Volts

WARRANTY

Warranty: 1 Year Free repair/replacement. See warranty terms and conditions.

