Braille GREEN-LiTE Lithium Technology

Part Number: **G7**

Up to 5X More Stored Energy

- Easy Install: Built in a Direct Replacement Size
- Safe: Sealed Safe Design
- Fast Power: Rapid Recharge, Stable Voltage Output
- Greener: Modular Design For Longer Life
- Exclusive Braille Lithium Racing Warranty

PHYSICAL SPECS

Battery Sizing Class:	"TX-7" Gr
Length:	5.94" / 15
Width:	2.57" /
Height:	3.59" /
Minimum Weight:	1.5 lbs / .
Post Type:	High Amp
	6mm x 1.
Polarity:	Loft Sido

ouping 50 mm 65 mm 91 mm 68 kg perage Brass with 0 mm Threaded Bolt Left Side Negative (**G7L** available for Right)

olarity

PERFORMANCE

12 volts Voltage: Full Charge Range: 13.3 volts Pulse Cranking Amps: 214 Lead-Acid Equivalent Capacity: 7.5 LAH

CHARGING

WARRANTY


Warranty:

Alternator or Mag: Battery charger: Rapid Recharge: **Recommended Charge Voltage:** Do Not Exceed Charge Voltage: Minimum Recommended Voltage: Minimum 14.0 volt output at 2 amp Braille Model # 1232L – 2amp Lithium 50 AH electronically controlled 14.4 - 14.8 Volts Up to 15.25 Volts 8.0 Volts

braille TTE

LIGHTER • STRONGER • FASTER

2 Year Repair/Replacement



Actual performance may vary. Pricing, specifications and features current as of 1/16, subject to change without notice. For latest information, contact Braille directly.

Braille Battery, Sarasota, FL 34243 USA Copyright Braille Battery, Inc. 2014

Ph: 941-312-5047

Fax: 941-870-3381 Email: sales@braillebattery.com

Web: braillebattery.com Braille GREEN-LiTE G7 Spec Data 1.17



Lighter. Stronger. Faster.