

PHYSICAL SPECS

Battery Sizing Class:	"ETX30" Group		
@Yb[h\:	6.6" / 168 mm		
Width:	5.2" / 132 mm		
Height:	6.88" / 173 mm		
Minimum Weight:	5.5 lbs / 2.5kg		
Post Type:	High Amperage Brass with 6mm x 1.0 mm		
Polarity:	Threaded Bolt (Auto Terminals) Right Positive (Left Custom):		

PERFORMANCE

Voltage:	12 volts
Full Charge Range:	13.8 volts
Pulse Cranking Amps:	947 amps
Cold Cranking Amp Replacement:	Up to 800 CCA Replacement (Racing Use)
Maximum Constant Amps:	150 amps
Lead-Acid Equivalent Capacity PbEq:	45 Lithium Amp Hour
Reserve Capacity:	32 minutes

Replaces:	Race	Street	Audio
Starting	800CCA	550CCA	500CCA
Reserve	90 Min	60 Min	30 Min
AH	39	26	39
Max Amps	1000+	800+	900+
Group Sizes	34,35,51, 51R, SBS30 &	U1R, 51, 51R,	U1R, 51, 51R,
Replaced	40, U1R PC925, PC1200	34, 35, PC925	34, 35, PC925

CHARGING

Alternator or Mag: Battery charger: Rapid Recharge: Recommended Charge Voltage: Do Not Exceed Charge Voltage: Minimum Recommended Voltage: Minimum 14.0 volt output Braille Model # 1236L- 6amp Lithium (Included with G30 Combo) 25 AH electronically controlled maximum 14.4 - 14.8 Volts Up to 15.25 Volts 8.0 Volts (do not charge if below, contact Braille)

*Performance specifications denote maximum lead-acid equivalents. Actual performance may vary. Pricing, specifications and features current as of 10/17, subject to change without notice. For latest information, contact Braille directly.

Braille Battery, Sarasota, FL 34243 USA Copyright Braille Battery, Inc. 2018

Ph: 941-312-5047

Fax: 941-870-3381

Email: sales@braillebattery.com Web: braillebattery.com Braille GREEN-LITE G30 Spec Data 4.18