

Braille GREEN-LiTE Lithium Technology

Lighter. Stronger. Faster.





- Up to 5X More Stored Energy
- Easy Install: Built in a Direct Replacement Size
- Safe: Sealed Safe Design, LiFePO4 cylindrical cells, UN DOT certified
- Fast Power: Rapid Recharge, Stable Voltage Output
- Greener: Modular Design For Longer Life
- Exclusive Braille Lithium Racing Warranty

PHYSICAL SPECS

 $\begin{array}{lll} \text{Battery Sizing Class:} & \text{``TX-5'' Grouping} \\ \text{Length:} & 4.45'' \ / \ 113 \ \text{mm} \\ \text{Width:} & 2.57'' \ / \ 65 \ \text{mm} \\ \text{Height:} & 3.69'' \ / \ 93.7 \ \text{mm} \\ \text{Weight:} & 2.1 \ \text{lbs} \ / \ 0.95 \ \text{kg} \\ \end{array}$

Post Type: High Amperage Brass with 6mm x 1.0 mm Threaded Bolt

Polarity: Right Side Negative

(G5LS available for Left)

PERFORMANCE

Voltage: 12 volts
Full Charge Range: 13.8 volts
Pulse Cranking Amps: 346

Lead-Acid Equivalent Capacity: 15 LAH (5Ah actual)



Braille Model G5 shown

CHARGING

Alternator or Mag: Minimum 14.0 volt output at 2 amp
Battery charger: Braille Model # 1236L – 6amp Lithium
Rapid Recharge: 6 AH electronically controlled

Recommended Charge Voltage: 14.4 Volts

Do Not Exceed Charge Voltage: Up to 15.25 Volts

Minimum Recommended Voltage: 8.0 Volts

WARRANTY

Warranty: 2 Year Repair/Replacement



*Performance specifications denote maximum lead-acid equivalents.

Actual performance may vary. Pricing, specifications and features current as of 1/19, subject to change without notice. For latest information, contact Braille directly.

Braille Battery, Sarasota, FL 34243 USA Copyright Braille Battery, Inc. 2019 Ph: 941-312-5047

Fax: 941-870-3381

Email: sales@braillebattery.com Web: braillebattery.com Braille GREEN-LITE G5 Spec Data 1.19