

Braille Battery[™] 2016 MICRO-LiTE[™] Lithium Technology

Lighter. Stronger. Faster.

Part Number: ML30C

Model Name: Braille MICRO-LiTE Lithium Technology Racing Battery



- Easy Install: Direct Drop In Replacements
- Faster: Only 9 Pounds Up to 40 Pounds Lighter
 Safer: Sealed Safe Design, Low Voltage Protection
- Efficient: Stable Voltage Output, Less Stress on Alternator
- · Greener: Modular Design For Longer Life
- Reliable: Longer Cycle Life backed by Racing Warranty

PHYSICAL SPECS

 Length:
 6.6" / 168 mm

 Width:
 5.2" / 132 mm

 Height:
 6.88" / 173 mm

 Weight:
 8.9 lbs/ 4.0 kg

BCI Group: "30L" Power Sports and Racing
Size: Same Size as B3121 AGM Battery
Polarity: Right Side Positive (left optional)
Post Type: SAE Auto Posts / M6 bolt
Recommended Mounts: Braille 3118 Horizontal Aluminum

PERFORMANCE

Voltage: 12 volts
Full Charge Voltage Range: 13.8 volts
Pulse Cranking Amps (PCA) 5 sec @ 80F*: 1905

Lead-Acid Equivalent Capacity: 84 Lithium AH (LAH)

Nominal Capacity (C/20 rate)*: 28 AH

Life Cycle @ 10% DOD: Up to 5000 cycles



ML30C Model with TrueTorque TM Terminals attached

CHARGING INFORMATION

Alternator: Automotive & Marine Compatible

Battery char ger: Model# 12310L, 12325L &12350L compatible

Rapid Recharge: 50 AH electronically controlled

Recommended Charge Voltage: 14.4 - 14.8 Volts

Do Not Exceed Charge Voltage: 16 Volts

WARRANTY

Warranty: 1 Year Free repair/replacement. See warranty terms and conditions.



^{*} Performance specifications denote maximum lead-acid equivalents.

Actual performance may vary. Pricing, specifications and features current as of 3/18, subject to change without notice. For latest information, contact Braille directly.