









• DEM SUPPLY BATTERY FOR STARTING

- DAYTONA 500 WINNING TECHNOLOGY
- BOLT-IN PERFORMANCE UPGRADE
- SEALED-SAFE DOT APPROVED
- ALTERNATOR COMPATIBLE
- FASTER RECHARGING
- 10+ YR DESIGN LIFE
- MADE IN THE USA



Lighter. Stronger. Faster.

PHYSICAL SPECS

Battery Sizing Class:"YTX-20L" Group / PC680Length:7.1" / 180 mmWidth:3.0" / 76 mmHeight:6.2" / 167 mmMinimum Weight:4.5 lbs / 2kgPost Type:M6 Female ThreadedPolarity:Bolt Right Positive

PERFORMANCE

Voltage:13.2 voltsFull Charge Range:13.8-14.0 voltsCranking Amps:697PCA / 625 CAMaximum Constant Amps:200 ampsLead-Acid Equivalent Capacity:38 Amp Hour / Actual 12.5 Amp Hour

CHARGING

Alternator or Mag: Battery charger: Rapid Recharge: Recommended Charge Voltage: Do Not Exceed Charge Voltage: Minimum Recommended Voltage: Minimum 14.0 volt output, Max 14.8 volt Braille Model # 1236L - 6amp Lithium (OE Must have approved Charging) 10 AH electronically controlled maximum 14.4 - 14.8 Volts Up to 15.25 Volts 8.0 Volts (Do not charge if below, contact Braille)

WARRANTY

Warranty: 2 Year ProRated Repair/Replacement

*Performance specifications denote maximum lead-acid equivalents. Actual performance may vary. Pricing, specifications and features current as of 10/16, subject to change without notice. For latest information, contact Braille directly.