
W90 Application Sheet

22.840 (580.14)

TORQUE-HUB. Planetary Final Drives

(Also available with special input and 25:1 ratio)



Catalog prints are representative of the units.

Before final design request a certified print from Fairfield.

W90

Performance Data		
Continuous	Intermittent	Peak
1,470,000 lb-in	2,941,000 lb-in	
122,500 lb-ft	245,000 lb-ft	Contact Fairfield
166,110 Nm	332,333 Nm	
16,905 kg-m	33,821 kg-m	

For ultimate torque and horsepower capacities, contact a Torque-Hub® representative.

Speed Limitations

Input Speed: Please contact Fairfield.

Weight

Approximately 2,276 lbs (1,024 kg)

Note: Specific models will change weights.

Oil

Fill to half full with 90 weight gear lube with EP additive on most applications.

Approximate Volume 7.5 gal. (28,400 cm³)

Note: Oil level and type will vary with specific model and application.


Conditions of Bearing Curve

Please contact Fairfield.

Bearing Curve

Please contact Fairfield.

Note: Unit shown uses S6C1 single planetary input to W90 for 3-stage ratios of 95:1, 113:1, 118:1, and 151:1. W90 with 25.218:1 ratio does not use S6C input.



Torque-Hub is a registered trademark of Fairfield. © 2003 Fairfield Manufacturing Company, Inc.