

SAFETY DATA SHEET

HD ULTRA BOND PIMER

Compilation date: 12/11/2014

Revision date: 10/02/2017

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ULTRA BOND PRIMER

Product code: HDPRO-AFP01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC39: Cosmetics, personal care products.

1.3. Details of the supplier of the safety data sheet

Company name: Hazel Dixon Nails Ltd

Unit 4, Faraday Place, Thetford, Norfolk, IP24 3RG

Tel: 44 7494 470 168

Email: hazeldixonnails@yahoo.co.uk

1.4. Emergency telephone number

Emergency Tel: +31 (0) 40 -2307559 (Office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 1: H224; Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; STOT SE 3: H335; STOT SE 3: H336; -: EUH208

Most important adverse effects: Contains 2-hydroxyethyl acrylate. May produce an allergic reaction. Extremely flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains 2-hydroxyethyl acrylate. May produce an allergic reaction.

H224: Extremely flammable liquid and vapour.

H315: Causes skin irritation.

SAFETY DATA SHEET

HD ULTRA BOND PIMER

Page: 2

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314: Get medical advice/attention if you feel unwell.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHYL ACETATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
205-500-4	141-78-6	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	50-75%

BIS GMA

-	1565-94-2	-	STOT SE 3: H335; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317	10-25%
---	-----------	---	--	--------

CARBOXYFUNCTIONAL ACRYLATE.

-	30697-40-6	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319	5-10%
---	------------	---	---	-------

[cont...]

SAFETY DATA SHEET

HD ULTRA BOND PIMER

Page: 3

ETHYL METHACRYLATE

202-597-5	97-63-2	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317	1-5%
-----------	---------	---	--	------

2-HYDROXYETHYL ACRYLATE

212-454-9	818-61-1	-	Acute Tox. 3: H311; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Acute 1: H400	<0.1%
-----------	----------	---	--	-------

Non-classified ingredients:

ACRYLFUNCTIONAL POLYESTER MODIFIED POLYDIMETHYLSILOXANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	Mixture	-	-	0.1-1%

Contains: CI 60725

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

[cont...]

SAFETY DATA SHEET

HD ULTRA BOND PIMER

Page: 4

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

7.3. Specific end use(s)

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET

HD ULTRA BOND PIMER

Page: 5

ETHYL ACETATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	200 ppm	400 ppm	-	-

BIS GMA

UK	-	-	N/A	-
----	---	---	-----	---

ETHYL METHACRYLATE

UK	250 mg/m ³	-	-	-
----	-----------------------	---	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Viscosity: Non-viscous

Flash point°C: <21

Relative density: 0.97

9.2. Other information

Section 10: Stability and reactivity

10.1. Reactivity

Other information: No data available.

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

10.3. Possibility of hazardous reactions

Chemical stability: Stable under normal conditions.

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

SAFETY DATA SHEET

HD ULTRA BOND PIMER

Page: 6

10.4. Conditions to avoid

Conditions to avoid: Heat. Flames.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

ETHYL METHACRYLATE

IPR	RAT	LD50	1223	mg/kg
ORL	MUS	LD50	7836	mg/kg
ORL	RAT	LD50	14800	mg/kg

2-HYDROXYETHYL ACRYLATE

ORL	MUS	LD50	300	mg/kg
ORL	RAT	LD50	548	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

[cont...]

SAFETY DATA SHEET

HD ULTRA BOND PIMER

Page: 7

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Mobility: Readily absorbed into soil.

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Other adverse effects: No data available.

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

(ETHYL ACETATE; BIS GMA; CARBOXYFUNCTIONAL ACRYLATE.; ETHYL METHACRYLATE; 2-HYDROXYETHYL ACRYLATE)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

14.5. Environmental hazards

Packing group: II

Environmentally hazardous: No

Marine pollutant: No

[cont...]

SAFETY DATA SHEET

HD ULTRA BOND PIMER

Page: 8

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

This safety data sheet is prepared in accordance with Commission Regulation (EC) No 1272/2008.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H224: Extremely flammable liquid and vapour.

H225: Highly flammable liquid and vapour.

H311: Toxic in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H400: Very toxic to aquatic life.

Legal disclaimer: The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions for INCI queries contact; DVD Group - De Tonne 49 9800 Deinze - Belgium - Tel: +31 (0) 40 -2307559 - Email: info@dvdgroup.eu