

SAFETY DATA SHEET
HD PROFESSIONAL NAIL SYSTEMS
NAIL PREP

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name: Nail Prep
Item code: HDPRO-NP06
Use of substance / mixture: Nail Plate preparation PC39: Cosmetics, personal care products.

Details of the supplier of the safety data sheet:

Company name:
 Hazel Dixon Nails Ltd
 Unit 4, Faraday Place,
 Thetford,
 Norfolk,
 IP24 3RG

Tel : +44 074 9447 0168
Email : hazeldixonnails@yahoo.co.uk



Emergency tel: +31 (0) 40 -2307559
 'Only for the purpose of informing medical personnel in cases of acute intoxications'.

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification under CHIP	F: R11; Xi: R36; -: R67
Classification under CLP	STOT SE 3: H336; Eye Irrit. 2: H319; Flam. Liq. 1: H224
Most important adverse effects	Highly flammable. Irritating to eyes. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CLP	
Hazard statements	H224: Extremely flammable liquid and vapour. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.
Signal words	Danger
Hazard pictograms	GHS02: Flame GHS07: Exclamation mark  
Precautionary statements	P280: Wear. P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with. P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312: Call a POISON CENTER or doctor if you feel unwell. P370+378: In case of fire: Use for extinction.
Label elements under CHIP	

Hazard symbols	Highly flammable. Harmful.  
Risk phrases	R11: Highly flammable. R36: Irritating to eyes. R67: Vapours may cause drowsiness and dizziness.
Safety phrases	S2: Keep out of the reach of children. S3/9: Keep in a cool, well ventilated place. S16: Keep away from sources of ignition - No smoking. S20/21: When using do not eat, drink or smoke. S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S60: This material and its container must be disposed of as hazardous waste.

2.3. Other hazards

Other hazards	In use, may form flammable / explosive vapour-air mixture.
PBT	This product is not identified as a PBT substance.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Mixtures

Hazardous Ingredients

PROPAN-2-OL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-661-7	67-63-0	F: R11; Xi: R36; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	50-75%

ETHYL ACETATE

205-500-4	141-78-6	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-25%
-----------	----------	---------------------------------	--	--------

N-BUTYL ACETATE

204-658-1	123-86-4	-: R10; -: R66; -: R67 Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-25%
-----------	----------	--	--	--------

Contains: CONTAINS COLOUR CI 42045

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

Skin contact	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
Eye contact	Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion	Wash out mouth with water. Consult a doctor.
Inhalation	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	There may be irritation and redness at the site of contact.
Eye contact	There may be irritation and redness. The eyes may water profusely.
Ingestion	There may be soreness and redness of the mouth and throat.
Inhalation;	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.
Delayed / immediate effects	Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment	Eye bathing equipment should be available on the premises.
--------------------------------------	--

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Extinguishing Media	Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.
----------------------------	---

5.2. Special hazards arising from the substance or mixture

Exposure hazards	Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.
-------------------------	--

5.3 Advice for fire-fighters

Advice for fire-fighters	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.
---------------------------------	--

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorized personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or rivers. Contain the spillage using bunding.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Clean-up procedures	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.
----------------------------	---

6.4. Reference to other sections

Reference to other sections	Refer to section 8 of SDS.
------------------------------------	----------------------------

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling requirements	Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do
------------------------------	---

Colour	Blue
Odor	Characteristic odor
Evaporation rate	Fast
Viscosity	Non-viscous
Flash point°C	12

9.2. Other information

Other information	No data available.
--------------------------	--------------------

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity	Stable under recommended transport or storage conditions.
-------------------	---

10.2. Chemical stability

Chemical stability	Stable under normal conditions. Stable at room temperature.
---------------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.
---	---

10.4. Conditions to avoid

Conditions to avoid	Heat. Hot surfaces. Sources of ignition. Flames.
----------------------------	--

10.5. Incompatible materials

Materials to avoid	Strong oxidizing agents. Strong acids.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	In combustion emits toxic fumes.
---	----------------------------------

10.7. Hazardous polymerization

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Hazardous ingredients:

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

N-BUTYL ACETATE

ORL	MUS	LD50	6	gn/kg
ORL	RAT	LD50	10768	mg/kg

Relevant effects for mixture

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

11.2. Symptoms / routes of exposure

Skin contact	There may be irritation and redness at the site of contact.
Eye contact	There may be irritation and redness. The eyes may water profusely.
Ingestion	There may be soreness and redness of the mouth and throat.
Inhalation	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.
Delayed / immediate effects	Immediate effects can be expected after short-term exposure.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity values	No data available.
---------------------------	--------------------

12.2. Persistence and degradability

Persistence and degradability	Biodegradable.
--------------------------------------	----------------

12.3. Bioaccumulative potential

Bioaccumulative potential	No bioaccumulation potential.
----------------------------------	-------------------------------

12.4. Mobility in soil

Mobility:	Readily absorbed into soil.
------------------	-----------------------------

12.5. Results of PBT and vPvB assessment

PBT identification	This product is not identified as a PBT substance.
---------------------------	--

12.6. Other adverse effects

Other adverse effects	Negligible ecotoxicity.
------------------------------	-------------------------

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Disposal operations	Transfer to a suitable container and arrange for collection by specialized disposal company.
NB	The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN number	UN 1993
------------------	---------

14.2. UN proper shipping name

Shipping name	FLAMMABLE LIQUID, N.O.S. (PROPAN-2-OL; ETHYL ACETATE; N-BUTYL ACETATE MIXTURE)
----------------------	---

14.3. Transport hazard class(es)

Transport class	3
------------------------	---

14.4. Packing Group

Packing group	II
----------------------	----

14.5. Environmental hazards

Environmentally hazardous	No
Marine pollutant	No

14.6. Special precautions for user

Special precautions	No special precautions.
----------------------------	-------------------------

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

SECTION 16. OTHER INFORMATION

Other information:

Other information	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010. * indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and 3	EUH066: Repeated exposure may cause skin dryness or cracking. H224: Extremely flammable liquid and vapour. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. R10: Flammable. R11: Highly flammable. R36: Irritating to eyes. R66: Repeated exposure may cause skin dryness or cracking. R67: Vapours may cause drowsiness and dizziness.
Legal disclaimer	The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.
	Prepared by; DVD Group - De Tonne 49 9800 Deinze - Belgium - Tel: +31 (0) 40 - 2307559 - Email: info@dvdgroup.eu