

# BDST-65

## PRODUCT INFORMATION

Here are the key specifications for this product model.

### OVERALL

|                          |                    |                       |
|--------------------------|--------------------|-----------------------|
| Operating weight         | 3800 kg            | 8378 lb               |
| Rated operating capacity | 1000 kg            | 2205 lb               |
| Overall dimensions       | 3500x1782x2150 mm  | 138x70x85 in          |
| Bucket capacity          | 0.5 m <sup>3</sup> | 17.65 ft <sup>3</sup> |
| Max. travel speed        | 12 km/h            | 7.5 mile/h            |
| Hydraulic pump flow      | 80L/min            | 21 GPM                |
| Fuel tank capacity       | 90 L               | 23.8 gal              |

### ENGINE

|                |   |         |
|----------------|---|---------|
| Model          | CUMMINS (EPA)QSF2.8t4TC74                                 |         |
| Rated power    | 54.9 kw   | 73.7 hp |
| Rotating speed | 2500 r/min  |         |
| Type           | 4 Cylinder in-line, Water cooled, 4 stroke, Diesel engine |         |
| Displacement   | 3.1 L   | 0.8 gal |

### DIMENSIONS

|                            |         |         |
|----------------------------|---------|---------|
| Height to bucket hinge pin | 2900 mm | 114 in  |
| Width with bucket          | 1830 mm | 72 in   |
| Crawler length             | 320 mm  | 12.6 in |
| Crawler length on ground   | 1500 mm | 59 in   |
| Ground clearance           | 200 mm  | 7.9 in  |

### CONFIGURATION

|                                      |                   |
|--------------------------------------|-------------------|
| Standard bucket                      | Standard Equipped |
| Open-type operator cab               | Standard Equipped |
| Hydraulic joystick controls          | Standard Equipped |
| Auxiliary hydraulic couplers         | Standard Equipped |
| Cab fitted with a heater as standard | Optional          |
| Air conditioner                      | Optional          |

ISO CE EPA EURO5

# BdiEQUIPMENTS



## 1-800-553-9061



## Bdi Equipments

# BDST-65

## SKID STEER LOADER

## BdiEQUIPMENTS

Ontario Head office Address: 7300 Warden Ave, Unit 503, Markham, ON L3R 9Z6

Ontario Warehouse Address: 267 Matheson Blvd E, Mississauga, ON L4Z 1X8

Montreal Warehouse Address: 6635 Chem. of the Côte de Liesse, Saint-Laurent, QC H4T 1Z5

Vancouver Warehouse Address: 8040 River Rd, Richmond, BC V6X 1X7

Los Angeles Warehouse Address: 9935 Beverly Blvd Unit 3, Pico Rivera, CA 90660, USA

New York Warehouse Address: 174 Ridge Rd a, South Brunswick Township, NJ 08810, USA

More details and other products please visit [www.bdiequipments.com](http://www.bdiequipments.com)

We reserve the right to improve or withdraw the specification or products without prior notice

■ Toll free : 1-800-553-9061

■ Fax : 1-866-238-8172

■ Email : [sales@bdiequipments.com](mailto:sales@bdiequipments.com)

## BDST-65

Toll free **1-800-553-9061**

### QUICK OVERVIEW (KEY SPECIFICATION)

|                            |                           |            |
|----------------------------|---------------------------|------------|
| Operating weight           | 3800 kg                   | 8378 lb    |
| Rated operating capacity   | 1000 kg                   | 2205 lb    |
| Max. travel speed          | 12 km/h                   | 7.5 mile/h |
| Engine model               | CUMMINS (EPA)QSF2.8t4TC74 |            |
| Engine rated power         | 54.9 kW                   | 73.7 hp    |
| Engine rotating speed      | 2500 rpm                  |            |
| Height to bucket hinge pin | 2900 mm                   | 114 in     |
| Oil type                   | Diesel                    |            |



Toll free: 1-800-553-9061

Fax: 1-866-238-8172

Email: [sales@bdiequipments.com](mailto:sales@bdiequipments.com)

