TECHNICAL SPECIFICATIONS



Call 01255 555200 Email info@durite.co.uk Visit www.durite.co.uk



0-445-36 - 10-30V Low Profile Single Bolt Beacon

Durite Single Bolt Amber Lens Amber LED Low Profile Beacon with 3 flash patterns (Rotating, Dual Flashing, Sextuple Flashing). 10-30v, 45 x 0.45W (2835 SMD) Amber LED's.

E Marked R65 + R10 EMC.



THE TRUSTED QUALITY BRAND FOR PROFESSIONALS



TECHNICAL SPECIFICATIONS

Call 01255 555200 Email info@durite.co.uk Visit www.durite.co.uk

TECHNICAL SPECIFICATIONS

Туре	Single Bolt Amber Lens Amber LED Low Profile Beacon
Voltage	10-30VDC
LED's	45 x 0.45W (2835 SMD)
Power	20W (Max Power)
Current Draw	1.8A@ 12V/ 0.9A @ 24V (Max Current)
IP Rating	IP65
Material Construction	ABS Base with PC Lens.
Weight	0285Kg
Dimensions	Please see below
Operating Temperature	-30°C to +50°C
Certificate	CE, E Mark R65 + R10 EMC

TECHNICAL DRAWING

