

auto electrical parts

Technical Information Sheet

Part No. 0-690-54

On/off, push-push single pole switch, 12/24 volt green LED indicator with 4.8mm blade terminals. Snap fits into 20mm diameter panel hole. 20 amp at 12 volts DC rating and 10 amp at 24 volts DC rating.


Additional Information


Terminal 1 - Supply +ve
Terminal 2 - Switched load
Terminal 4 - Ground -ve




TERMS	0	1
A-B		
A-:\$		

Technical Drawing (not to scale)









Specification

Type Single pole 2 position on/off push-push switch with LED indication

DC current rating 20 amps at 12 volts and 10 amps at 24 volts

LED Green LED current @ 12 volts 7mA

Terminals 4.8mm lucar blade

Temperature range -20° C to 85° C Contact resistance ≥50m Ω

Electric strength 500vdc/1000vac

 $\begin{array}{ll} \text{Insulation resistance} & \leq 100 \text{M}\Omega \\ \text{Material} & \text{Nylon} \\ \text{Panel cut-out} & 20 \text{mm} \\ \text{Panel depth} & 0.7 \text{ to } 3.0 \text{mm} \end{array}$

Protection IP56 Weight 10g

Dimensions Ø24 x h 33mm (including terminals)

The information contained in this document is correct to the best of our knowledge at the time of printing. However, specifications may change at any time without notice.