

Non e permesso consegnare a terzi o riprodurre questo documento, ne utilizzare il contenuto o renderlo comunque noto a terzi senza autorizzazione esplicita. Ogni infrazione costituirà un evidente abuso e comporterà il risarcimento dei danni subiti. E' fatta riserva di tutti i diritti derivanti da brevetti o modelli.

Toute communication ou reproduction de ce document, toute exploitation ou communication de son contenu sont interdites, sauf autorisation expresse. Tout manquement a cette regle constitue un abus evident et expose son auteur au versement de dommages et interets. Tous droits de propriete industrielle reserves, notamment en matiere de brevets et de modesles.

Copying of this document and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Contravention of this restriction will constitute an evident abuse and result in a liability to the payment of damages. All rights are reserved in the event of the grant of patent or registration of a utility model or design. This document is the subject of copyright.

Weitergabe sowie Vervielfaeligung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdruecklich zugestanden. Zuwiderhandlungen stellen einen offensichtlichen Missbrauch dar und verpflichten zu Schadensersatz. Alle Rechte fuer den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.

1	2	3	4	5	6	7	8			
A	B	C	D	E	F	G	H	I	J	K
for Tube 8x1,0 new Line <CI>	M12x1,5	8	Hex.18	Ø17,4	33,3	20Nm (24Nm)	(20,5) Push in length <CI>	1,5	Ø18,3	with O-ring

G : recommended torque without lubrication (max. torque) respect max torque of counter part


Cleanliness requirement:

Class: K00 according JED-593

Area: for the whole part (Special agreements possible; to be agreed with Product Engineering)

Material:

- ① CuZn
- ② PA (inner components)
- ③ EPDM




General Specification : JED-762 ; JED-622 ; JED-220

Engineering related agreements with Supplier have to be mentioned in the "Release of Supplier"

For use in application in compressed air systems in commercial vehicles :

- with Polyamid or Hytrel tubes acc. ISO7628; DIN74324, DIN73378
- with compressed air acc. JED-848
- at working conditions (consider tube spec.) :

- -40 °C ... 100 °C
- max. 12,5 bar



General Specification: JED-334-1, Size ISO 14405 LP				Copyright WABCO®		<b>WABCO</b>						
Further Technical Data:				Date	Signature							
Doc. Code:		Sheet:		To		Screw-in Fitting						
General Tolerances				2019-11-28		Balago						
Range of Nominal Dimensions ( ± mm)				Checked		2019-12-11						
				Expert		Szczulkowski						
				Szczulkowski								
Class	1)	≤ 50	> 50 ≤ 180	> 180 ≤ 400	> 400	Mass	Scale	Material No.	Date of first issue: 2007-01-16			
Fine	X	0.5	1.0	1.5	2.0	0.028 KG	2:1 1:1	893 800 007 2	Doc.Code	Language	Sheet	
Medium		1.0	2.0	3.0	4.0	A 3	CREO		005	EN	1/1	
Coarse		2.0	3.5	5.0	6.5				502571	2 x B	5790	Replacement for
Tapped Holes acc. -				1) Tolerance Class Applied Crossmarked		Size		ECN-No.	Revision	Techn. Resp.		

