



P502465

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	93 mm (3.66 inch)
Thread Size	M22 x 1.5
Length	165 mm (6.50 inch)
Gasket OD	89 mm (3.50 inch)
Gasket ID	81 mm (3.19 inch)
Efficiency 50%	17 micron
Efficiency Test Std	ISO 16889
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	1 bar (15 psi)
-------------------------	----------------

Media Type	Cellulose
------------	-----------

Collapse Burst	6.9 bar (100 psi)
----------------	-------------------

Type	Full-Flow
------	-----------

Style	Spin-On
-------	---------

Primary Application	JCB 32004133
---------------------	--------------

Packaged Dimensions

Packaged Length	4.1 IN
-----------------	--------

Packaged Width	4.1 IN
----------------	--------

Packaged Height	6.8IN
-----------------	-------

Packaged Weight	1.455 LB
-----------------	----------

Packaged Volume	0.0662 FT3
-----------------	------------

Other Information

Country of Origin	Indonesia
-------------------	-----------

NMFC Code	069100-05
-----------	-----------

HTS Code	8421230090
----------	------------

UPC Code	742330202456
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.