

## **Product Specifications**



## P554407 LUBE FILTER, SPIN-ON FULL FLOW

## Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

• Keep oil clean by capturing contaminants that cause engine damage.

• Include heavy duty components that are built to perform, built to last.

• Deliver essential engine protection for maximum cold flow performance.

## Attributes

Outer Diameter	93 mm (3.66 inch)
Thread Size	3/4-16 UN
Length	174 mm (6.85 inch)
Gasket OD	72 mm (2.83 inch)
Gasket ID	63 mm (2.48 inch)
Efficiency 99%	48 micron
Anti-Drainback Valve	Yes
Bypass Valve	Yes
Bypass Valve Setting LR	0.8 bar (12 psi)

Media Type	Cellulose
Collapse Burst	6.9 bar (100 psi)
Туре	Full-Flow
Style	Spin-On
Primary Application	PERKINS 2654407
Packaged Dimensions	
Packaged Length	3.9996 IN
Packaged Width	3.9 IN
Packaged Height	7.2996IN
Packaged Weight	1.265 LB
Packaged Volume	0.0659 FT3
Other Information	
Country of Origin	Indonesia
NMFC Code	069100-06
HTS Code	8421230090
UPC Code	742330081679

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.