



Product Specification

WF2096

Water, Spin-On

Choose Fleetguard® WF2096 non-chemical water filter for coolant system protection that provides filtration only. Non-chemical water filters are designed for use with OAT technology (which doesn't require DCA's for maintenance) or Hybrid and Conventional systems using liquid DCA's for reinhibition.



Length	138.33 mm
COOLANT ADDITIVE FORM	PELLET
Thread Size	M16 X 1.5-6H INT
Largest OD	93.47 mm
Additive Base	DCA2
Gasket Inside Diameter	62.53 mm
Gasket OD	71.98 mm
Seam OD	93.47 mm
Chemical Additive	DCA2 (MODIFIED)

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved