

## PRODUCTION COMPOUND

**BESTOLIFE® 2000®**

5 Gallon Plastic Pail

**PRODUCT CHARACTERISTICS**

<b>Color:</b>	Dark Copper
<b>Penetration:</b> (ASTM D217)	310 - 340
<b>NLGI Grade:</b>	1
<b>Weight/Gallon:</b>	10.4 pounds/gallon
<b>Thickener:</b>	Lithium
<b>Fluid Type:</b>	Petroleum
<b>Particle Size:</b>	<450 microns
<b>Dropping Point:</b> (ASTM D2265)	≥350°F (≥177°C)
<b>Flash Point:</b>	≥392°F (≥200°C)
<b>Brushable To:</b>	10°F (-12°C)
<b>Service Rating:</b>	500°F (260°C)
<b>Friction Factor:</b>	.9*
<b>Salt Spray Test:</b> (ASTM B117)	1,250 hours
<b>Shelf Life:</b> (Unopened container)	4 years
<b>Contains:</b>	PTFE, other inert nonmetallic solids and <4% copper flake

\*The proper field torque for all API casing and tubing connections should be determined by following the procedures outlined in API RP 5C1: "Recommended Practice for Care and Use of Casing and Tubing."

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

Note: All package sizes are not listed. Call your sales representative for a complete listing.

**DESCRIPTION**

BESTOLIFE® 2000® is a lead-free, zinc-free thread compound for casing, tubing, and line pipe. It is stable in high-pressure and high-temperature conditions. An excellent running compound, 2000® also provides superior protection for long-term storage.

**APPLICATIONS**

Premium lead-free API alternative for casing, tubing, and line pipe; contains no lead or zinc. Formulated for use in high temp steam injection service.

**TECHNICAL DATA**

BESTOLIFE® 2000® will meet or exceed the listed performance objectives in API RP 5A3. The major solid components are a proprietary blend of nonmetallic materials that are inert to chemical attack, such as occurs in sour gas environments and with CO<sub>2</sub> injection. Contains a high-quality lubricating base grease formulated with H<sub>2</sub>S and oxidation inhibitors. BESTOLIFE® 2000® also addresses one of the major concerns in pipe yards and threading operations today: rejects due to pitting and corrosion. In a salt fog spray test, 2000® demonstrated corrosion protection that exceeds the performance of the leading storage compound in the industry. BESTOLIFE® 2000® conforms to API RP 5A3 evaporation, gas evolution, oil separation, water leaching, copper corrosion and cold application at 19.4°F (-7°C) requirements.

**PACKAGING**

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
615009	1 gallon	9 pounds plastic
615018	2 gallon	18 pounds plastic
615030	3 1/2 gallon	30 pounds plastic
615045	5 gallon	45 pounds plastic



**BESTOLIFE®**  
PREMIUM COMPOUNDS

2126 Vanco Dr. • Irving, TX 75061 • (855) 243-9164

**BESTOLIFE.COM**