

BESTOLIFE 2000® AG



5 Gallon Plastic Pail

PRODUCT CHARACTERISTICS

Color:	Dark Copper
Penetration: (ASTM D217)	320 - 340
NLGI Grade:	1
Weight/Gallon:	10.7 pounds/gallon
Thickener:	Calcium 12 Hydroxy
Fluid Type:	Petroleum
Dropping Point: (ASTM D2265)	≥300°F (≥149°C)
Flash Point:	≥325°F (≥162°C)
Brushable To:	-40°F (-40°C)
Service Rating:	400°F (204°C)
Friction Factor:	.9*
Contains:	Inert nonmetallic solids and <4% copper flake

*API RP 7A1: "Recommended Practice for Testing of Thread Compound for Rotary Shouldered Connections"

Note: Due to operation and equipment variables, this value may require adjustment based on field experience.

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

DESCRIPTION

BESTOLIFE 2000® AG (Arctic Grade) is a lead-free, zinc-free thread compound for casing, tubing, and line pipe that applies smoothly at cold temperatures. An excellent running compound, 2000® AG (Arctic Grade) also provides superior storage protection.

APPLICATIONS

Premium arctic grade thread compound for casing, tubing, and line pipe.

TECHNICAL DATA

Extensive controlled testing, including full-scale make and break and sustained gas pressure tests on the same solids formulations found in the "2000®" series of products, indicates that 2000® AG (Arctic Grade) will meet or exceed the listed performance objectives in API RP 5A3. The major solid components of 2000® AG (Arctic Grade) are a proprietary blend of nonmetallic materials that are inert to chemical attack, such as occurs in sour gas environments and with CO2 injection.

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
615014	2 gallon	18 pounds metal
615015	2 gallon	18 pounds plastic
615032	3 1/2 gallon	30 pounds metal
615047	5 gallon	45 pounds plastic

Note: All package sizes are not listed. Call your sales representative for a complete listing.



BESTOLIFE
PREMIUM COMPOUNDS

2777 N. Stemmons Fwy, Suite 1800 • Dallas, TX 75207 • (855) 243-9164

BESTOLIFE.COM