

## DRILLING COMPOUND

**BESTOLIFE® No. 270®**

3 1/2 Gallon Metal Pail

**PRODUCT CHARACTERISTICS**

<b>Color:</b>	Black
<b>Penetration:</b> (ASTM D217)	290-310
<b>NLGI Grade:</b>	1.5
<b>Weight/Gallon:</b>	19.6 pounds/gallon
<b>Thickener:</b>	Lithium
<b>Fluid Type:</b>	Petroleum
<b>Dropping Point:</b> (ASTM D2265)	≥350°F (≥177°C)
<b>Flash Point:</b>	≥392°F (≥200°C)
<b>Brushable To:</b>	10°F (-12°C)
<b>Service Rating:</b>	500°F (260°C)
<b>Friction Factor:</b>	1.0*
<b>Shelf Life:</b> (Unopened container)	4 years
<b>Contains:</b>	Over 60% metallic lead and other nonmetallic additives

\*NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

Note: All package sizes are not listed. Call your sales representative for a complete listing.

**DESCRIPTION**

The original BESTOLIFE® No. 270® is a patented formulation for rotary-shouldered connections. It combats galling, seizing, and downhole makeup.

**APPLICATIONS**

Premium drill collar compound provides maximum protection. Recommended for drill collars, tool joints, casing, tubing, pipe joints, studs, bolts, nuts and screws, gaskets, high temperature flange connections, pumps, exhaust lines and pipeline connections.

**TECHNICAL DATA**

BESTOLIFE® No. 270® is a superior thread compound that contains over 60% pure metallic lead and special non metallic additives. This premium compound provides maximum protection of drill collars, drill pipe and all threaded connections, except oxygen lines. BESTOLIFE® No. 270® provides a stable seal under all conditions and is not attacked by H<sub>2</sub>S or drilling fluids.

**NOTES**

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

**PACKAGING**

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
600114	1 gallon	14 pounds plastic
600150	3 1/2 gallon	50 pounds metal



**BESTOLIFE®**  
PREMIUM COMPOUNDS

2777 N. Stemmons Fwy, Suite 1800 • Dallas, TX 75207 • (855) 243-9164

**BESTOLIFE.COM**