



Version Revision Date: SDS Number: Date of last issue: 10/01/2018 1.12 10/11/2018 130217-00012 Date of first issue: 05/27/2015

SECTION 1. IDENTIFICATION

Product name : 3010® ULTRA

Other means of identification : No data available

SDS-Identcode : 379G

Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation

Address : 2777 N. Stemmons Frwy Ste 1800

Dallas TX 75207,

Telephone : 855-243-9164/972-865-8961

Telefax : 214-631-3047 E-mail address : www.bestolife.com

Recommended use of the chemical and restrictions on use

Recommended use : Industrial use

Thread Compound (Pipe Dope) and Jacking grease for use in

Offshore industries

Mining, (without offshore industries)

Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-

pheres.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Graphite	7782-42-5	>= 30 - < 60
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 30 - < 60
Talc	14807-96-6	>= 10 - < 30
Quartz	14808-60-7	>= 1 - < 5
Boric acid	10043-35-3	>= 0.1 - < 1

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.





Revision Date: SDS Number: Date of last issue: 10/01/2018 Version 130217-00012 Date of first issue: 05/27/2015 1.12 10/11/2018

Get medical attention if symptoms occur.

In case of skin contact Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed If swallowed, DO NOT induce vomiting.

> Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

Notes to physician

None known.

delaved

Protection of first-aiders No special precautions are necessary for first aid responders.

Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides

Metal oxides Silicon oxides

Specific extinguishing meth-

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to





Version Revision Date: SDS Number: Date of last issue: 10/01/2018 1.12 10/11/2018 130217-00012 Date of first issue: 05/27/2015

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure

assessment

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Graphite	7782-42-5	TWA (Res- pirable)	2 mg/m³	CA BC OEL
		TWA (Res- pirable)	2 mg/m³	CA AB OEL
		TWAEV (respirable dust)	2 mg/m³	CA QC OEL
		TWA (Respirable fraction)	2 mg/m³	ACGIH
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	TWA (Mist)	5 mg/m³	CA AB OEL
		STEL (Mist)	10 mg/m³	CA AB OEL
		TWAEV (Mist)	5 mg/m³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m³	CA BC OEL
		TWA (Inhalable fraction)	5 mg/m³	ACGIH
Talc	14807-96-6	TWAEV (respirable dust)	3 mg/m³	CA QC OEL
		TWA (Res- pirable par- ticulates)	2 mg/m³	CA AB OEL
		TWA (Res- pirable)	2 mg/m³	CA BC OEL





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/01/2018

 1.12
 10/11/2018
 130217-00012
 Date of first issue: 05/27/2015

		TWA	2 fibres per cubic centimeter	CA ON OEL
		TWA (Res- pirable frac- tion)	2 mg/m³	CA ON OEL
		TWA (Respirable fraction)	2 mg/m³	ACGIH
Quartz	14808-60-7	TWA (Res- pirable par- ticulates)	0.025 mg/m³	CA AB OEL
		TWA (Res- pirable frac- tion)	0.1 mg/m³	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m³	CA QC OEL
		TWÁ (Res- pirable)	0.025 mg/m³ (Silica)	CA BC OEL
		TWA (Respirable fraction)	0.025 mg/m³ (Silica)	ACGIH
Boric acid	10043-35-3	TWA (Inhal- able)	2 mg/m³ (Borate)	CA BC OEL
		STEL (Inhal- able)	6 mg/m³ (Borate)	CA BC OEL
		TWA (Inhalable fraction)	2 mg/m³ (Borate)	ACGIH
		STEL (Inhalable fraction)	6 mg/m³ (Borate)	ACGIH

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz

Engineering measures : Minimize workplace exposure concentrations.

Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m3 - total dust, 5 mg/m3 - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m3 - respirable particles, 10 mg/m3 -

inhalable particles.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapor type





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/01/2018

 1.12
 10/11/2018
 130217-00012
 Date of first issue: 05/27/2015

Hand protection

Remarks : Wash hands before breaks and at the end of workday. Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection

on : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Viscous semi-solid

Color : black Odor : Petroleum

Odor Threshold : No data available

pH : Not applicable (not an aqueous solution)

Melting point/freezing point : No data available

Initial boiling point and boiling

range

208 °C

Method: ASTM D 2887

Distillates (petroleum), hydrotreated light naphthenic

Flash point : $> 150 \, ^{\circ}\text{C}$

Method: Cleveland open cup

Distillates (petroleum), hydrotreated light naphthenic

Evaporation rate : < 1

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 1.3

Density : No data available

Solubility(ies)

Water solubility : negligible

Partition coefficient: n-

octanol/water

Not applicable





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/01/2018

 1.12
 10/11/2018
 130217-00012
 Date of first issue: 05/27/2015

Autoignition temperature : 407 °C

Method: ASTM E 659

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 18.17 cSt (40 °C)

Distillates (petroleum), hydrotreated light naphthenic

1.817 mm²/s (40 °C)

Distillates (petroleum), hydrotreated light naphthenic

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reac- : Can react with strong oxidizing agents.

tions

Conditions to avoid : None known.
Incompatible materials : Oxidizing agents

Hazardous decomposition : Oxidizing agents

Hazardous decomposition : No hazardous decomposition products are known.

products

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Graphite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l

Exposure time: 4 h





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/01/2018

 1.12
 10/11/2018
 130217-00012
 Date of first issue: 05/27/2015

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Distillates (petroleum), hydrotreated light naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Boric acid:

Acute oral toxicity : LD50 (Rat): 3,450 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.03 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Graphite:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Distillates (petroleum), hydrotreated light naphthenic:

Species : Rabbit





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/01/2018

 1.12
 10/11/2018
 130217-00012
 Date of first issue: 05/27/2015

Result : No skin irritation

Talc:

Species : Rabbit

Result : No skin irritation

Boric acid:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Graphite:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Distillates (petroleum), hydrotreated light naphthenic:

Species : Rabbit

Result : No eye irritation

Talc:

Species : Rabbit

Result : No eye irritation

Boric acid:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Graphite:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact
Species : Mouse
Result : negative

Distillates (petroleum), hydrotreated light naphthenic:

Test Type : Buehler Test





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/01/2018

 1.12
 10/11/2018
 130217-00012
 Date of first issue: 05/27/2015

Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Talc:

Routes of exposure : Skin contact Species : Humans Result : negative

Boric acid:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Distillates (petroleum), hydrotreated light naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/01/2018

 1.12
 10/11/2018
 130217-00012
 Date of first issue: 05/27/2015

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro

Species: Rat

Application Route: Ingestion

Result: negative

Boric acid:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: equivocal

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assess-

ment

Petroleum distillates have been classified as not carcinogenic

based on DMSO extract content < 3% (Regulation (EC)

1272/2008, Annex VI, Part 3, Note L).

Components:

Distillates (petroleum), hydrotreated light naphthenic:

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Result : negative

Talc:

Species : Mouse

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 Years
Result : negative

Quartz:

Species : Humans

Application Route : inhalation (dust/mist/fume)

Result : positive

Remarks : IARC: (International Agency for Research on Cancer)

These substance(s) are inextricably bound in the product and

therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assess- : Positive evidence from human epidemiological studies (inhala-





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/01/2018

 1.12
 10/11/2018
 130217-00012
 Date of first issue: 05/27/2015

ment tion)

Boric acid:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Distillates (petroleum), hydrotreated light naphthenic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Skin contact

Result: negative

Talc:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Boric acid:

Effects on fertility : Test Type: Three-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: positive





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/01/2018

 1.12
 10/11/2018
 130217-00012
 Date of first issue: 05/27/2015

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rabbit

Application Route: Ingestion

Result: positive

Reproductive toxicity - As-

sessment

Clear evidence of adverse effects on sexual function and fertility, based on animal experiments., Clear evidence of

adverse effects on development, based on animal

experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:

Quartz:

Routes of exposure : inhalation (dust/mist/fume)

Target Organs : Lungs

Assessment : Shown to produce significant health effects in animals at con-

centrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Distillates (petroleum), hydrotreated light naphthenic:

Species : Rabbit
NOAEL : 1,000 mg/kg
Application Route : Skin contact
Exposure time : 4 Weeks

Method : OECD Test Guideline 410

Quartz:

Species : Humans LOAEL : 0.053 mg/m³

Application Route : inhalation (dust/mist/fume)

Remarks : These substance(s) are inextricably bound in the product and

therefore do not contribute to a dust inhalation hazard.

Boric acid:

Species : Rat

NOAEL : 100 mg/kg

LOAEL : 334 mg/kg

Application Route : Ingestion

Exposure time : 2 y

Aspiration toxicity

Not classified based on available information.





Version Revision Date: SDS Number: Date of last issue: 10/01/2018 10/11/2018 130217-00012 Date of first issue: 05/27/2015 1.12

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Graphite:

Toxicity to fish LL50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): >

100 ma/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

EC50: > 1,012.5 mg/l Toxicity to microorganisms

Exposure time: 3 h

Method: OECD Test Guideline 209

Distillates (petroleum), hydrotreated light naphthenic:

Toxicity to fish LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Toxicity to algae NOELR (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

NOEC (Daphnia magna (Water flea)): 10 mg/l

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

Exposure time: 21 d

Toxicity to microorganisms NOEC (Photobacterium phosphoreum): > 2.17 mg/l

Exposure time: 4 d





Version Revision Date: SDS Number: Date of last issue: 10/01/2018 10/11/2018 130217-00012 Date of first issue: 05/27/2015 1.12

Talc:

Toxicity to fish LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l

Exposure time: 24 h

Quartz:

Ecotoxicology Assessment

Acute aquatic toxicity No toxicity at the limit of solubility.

Chronic aquatic toxicity No toxicity at the limit of solubility.

Boric acid:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): 74 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Ceriodaphnia dubia (water flea)): 102 mg/l

Exposure time: 48 h

Toxicity to algae EC50 (Pseudokirchneriella subcapitata (green algae)): 52.4

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 17.5

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Danio rerio (zebra fish)): 6.4 mg/l

NOEC (Daphnia magna (Water flea)): 10.8 mg/l

Exposure time: 34 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

Exposure time: 21 d

ic toxicity) Toxicity to microorganisms

EC10: 35.4 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Persistence and degradability

Components:

Distillates (petroleum), hydrotreated light naphthenic:

Biodegradability Result: Not readily biodegradable.

Biodegradation: 2 - 8 % Exposure time: 28 d

Method: OECD Test Guideline 301B





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/01/2018

 1.12
 10/11/2018
 130217-00012
 Date of first issue: 05/27/2015

Bioaccumulative potential

Components:

Boric acid:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): <= 3.2 Method: OECD Test Guideline 305

Partition coefficient: n-

octanol/water

: log Pow: -1.09

Mobility in soilNo data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or

death.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/01/2018

 1.12
 10/11/2018
 130217-00012
 Date of first issue: 05/27/2015

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

AICS : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average CA BC OEL / STEL : short-term exposure limit

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/01/2018

 1.12
 10/11/2018
 130217-00012
 Date of first issue: 05/27/2015

Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety

Data Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 10/11/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8