

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

### SECTION 1. IDENTIFICATION

Product name : 3010® ULTRA  
SDS-Identcode : 379G

#### Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation  
Address : 2777 N. Stemmons Frwy Ste 1800  
Dallas TX 75207,  
Telephone : 855-243-9164/972-865-8961  
Telefax : 214-631-3047  
Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887  
(24-hours/7 days)  
E-mail address : www.bestolife.com

#### Recommended use of the chemical and restrictions on use

Recommended use : Industrial use  
Thread Compound (Pipe Dope) and Jacking grease for use in  
Offshore industries  
Mining, (without offshore industries)  
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-  
pheres.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Not a hazardous substance or mixture.

#### GHS label elements

Not a hazardous substance or mixture.

#### Other hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Graphite	7782-42-5	>= 30 - < 50
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 30 - < 50
Talc	14807-96-6	>= 10 - < 20
Dolomite	16389-88-1	>= 1 - < 5
Quartz	14808-60-7	>= 1 - < 5
Boric acid	10043-35-3	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Metal oxides  
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items
-

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Graphite	7782-42-5	TWA (Respirable)	2.5 mg/m <sup>3</sup>	NIOSH REL
		TWA (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIH
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
Talc	14807-96-6	ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	2 mg/m <sup>3</sup>	NIOSH REL
Dolomite	16389-88-1	TWA (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable)	5 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup> (Calcium car-	NIOSH REL

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
 Date of first issue: 05/27/2015

Quartz	14808-60-7	TWA (Respirable dust)	0.05 mg/m <sup>3</sup> bonate)	OSHA Z-1
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup> (Silica)	NIOSH REL
Boric acid	10043-35-3	TWA (Inhalable fraction)	2 mg/m <sup>3</sup> (Borate)	ACGIH
		STEL (Inhalable fraction)	6 mg/m <sup>3</sup> (Borate)	ACGIH

**These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.**

Quartz

**Engineering measures** : Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m<sup>3</sup> - total dust, 5 mg/m<sup>3</sup> - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m<sup>3</sup> - respirable particles, 10 mg/m<sup>3</sup> - inhalable particles.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Hand protection**

**Remarks** : Wash hands before breaks and at the end of workday.  
**Eye protection** : Wear the following personal protective equipment:  
 Safety glasses  
**Skin and body protection** : Skin should be washed after contact.  
**Hygiene measures** : Ensure that eye flushing systems and safety showers are located close to the working place.

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Viscous semi-solid  
Color : black  
Odor : Petroleum  
Odor Threshold : No data available

pH : Not applicable (not an aqueous solution)

Melting point/freezing point : No data available

Initial boiling point and boiling range : 406 °F / 208 °C  
Method: ASTM D 2887  
Distillates (petroleum), hydrotreated light naphthenic

Flash point : > 302 °F / > 150 °C  
  
Method: Cleveland open cup  
Distillates (petroleum), hydrotreated light naphthenic

Evaporation rate : < 1

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 1.3

Density : No data available

Solubility(ies)  
Water solubility : negligible

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : 765 °F / 407 °C  
Method: ASTM E 659

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : No data available  
  
Viscosity, kinematic : 18.17 cSt (104 °F / 40 °C)

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

Distillates (petroleum), hydrotreated light naphthenic

1.817 mm<sup>2</sup>/s (104 °F / 40 °C)

Distillates (petroleum), hydrotreated light naphthenic

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### Graphite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 423  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

##### Distillates (petroleum), hydrotreated light naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h

---

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

### **Talc:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

### **Dolomite:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### **Quartz:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

### **Boric acid:**

Acute oral toxicity : LD50 (Rat): 3,450 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.03 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

### **Skin corrosion/irritation**

Not classified based on available information.

#### **Components:**

##### **Graphite:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

##### **Distillates (petroleum), hydrotreated light naphthenic:**

Species : Rabbit  
Result : No skin irritation

##### **Talc:**

Species : Rabbit  
Result : No skin irritation

##### **Dolomite:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

##### **Boric acid:**

Species : Rabbit  
Result : No skin irritation

### **Serious eye damage/eye irritation**

Not classified based on available information.

#### **Components:**

##### **Graphite:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

##### **Distillates (petroleum), hydrotreated light naphthenic:**

Species : Rabbit  
Result : No eye irritation

##### **Talc:**

Species : Rabbit  
Result : No eye irritation

##### **Dolomite:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405



**3010® ULTRA**

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

Remarks : Based on data from similar materials

**Boric acid:**

Species : Rabbit  
Result : No eye irritation

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:****Graphite:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Result : negative

**Distillates (petroleum), hydrotreated light naphthenic:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

**Talc:**

Routes of exposure : Skin contact  
Species : Humans  
Result : negative

**Dolomite:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative  
Remarks : Based on data from similar materials

**Boric acid:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

**Germ cell mutagenicity**

Not classified based on available information.

**3010® ULTRA**

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

**Components:****Graphite:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

**Distillates (petroleum), hydrotreated light naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

**Talc:**

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA syn-  
thesis in mammalian cells (in vitro)  
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro  
Species: Rat  
Application Route: Ingestion  
Result: negative

**Dolomite:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

**Boric acid:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: equivocal

Test Type: Chromosome aberration test in vitro  
Result: negative

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

#### **Product:**

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

#### **Components:**

##### **Distillates (petroleum), hydrotreated light naphthenic:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 78 weeks  
Result : negative

##### **Talc:**

Species : Mouse  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Result : negative

##### **Quartz:**

Species : Humans  
Application Route : inhalation (dust/mist/fume)  
Result : positive  
Remarks : IARC: (International Agency for Research on Cancer)  
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

##### **Boric acid:**

Species : Mouse  
Application Route : Ingestion  
Exposure time : 103 weeks  
Result : negative

**IARC**      Group 1: Carcinogenic to humans  
Quartz      14808-60-7  
(Silica dust, crystalline)

**OSHA**      No component of this product present at levels greater than or equal to 0.1% is

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

on OSHA's list of regulated carcinogens.

**NTP**      Known to be human carcinogen      14808-60-7  
Quartz  
(Silica, Crystalline (Respirable Size))

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **Graphite:**

Effects on fertility      :    Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development    :    Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

#### **Distillates (petroleum), hydrotreated light naphthenic:**

Effects on fertility      :    Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development    :    Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Skin contact  
Result: negative

#### **Talc:**

Effects on fetal development    :    Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

#### **Dolomite:**

Effects on fertility      :    Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

### **Boric acid:**

Effects on fertility : Test Type: Three-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: positive

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rabbit  
Application Route: Ingestion  
Result: positive

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, based on animal experiments., Clear evidence of adverse effects on development, based on animal experiments.

### **STOT-single exposure**

Not classified based on available information.

### **STOT-repeated exposure**

Not classified based on available information.

### **Components:**

#### **Quartz:**

Routes of exposure : inhalation (dust/mist/fume)  
Target Organs : Lungs  
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

### **Repeated dose toxicity**

### **Components:**

#### **Distillates (petroleum), hydrotreated light naphthenic:**

Species : Rabbit  
NOAEL : 1,000 mg/kg  
Application Route : Skin contact  
Exposure time : 4 Weeks  
Method : OECD Test Guideline 410

#### **Dolomite:**

Species : Mouse  
NOAEL : 1,300 mg/kg

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

Application Route : Ingestion  
Exposure time : 28 Days  
Remarks : Based on data from similar materials

### Quartz:

Species : Humans  
LOAEL : 0.053 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

### Boric acid:

Species : Rat  
NOAEL : 100 mg/kg  
LOAEL : 334 mg/kg  
Application Route : Ingestion  
Exposure time : 2 y

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### Graphite:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,012.5 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

---

**3010® ULTRA**

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
6.5	10/11/2018	130237-00013	Date of first issue: 05/27/2015

---

**Distillates (petroleum), hydrotreated light naphthenic:**

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Test substance: Water Accommodated Fraction
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h  
 Test substance: Water Accommodated Fraction
- Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
 Exposure time: 72 h  
 Test substance: Water Accommodated Fraction
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
 Exposure time: 21 d
- Toxicity to microorganisms : NOEC (Photobacterium phosphoreum): > 2.17 mg/l  
 Exposure time: 4 d

**Talc:**

- Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l  
 Exposure time: 24 h

**Dolomite:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 16.6 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203  
 Remarks: No toxicity at the limit of solubility.  
 Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 16.6 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202  
 Remarks: No toxicity at the limit of solubility.  
 Based on data from similar materials
- Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): 14 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials

**Quartz:****Ecotoxicology Assessment**

- Acute aquatic toxicity : No toxicity at the limit of solubility.
- Chronic aquatic toxicity : No toxicity at the limit of solubility.

**Boric acid:**

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 74 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 102 mg/l  
Exposure time: 48 h
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 52.4 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 17.5 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): 6.4 mg/l  
Exposure time: 34 d  
Method: OECD Test Guideline 210
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10.8 mg/l  
Exposure time: 21 d
- Toxicity to microorganisms : EC10: 35.4 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

### Persistence and degradability

#### Components:

#### **Distillates (petroleum), hydrotreated light naphthenic:**

- Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 8 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

### Bioaccumulative potential

#### Components:

#### **Boric acid:**

- Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): <= 3.2  
Method: OECD Test Guideline 305

- Partition coefficient: n-octanol/water : log Pow: -1.09

#### **Mobility in soil**

No data available

#### **Other adverse effects**

No data available



# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

---

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know

##### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

##### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# SAFETY DATA SHEET



## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

### US State Regulations

#### Pennsylvania Right To Know

Graphite	7782-42-5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Decanoic acid, mixed esters with heptanoic acid, isovaleric acid, octanoic acid and pentaerythritol	68130-51-8
Talc	14807-96-6
Dolomite	16389-88-1
Calcium(2+) 12-hydroxyoctadecanoate	3159-62-4
Quartz	14808-60-7

#### California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California List of Hazardous Substances

Graphite	7782-42-5
Talc	14807-96-6

#### California Permissible Exposure Limits for Chemical Contaminants

Graphite	7782-42-5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Talc	14807-96-6
Quartz	14808-60-7

#### California Regulated Carcinogens

Quartz	14808-60-7
--------	------------

#### The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

AICS : All ingredients listed or exempt.

# SAFETY DATA SHEET




## 3010® ULTRA

Version 6.5      Revision Date: 10/11/2018      SDS Number: 130237-00013      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA 704:



Special hazard.

##### HMIS® IV:

HEALTH	/	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Pre-

# SAFETY DATA SHEET



## 3010® ULTRA

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
6.5	10/11/2018	130237-00013	Date of first issue: 05/27/2015

---

vention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/11/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8