

DRILLING COMPOUND

BESTOLIFE 60% LEAD BASE



3 1/2 Gallon Metal Pail

PRODUCT CHARACTERISTICS

Color:	Black
Penetration: (ASTM D217)	290-310
NLGI Grade:	1.5
Weight/Gallon:	19.6 pounds/gallon
Thickener:	Lithium
Fluid Type:	Petroleum
Dropping Point: (ASTM D2265)	≥350°F (≥177°C)
Flash Point:	≥392°F (≥200°C)
Brushable To:	10°F (-12°C)
Service Rating:	500°F (260°C)
Friction Factor:	1.0*
Shelf Life: (Unopened container)	4 years
Contains:	60% lead and other nonmetallic additives

*API RP 7A1: "Recommended Practice for Testing of Thread Compound for Rotary-Shouldered Connections" NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

DESCRIPTION

When budget is a factor, BESTOLIFE 60% Lead Base is the compound for you. Designed for use on drill collars and drill pipe, the economical 60% Lead Base resists H₂S and drilling fluids.

APPLICATIONS

Economical drill collar compound.

TECHNICAL DATA

BESTOLIFE 60% Lead Base is an economical lead base compound designed for use on drill collars, drill pipe, and other threaded connections. It will provide performance comparable to other more expensive drill collar compounds at a very competitive cost. BESTOLIFE 60% Lead Base contains 60% pure metallic lead blended with other non-metallic additives in a high quality base grease, and is not affected by H₂S or drilling fluids. Meets the requirements of API RP SPEC 7: Specification for Rotary Drill Stem Elements.

NOTES

BESTOLIFE 60% Lead Base meets all applicable API and IADC standards.

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
600850	3 1/2 gallon	50 pounds metal

Note: All package sizes are not listed. Call your sales representative for a complete listing.



BESTOLIFE
PREMIUM COMPOUNDS

2777 N. Stemmons Fwy, Suite 1800 • Dallas, TX 75207 • (855) 243-9164

BESTOLIFE.COM