

60% LEAD BASE

Version	Revision Date:	SDS Number:	Date of last issue: 24.07.2018
7.0	01.10.2018	104397-00018	Date of first issue: 29.04.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : 60% LEAD BASE

SDS-Identcode : 034G

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Industrial use, Thread Compound (Pipe Dope) and Jacking grease for use in Offshore industries, Mining, (without offshore industries)

Recommended restrictions on use : Do not use on oxygen lines or in oxygen enriched atmospheres.

1.3 Details of the supplier of the safety data sheet

Company : Bestolife Corporation INTERTEK FRANCE
2777 N. Stemmons Frwy 27400 HEUDEBOUVILLE
DALLAS, TX 75207, FRANCE

Telephone : 855-243-9164/972-865-8961 +33 385 991270

Telefax : 214-631-3047 +33 385 991288

E-mail address of person responsible for the SDS : www.bestolife.com/christian.gimenez@intertek.com/if.reach@intertek.com

1.4 Emergency telephone number

CHEMTREC: +(44)-870-8200418; Interntnl: +1-703-527-3887 NHS Drct: +44 0845 4647
(Medical only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)


Reproductive toxicity, Category 1A	H360FD: May damage fertility. May damage the unborn child.
Effects on or via lactation	H362: May cause harm to breast-fed children.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

60% LEAD BASE

Version 7.0 Revision Date: 01.10.2018 SDS Number: 104397-00018 Date of last issue: 24.07.2018
Date of first issue: 29.04.2015

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H360FD May damage fertility. May damage the unborn child. H362 May cause harm to breast-fed children. H372 Causes damage to organs through prolonged or repeated exposure. H410 Very toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P201 Obtain special instructions before use. P263 Avoid contact during pregnancy and while nursing. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P308 + P313 IF exposed or concerned: Get medical advice/ attention. P391 Collect spillage.

Hazardous components which must be listed on the label:

Lead

Additional Labelling

EUH208 Contains Calcium petroleum sulfonates. May produce an allergic reaction.
Restricted to professional users.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Lead	7439-92-1 231-100-4 082-013-00-1 01-2119513221-59	Repr. 1A; H360FD Lact.H362 STOT RE 1; H372 Aquatic Acute 1; H400	>= 50 - < 70

60% LEAD BASE

Version 7.0 Revision Date: 01.10.2018 SDS Number: 104397-00018 Date of last issue: 24.07.2018
Date of first issue: 29.04.2015

		Aquatic Chronic 1; H410	
Calcium petroleum sulfonates	61789-86-4 263-093-9	Skin Sens. 1B; H317	>= 0.1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May damage fertility. May damage the unborn child.
May cause harm to breast-fed children.
Causes damage to organs through prolonged or repeated exposure.
- May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

60% LEAD BASE

Version	Revision Date:	SDS Number:	Date of last issue: 24.07.2018
7.0	01.10.2018	104397-00018	Date of first issue: 29.04.2015

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Lead compounds
Carbon oxides
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

60% LEAD BASE

Version	Revision Date:	SDS Number:	Date of last issue: 24.07.2018
7.0	01.10.2018	104397-00018	Date of first issue: 29.04.2015

employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Store in accordance with the particular national regulations.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Organic peroxides
Explosives
Gases

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Lead	7439-92-1	TWA	0.15 mg/m ³ (Lead)	98/24/EC I
Further information	Binding			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



60% LEAD BASE

Version 7.0 Revision Date: 01.10.2018 SDS Number: 104397-00018 Date of last issue: 24.07.2018
 Date of first issue: 29.04.2015

Talc	14807-96-6	TWA (Respirable dust)	1 mg/m3	GB EH40
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, Talc is defined as the mineral talc together with other hydrous phyllosilicates including chlorite and carbonate materials which occur with it, but excluding amphibole asbestos and crystalline silica., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			
Graphite	7782-42-5	TWA (inhalable dust)	10 mg/m3	GB EH40
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			
		TWA (Respirable dust)	4 mg/m3	GB EH40
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those</p>			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



60% LEAD BASE

Version 7.0 Revision Date: 01.10.2018 SDS Number: 104397-00018 Date of last issue: 24.07.2018
Date of first issue: 29.04.2015

fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Lead	7439-92-1	Lead (Lead): 40 µg/dl (Blood)		GB EH40 BAT
		Lead (Lead): 50 µg/dl (Blood)		GB EH40 BAT
		Lead (Lead): 30 µg/dl (Blood)		GB EH40 BAT
		Lead (Lead): 50 µg/dl (Blood)		GB EH40 BAT
		Lead (Lead): 60 µg/dl (Blood)		GB EH40 BAT
		Lead (Lead): 25 µg/dl (Blood)		GB EH40 BAT
		Lead (Lead): 0.7 mg/l (Blood)		98/24/EC II

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Graphite	Consumers	Inhalation	Long-term local effects	0.3 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	813 mg/kg bw/day

60% LEAD BASE

Version 7.0 Revision Date: 01.10.2018 SDS Number: 104397-00018 Date of last issue: 24.07.2018
Date of first issue: 29.04.2015

	Workers	Inhalation	Long-term local effects	1.2 mg/m ³
Calcium petroleum sulfonates	Workers	Inhalation	Long-term systemic effects	11.75 mg/m ³
	Workers	Skin contact	Long-term systemic effects	3.33 mg/kg bw/day
	Workers	Skin contact	Long-term local effects	1.03 mg/cm ²
	Consumers	Inhalation	Long-term systemic effects	2.9 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	1.667 mg/kg bw/day
	Consumers	Skin contact	Long-term local effects	0.513 mg/cm ²
	Consumers	Ingestion	Long-term systemic effects	0.8333 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Lead	Fresh water	6.5 µg/l
	Marine water	3.4 µg/l
	Sewage treatment plant	100 µg/l
	Fresh water sediment	174 mg/kg
	Marine sediment	164 mg/kg
	Soil	147 mg/kg
	Oral (Secondary Poisoning)	10.9 mg/kg food
Calcium petroleum sulfonates	Fresh water	1 mg/l
	Marine water	1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	1000 mg/l
	Fresh water sediment	226000000 mg/kg
	Marine sediment	226000000 mg/kg
	Soil	271000000 mg/kg
	Oral (Secondary Poisoning)	16.667 mg/kg food

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety glasses

Hand protection
Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



60% LEAD BASE

Version	Revision Date:	SDS Number:	Date of last issue: 24.07.2018
7.0	01.10.2018	104397-00018	Date of first issue: 29.04.2015

applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Viscous semi-solid
Colour : black
Odour : Petroleum
Odour Threshold : No data available

pH : Not applicable (not an aqueous solution)

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : ≥ 200 °C
Method: ASTM D 92, Cleveland open cup
Distillates (petroleum), hydrotreated heavy naphthenic

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Relative density : 2.3

Density : No data available

Solubility(ies)
Water solubility : negligible

Partition coefficient: n- : Not applicable

60% LEAD BASE

Version	Revision Date:	SDS Number:	Date of last issue: 24.07.2018
7.0	01.10.2018	104397-00018	Date of first issue: 29.04.2015

|| Octanol/water
Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

|| Viscosity, kinematic : Not applicable

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight : No data available

|| Particle size : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



60% LEAD BASE

Version 7.0 Revision Date: 01.10.2018 SDS Number: 104397-00018 Date of last issue: 24.07.2018
Date of first issue: 29.04.2015

Acute toxicity

Not classified based on available information.

Components:

Lead:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Calcium petroleum sulfonates:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 1.9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 4,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Lead:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Calcium petroleum sulfonates:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Lead:

Species : Rabbit
Method : OECD Test Guideline 405

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



60% LEAD BASE

Version	Revision Date:	SDS Number:	Date of last issue: 24.07.2018
7.0	01.10.2018	104397-00018	Date of first issue: 29.04.2015

Result	: No eye irritation
Remarks	: Based on data from similar materials

Calcium petroleum sulfonates:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: No eye irritation
Remarks	: Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Lead:

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

Calcium petroleum sulfonates:

Test Type	: Buehler Test
Exposure routes	: Skin contact
Species	: Guinea pig
Result	: positive

Assessment	: Probability or evidence of low to moderate skin sensitisation rate in humans
------------	--

Germ cell mutagenicity

Not classified based on available information.

Components:

Lead:

Genotoxicity in vitro	: Test Type: In vitro sister chromatid exchange assay in mammalian cells Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Ingestion Result: positive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



60% LEAD BASE

Version 7.0 Revision Date: 01.10.2018 SDS Number: 104397-00018 Date of last issue: 24.07.2018
Date of first issue: 29.04.2015

Remarks: Based on data from similar materials

Calcium petroleum sulfonates:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Reproductive toxicity

May damage fertility. May damage the unborn child.
May cause harm to breast-fed children.

Components:

Lead:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Positive evidence of adverse effects on sexual function and fertility from human epidemiological studies., Positive evidence of adverse effects on development from human epidemiological studies., Studies indicating a hazard to babies during the lactation period

Calcium petroleum sulfonates:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 415
Result: negative

60% LEAD BASE

Version 7.0 Revision Date: 01.10.2018 SDS Number: 104397-00018 Date of last issue: 24.07.2018
Date of first issue: 29.04.2015

Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Components:

Lead:

Target Organs : Kidney, Central nervous system, Blood
Assessment : Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Lead:

Species : Rat
NOAEL : 0.0015 mg/kg
LOAEL : 0.005 mg/kg
Application Route : Ingestion
Exposure time : 6 - 12 Months
Remarks : Based on data from similar materials

Calcium petroleum sulfonates:

Species : Rat
> 1000 mg/kg
Application Route : Skin contact
Exposure time : 28 Days
Method : OECD Test Guideline 410
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Lead:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.107 mg/l
Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 0.029 mg/l
Exposure time: 48 h
Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.025

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



60% LEAD BASE

Version 7.0 Revision Date: 01.10.2018 SDS Number: 104397-00018 Date of last issue: 24.07.2018
Date of first issue: 29.04.2015

	mg/l
	Exposure time: 72 h
	EC10 (Pseudokirchneriella subcapitata (green algae)): 6.1 µg/l
	Exposure time: 72 h
M-Factor (Acute aquatic toxicity)	: 10
Toxicity to fish (Chronic toxicity)	: EC10: 20 µg/l Exposure time: 30 d Species: Pimephales promelas (fathead minnow)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: EC10: 1.7 µg/l Exposure time: 7 d Species: Ceriodaphnia dubia (water flea)
M-Factor (Chronic aquatic toxicity)	: 10

Calcium petroleum sulfonates:

Toxicity to fish	: LL50 (Cyprinodon variegatus (sheepshead minnow)): > 10,000 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials
	NOEC (Pseudokirchneriella subcapitata (green algae)): 1,000 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials
Toxicity to microorganisms	: EC50 : > 10,000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

12.2 Persistence and degradability

Components:

Calcium petroleum sulfonates:

60% LEAD BASE

Version	Revision Date:	SDS Number:	Date of last issue: 24.07.2018
7.0	01.10.2018	104397-00018	Date of first issue: 29.04.2015

||| Biodegradability : Result: Not readily biodegradable.
Biodegradation: 8.6 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

Calcium petroleum sulfonates:

||| Partition coefficient: n- : log Pow: > 6.65
octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 3077
ADR : UN 3077
RID : UN 3077
IMDG : UN 3077
IATA : UN 3077

14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

60% LEAD BASE

Version	Revision Date:	SDS Number:	Date of last issue: 24.07.2018
7.0	01.10.2018	104397-00018	Date of first issue: 29.04.2015

(Lead)

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Lead)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Lead)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Lead)

IATA : Environmentally hazardous substance, solid, n.o.s.
(Lead)

14.3 Transport hazard class(es)

ADN : 9

ADR : 9

RID : 9

IMDG : 9

IATA : 9

14.4 Packing group

ADN
Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9

ADR
Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID
Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9

IMDG
Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)
Packing instruction (cargo aircraft) : 956
Packing instruction (LQ) : Y956
Packing group : III
Labels : Miscellaneous

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



60% LEAD BASE

Version	Revision Date:	SDS Number:	Date of last issue: 24.07.2018
7.0	01.10.2018	104397-00018	Date of first issue: 29.04.2015

IATA (Passenger)

Packing instruction (passenger aircraft)	:	956
Packing instruction (LQ)	:	Y956
Packing group	:	III
Labels	:	Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Lead
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EC) No 850/2004 on persistent organic pollutants	:	Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	:	Lead
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Lead (Number on list 30)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



60% LEAD BASE

Version	Revision Date:	SDS Number:	Date of last issue: 24.07.2018
7.0	01.10.2018	104397-00018	Date of first issue: 29.04.2015

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E1 ENVIRONMENTAL HAZARDS

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

AICS : All ingredients listed or exempt.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H317 : May cause an allergic skin reaction.
H360FD : May damage fertility. May damage the unborn child.
H362 : May cause harm to breast-fed children.
H372 : Causes damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Lact. : Effects on or via lactation
Repr. : Reproductive toxicity
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
98/24/EC I : Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values
98/24/EC II : Chemical Agents Directive - Annex II: Binding biological limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT : UK. Biological monitoring guidance values
98/24/EC I / TWA : Occupational Exposure Limit Value

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



60% LEAD BASE

Version	Revision Date:	SDS Number:	Date of last issue: 24.07.2018
7.0	01.10.2018	104397-00018	Date of first issue: 29.04.2015

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Repr. 1A	H360FD
Lact.	H362
STOT RE 1	H372
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



60% LEAD BASE

Version	Revision Date:	SDS Number:	Date of last issue: 24.07.2018
7.0	01.10.2018	104397-00018	Date of first issue: 29.04.2015

safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN