

PRODUCTION COMPOUND

BESTOLIFE 72733



3 1/2 Gallon Metal Pail

PRODUCT CHARACTERISTICS

Color:	Dark Copper
Penetration: (ASTM D217)	310-340
NLGI Grade:	1
Weight/Gallon:	15.8 pounds/gallon
Thickener:	Lithium
Fluid Type:	Petroleum
Particle Size:	<300 microns
Dropping Point: (ASTM D2265)	≥350°F (≥177°C)
Flash Point: (ASTM D92)	≥325°F (162.8°C)
Brushable To:	0°F (-18°C)
Service Rating:	500°F (260°C)
Friction Factor:	1.0*
Shelf Life: (Unopened container)	4 years
Contains:	Graphite, Lead, Zinc, Copper

*ANSI/API Recommended Practice 5A3: "Recommended Practice on Thread Compounds for Casing, Tubing, Line Pipe and Drill Stem Elements": Third Edition, November 2009.

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

DESCRIPTION

BESTOLIFE 72733 is a high pressure, high temperature thread compound for casing, tubing, and line pipe that exceeds API RP 5A3*/ISO 13678 and obsolete BUL 5A2. It includes a special corrosion inhibitor for superior corrosion resistance as compared to API Modified.

APPLICATIONS

High-pressure thread compound for casing, tubing, and line pipe.

TECHNICAL DATA

BESTOLIFE 72733 exceeds the performance requirements and objectives outlined in API RP 5A3*/ISO 13678 and obsolete BUL 5A2. This superior thread compound protects connections against galling during make-up and breakout, prevents leakage at temperatures in excess of 300° F, and withstands pressure to 10,000 psi. BESTOLIFE 72733 resists water absorption, disintegration and volume changes, and will not harden, dry out, evaporate or oxidize. It contains special corrosion inhibitors to resist pitting and discoloration of threaded surfaces during field use and storage. Bestolife 72733 conforms to Evaporation, Gas Evolution, Oil Separation, Water Leaching, Copper Corrosion and Cold Application at 19.4°F (-7°C). The Salt Spray Corrosion Protection is 900 hours.

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
613150	3 1/2 gallon	50 pounds metal

Note: All package sizes are not listed. Call your sales representative for a complete listing.



BESTOLIFE
PREMIUM COMPOUNDS

2777 N. Stemmons Fwy, Suite 1800 • Dallas, TX 75207 • (855) 243-9164

BESTOLIFE.COM