

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

SECTION 1. IDENTIFICATION

Product name : BLACK JACK
Other means of identification : No data available
SDS-Identcode : 419G

Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation
Address : 2777 N. Stemmons Frwy Ste 1800
Dallas TX 75207,
Telephone : 855-243-9164/972-865-8961
Telefax : 214-631-3047
E-mail address : www.bestolife.com

Recommended use of the chemical and restrictions on use

Recommended use : Industrial use
Thread Compound (Pipe Dope) and Jacking grease for use in
Offshore industries
Mining, (without offshore industries)
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-
pheres.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Eye irritation : Category 2A

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.

Precautionary Statements :

Prevention:

P264 Wash skin thoroughly after handling.
P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|------------|-----------------------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | >= 30 - < 60 |
| Zinc oxide | 1314-13-2 | >= 10 - < 30 |
| Talc | 14807-96-6 | >= 10 - < 30 |
| Graphite | 7782-42-5 | >= 5 - < 10 |
| 12-Hydroxy lithium stearate | 7620-77-1 | >= 1 - < 5 |
| Calcium oxide | 1305-78-8 | >= 1 - < 5 |
| Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) | 57855-77-3 | >= 1 - < 5 |
| Quartz | 14808-60-7 | >= 1 - < 5 |

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

- Unsuitable extinguishing media : Carbon dioxide (CO₂)
Dry chemical
None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Metal oxides
Fluorine compounds
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
-

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
 Date of first issue: 05/18/2015

Materials to avoid : Store in accordance with the particular national regulations.
 : Do not store with the following product types:
 Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--|------------|----------------------------------|--|-----------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | TWA (Mist) | 5 mg/m ³ | CA AB OEL |
| | | STEL (Mist) | 10 mg/m ³ | CA AB OEL |
| | | TWAEV (Mist) | 5 mg/m ³ | CA QC OEL |
| | | STEV (Mist) | 10 mg/m ³ | CA QC OEL |
| | | TWA (Mist) | 1 mg/m ³ | CA BC OEL |
| Zinc oxide | 1314-13-2 | TWA (Inhalable fraction) | 5 mg/m ³ | ACGIH |
| | | TWA (Respirable) | 2 mg/m ³ | CA AB OEL |
| | | STEL (Respirable) | 10 mg/m ³ | CA AB OEL |
| | | TWA (Respirable) | 2 mg/m ³ | CA BC OEL |
| | | STEL (Respirable) | 10 mg/m ³ | CA BC OEL |
| | | TWAEV (Fumes) | 5 mg/m ³ | CA QC OEL |
| | | TWAEV (total dust) | 10 mg/m ³ | CA QC OEL |
| | | STEV (Fumes) | 10 mg/m ³ | CA QC OEL |
| | | TWA (Respirable fraction) | 2 mg/m ³ | ACGIH |
| | | STEL (Respirable fraction) | 10 mg/m ³ | ACGIH |
| Talc | 14807-96-6 | TWAEV (respirable dust) | 3 mg/m ³ | CA QC OEL |
| | | TWA (Respirable particulates) | 2 mg/m ³ | CA AB OEL |
| | | TWA (Respirable) | 2 mg/m ³ | CA BC OEL |
| | | TWA | 2 fibres per cubic centimeter | CA ON OEL |
| | | TWA (Respirable frac- | 2 mg/m ³ | CA ON OEL |

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
 Date of first issue: 05/18/2015

| | | | | |
|-----------------------------|------------|-------------------------------|----------------------------------|-----------|
| | | tion) | | |
| | | TWA (Respirable fraction) | 2 mg/m ³ | ACGIH |
| Graphite | 7782-42-5 | TWA (Respirable) | 2 mg/m ³ | CA BC OEL |
| | | TWA (Respirable) | 2 mg/m ³ | CA AB OEL |
| | | TWAEV (respirable dust) | 2 mg/m ³ | CA QC OEL |
| | | TWA (Respirable fraction) | 2 mg/m ³ | ACGIH |
| 12-Hydroxy lithium stearate | 7620-77-1 | TWA | 10 mg/m ³ | CA AB OEL |
| | | TWA | 10 mg/m ³ | CA BC OEL |
| | | TWA (Inhalable fraction) | 10 mg/m ³ | ACGIH |
| | | TWA (Respirable fraction) | 3 mg/m ³ | ACGIH |
| Calcium oxide | 1305-78-8 | TWA | 2 mg/m ³ | CA AB OEL |
| | | TWA | 2 mg/m ³ | CA BC OEL |
| | | TWAEV | 2 mg/m ³ | CA QC OEL |
| | | TWA | 2 mg/m ³ | ACGIH |
| Quartz | 14808-60-7 | TWA (Respirable particulates) | 0.025 mg/m ³ | CA AB OEL |
| | | TWA (Respirable fraction) | 0.1 mg/m ³ | CA ON OEL |
| | | TWAEV (respirable dust) | 0.1 mg/m ³ | CA QC OEL |
| | | TWA (Respirable) | 0.025 mg/m ³ (Silica) | CA BC OEL |
| | | TWA (Respirable fraction) | 0.025 mg/m ³ (Silica) | ACGIH |

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz

Engineering measures : Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Combined particulates and organic vapor type
- Hand protection
- Material : Chemical-resistant gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Viscous semi-solid
- Color : black
- Odor : Petroleum
- Odor Threshold : No data available
- pH : Not applicable (not an aqueous solution)
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Flash point : ≥ 200 °C
- Method: ASTM D 92, Cleveland open cup
Distillates (petroleum), hydrotreated heavy naphthenic
- Evaporation rate : Not applicable
- Flammability (solid, gas) : Not classified as a flammability hazard
- Upper explosion limit / Upper : No data available
-

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

flammability limit

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 1.4

Density : No data available

Solubility(ies)
Water solubility : negligible

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : Not applicable

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Can react with strong oxidizing agents.
Conditions to avoid : None known.
Incompatible materials : Oxidizing agents
Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Acute toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Zinc oxide:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Talc:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Graphite:

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

12-Hydroxy lithium stearate:

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Calcium oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 425

Acute inhalation toxicity : (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Talc:

Species : Rabbit
Result : No skin irritation

Graphite:

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

12-Hydroxy lithium stearate:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Calcium oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Talc:

Species : Rabbit
Result : No eye irritation

Graphite:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

12-Hydroxy lithium stearate:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Calcium oxide:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Remarks : Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Zinc oxide:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Talc:

Routes of exposure : Skin contact
Species : Humans
Result : negative

Graphite:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

12-Hydroxy lithium stearate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

BLACK JACK

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/01/2018 |
| 4.1 | 10/11/2018 | 119813-00014 | Date of first issue: 05/18/2015 |

Calcium oxide:

| | |
|--------------------|--|
| Test Type | : Local lymph node assay (LLNA) |
| Routes of exposure | : Skin contact |
| Species | : Mouse |
| Method | : OECD Test Guideline 429 |
| Result | : negative |
| Remarks | : Based on data from similar materials |

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

| | |
|--------------------|--|
| Test Type | : Human repeat insult patch test (HRIPT) |
| Routes of exposure | : Skin contact |
| Result | : negative |

Germ cell mutagenicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

| | |
|-----------------------|--|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative |
| Genotoxicity in vivo | : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials |

Zinc oxide:

| | |
|-----------------------|---|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES) Result: positive |
| | Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative |
| | Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: equivocal |
| | Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative |
| | Test Type: Chromosome aberration test in vitro Result: positive |
| | Test Type: in vitro micronucleus test |

BLACK JACK

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/01/2018 |
| 4.1 | 10/11/2018 | 119813-00014 | Date of first issue: 05/18/2015 |

Result: positive

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)

Result: positive

Test Type: In vitro sister chromatid exchange assay in mammalian cells

Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
 Species: Rat
 Application Route: inhalation (dust/mist/fume)
 Method: OECD Test Guideline 474
 Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: inhalation (dust/mist/fume)

Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
 Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
 Species: Rat
 Application Route: Ingestion
 Result: negative

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

BLACK JACK

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/01/2018 |
| 4.1 | 10/11/2018 | 119813-00014 | Date of first issue: 05/18/2015 |

Result: negative

Calcium oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Test Type: Chromosome aberration test in vitro
 Method: OECD Test Guideline 473
 Result: negative
 Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
 Method: OECD Test Guideline 476
 Result: negative
 Remarks: Based on data from similar materials

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative
 Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Mouse
 Application Route : Skin contact
 Exposure time : 78 weeks
 Method : OECD Test Guideline 451
 Result : negative

Zinc oxide:

Species : Mouse
 Application Route : Ingestion
 Exposure time : 1 Years
 Result : negative
 Remarks : Based on data from similar materials

Talc:

Species : Mouse
 Application Route : inhalation (dust/mist/fume)
 Exposure time : 2 Years

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Result : negative

Calcium oxide:

Species : Rat
Application Route : Ingestion
Exposure time : 104 weeks
Result : negative
Remarks : Based on data from similar materials

Quartz:

Species : Humans
Application Route : inhalation (dust/mist/fume)
Result : positive
Remarks : IARC: (International Agency for Research on Cancer)
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

Reproductive toxicity

Not classified based on available information.

Components:

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Talc:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Calcium oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

STOT-single exposure

Not classified based on available information.

Components:

Calcium oxide:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Components:

Zinc oxide:

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

12-Hydroxy lithium stearate:

Routes of exposure : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Quartz:

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Repeated dose toxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rat
NOAEL : > 0.98 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Remarks : Based on data from similar materials

Zinc oxide:

Species : Rat, male
NOAEL : 0.0015 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 3 Months
Method : OECD Test Guideline 413

12-Hydroxy lithium stearate:

Species : Rat
NOAEL : > 88 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Calcium oxide:

Species : Rat
NOAEL : ≥ 0.399 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 90 Days
Method : OECD Test Guideline 413

Quartz:

Species : Humans
LOAEL : 0.053 mg/m³
Application Route : inhalation (dust/mist/fume)
Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (*Pseudokirchneriella subcapitata* (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): 10 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Remarks: Based on data from similar materials

Zinc oxide:

Toxicity to fish : LC50 (*Oncorhynchus mykiss* (rainbow trout)): > 0.1 - 1 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 0.01 - 0.1 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (*Selenastrum capricornutum* (green algae)): > 0.1 - 1 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

NOEC (*Selenastrum capricornutum* (green algae)): > 0.001 - 0.01 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC (*Oncorhynchus mykiss* (rainbow trout)): > 0.01 - 0.1 mg/l
Exposure time: 25 d
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): > 0.01 - 0.1 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

Talc:

Toxicity to fish : LC50 (*Brachydanio rerio* (zebrafish)): > 100,000 mg/l
Exposure time: 24 h

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Graphite:

- Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
- Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50: > 1,012.5 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

12-Hydroxy lithium stearate:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Calcium oxide:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Crangon crangon (shrimp)): > 1 mg/l
Exposure time: 14 d
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10: 110 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Quartz:

Ecotoxicology Assessment

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Persistence and degradability

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Method: OECD Test Guideline 301B

12-Hydroxy lithium stearate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 16 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Zinc oxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 78 - 2,060

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Zinc oxide)
Class : 9

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Zinc oxide)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956
Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Zinc oxide)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Zinc oxide)
Class : 9
Packing group : III
Labels : 9
ERG Code : 171
Marine pollutant : yes(Zinc oxide)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

SAFETY DATA SHEET



BLACK JACK

Version 4.1 Revision Date: 10/11/2018 SDS Number: 119813-00014 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

AICS : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV : Time-weighted average exposure value
CA QC OEL / STEV : Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on

SAFETY DATA SHEET



BLACK JACK

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/01/2018 |
| 4.1 | 10/11/2018 | 119813-00014 | Date of first issue: 05/18/2015 |

the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/11/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8