

C-55

Version 8.2 Revision Date: 10/11/2018 SDS Number: 208373-00015 Date of last issue: 10/01/2018
Date of first issue: 07/09/2015

SECTION 1. IDENTIFICATION

Product name : C-55
Other means of identification : No data available
SDS-Identcode : 027G

Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation
Address : 2777 N. Stemmons Frwy Ste 1800
Dallas TX 75207,
Telephone : 855-243-9164/972-865-8961
Telefax : 214-631-3047
E-mail address : www.bestolife.com

Recommended use of the chemical and restrictions on use

Recommended use : Industrial use
Thread Compound (Pipe Dope) and Jacking grease for use in
Offshore industries
Mining, (without offshore industries)
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-
pheres.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Skin sensitization : Category 1
Carcinogenicity : Category 2
Reproductive toxicity : Category 1A
Effects on or via lactation
Specific target organ : Category 1 (Kidney, Central nervous system, Blood)
systemic toxicity - repeated
exposure

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H360FD May damage fertility. May damage the unborn child.
H362 May cause harm to breast-fed children.

SAFETY DATA SHEET



C-55

Version 8.2 Revision Date: 10/11/2018 SDS Number: 208373-00015 Date of last issue: 10/01/2018
Date of first issue: 07/09/2015

H372 Causes damage to organs (Kidney, Central nervous system, Blood) through prolonged or repeated exposure.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P263 Avoid contact during pregnancy and while nursing.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Lead	7439-92-1	>= 60 - < 80
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	>= 10 - < 30
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 10 - < 30
Talc	14807-96-6	>= 10 - < 30
Graphite	7782-42-5	>= 1 - < 5
Dilithium azelate	38900-29-7	>= 1 - < 5
Quartz	14808-60-7	>= 0.1 - < 1
2,5-Bis(octyldithio)-1,3,4-thiadiazole	13539-13-4	>= 0.1 - < 1
Diocetyl disulphide	822-27-5	>= 0.1 - < 1

Actual concentration or concentration range is withheld as a trade secret

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

SECTION 4. FIRST AID MEASURES

General advice	:	In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	:	If inhaled, remove to fresh air. Get medical attention.
In case of skin contact	:	In case of contact, immediately flush skin with soap and plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	:	Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	:	May cause an allergic skin reaction. Suspected of causing cancer. May damage fertility. May damage the unborn child. May cause harm to breast-fed children. Causes damage to organs through prolonged or repeated exposure.
Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
Notes to physician	:	Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion products	:	Lead compounds Carbon oxides Metal oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Organic peroxides
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lead	7439-92-1	TWA	0.05 mg/m ³	CA AB OEL
		TWA	0.05 mg/m ³	CA BC OEL
		TWA	0.05 mg/m ³ (Lead)	CA ON OEL

SAFETY DATA SHEET



C-55

Version
8.2

Revision Date:
10/11/2018

SDS Number:
208373-00015

Date of last issue: 10/01/2018
Date of first issue: 07/09/2015

		TWAEV	0.05 mg/m ³ (Lead)	CA QC OEL
		TWA	0.05 mg/m ³ (Lead)	ACGIH
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
Talc	14807-96-6	TWAEV (respirable dust)	3 mg/m ³	CA QC OEL
		TWA (Res- pirable par- ticulates)	2 mg/m ³	CA AB OEL
		TWA (Res- pirable)	2 mg/m ³	CA BC OEL
		TWA	2 fibres per cubic centimeter	CA ON OEL
		TWA (Res- pirable frac- tion)	2 mg/m ³	CA ON OEL
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
Graphite	7782-42-5	TWA (Res- pirable)	2 mg/m ³	CA BC OEL
		TWA (Res- pirable)	2 mg/m ³	CA AB OEL
		TWAEV (respirable dust)	2 mg/m ³	CA QC OEL
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
Quartz	14808-60-7	TWA (Res- pirable par- ticulates)	0.025 mg/m ³	CA AB OEL
		TWA (Res- pirable frac- tion)	0.1 mg/m ³	CA ON OEL

SAFETY DATA SHEET



C-55

Version 8.2 Revision Date: 10/11/2018 SDS Number: 208373-00015 Date of last issue: 10/01/2018
 Date of first issue: 07/09/2015

		TWAEV (respirable dust)	0.1 mg/m ³	CA QC OEL
		TWA (Respirable)	0.025 mg/m ³ (Silica)	CA BC OEL
		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Lead	7439-92-1	Lead (Lead)	In blood	Not critical	200 µg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

Hygiene measures : clothing (gloves, aprons, boots, etc).
 : Ensure that eye flushing systems and safety showers are located close to the working place.
 : When using do not eat, drink or smoke.
 : Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Viscous semi-solid
Color	: black
Odor	: Petroleum
Odor Threshold	: No data available
pH	: Not applicable (not an aqueous solution)
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: ≥ 200 °C
	Method: ASTM D 92, Cleveland open cup Distillates (petroleum), hydrotreated heavy naphthenic
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: Not applicable
Relative vapor density	: Not applicable
Relative density	: 2.5
Solubility(ies)	
Water solubility	: negligible
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: Not applicable
Flow time	: No data available

SAFETY DATA SHEET



C-55

Version 8.2 Revision Date: 10/11/2018 SDS Number: 208373-00015 Date of last issue: 10/01/2018
Date of first issue: 07/09/2015

Explosive properties : Not explosive
Oxidizing properties : The substance or mixture is not classified as oxidizing.
Molecular weight : No data available
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Can react with strong oxidizing agents.
Conditions to avoid : None known.
Incompatible materials : Oxidizing agents
Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:

Lead:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Graphite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Dilithium azelate:

Acute oral toxicity : LD50 (Rat): > 300 - 2,000 mg/kg
Method: OECD Test Guideline 420
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

SAFETY DATA SHEET



C-55

Version 8.2 Revision Date: 10/11/2018 SDS Number: 208373-00015 Date of last issue: 10/01/2018
Date of first issue: 07/09/2015

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Diocetyl disulphide:

Acute oral toxicity : LD50 (Rat): > 290 - 500 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 5.05 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Lead:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Talc:

Species : Rabbit
Result : No skin irritation

Graphite:

C-55

Version 8.2 Revision Date: 10/11/2018 SDS Number: 208373-00015 Date of last issue: 10/01/2018
Date of first issue: 07/09/2015

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Dilithium azelate:

Method : OECD Test Guideline 439
Result : No skin irritation
Remarks : Based on data from similar materials

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species : Rabbit
Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Lead:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Talc:

Species : Rabbit
Result : No eye irritation

Graphite:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Dilithium azelate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:**Lead:**

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative
Remarks	:	Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative
Remarks	:	Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

Talc:

Routes of exposure	:	Skin contact
Species	:	Humans
Result	:	negative

Graphite:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Result	:	negative

Dilithium azelate:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact

C-55

Version 8.2 Revision Date: 10/11/2018 SDS Number: 208373-00015 Date of last issue: 10/01/2018
Date of first issue: 07/09/2015

Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Routes of exposure : Skin contact
Species : Guinea pig
Result : positive

Assessment : Probability or evidence of skin sensitization in humans

Germ cell mutagenicity

Not classified based on available information.

Components:**Lead:**

Genotoxicity in vitro : Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

Method: OECD Test Guideline 474
 Result: negative
 Remarks: Based on data from similar materials

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
 Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
 Species: Rat
 Application Route: Ingestion
 Result: negative

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Test Type: In vitro mammalian cell gene mutation test
 Method: OECD Test Guideline 476
 Result: negative

Test Type: Chromosome aberration test in vitro
 Method: OECD Test Guideline 473
 Result: negative

Dilithium azelate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Test Type: In vitro mammalian cell gene mutation test
 Method: OECD Test Guideline 476
 Result: negative
 Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
 Method: OECD Test Guideline 473
 Result: negative
 Remarks: Based on data from similar materials

Carcinogenicity

Suspected of causing cancer.

Product:

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

Components:**Lead:**

Species : Rat
 Application Route : Ingestion
 Exposure time : 2 Years
 Result : positive
 Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Mouse
 Application Route : Skin contact
 Exposure time : 78 weeks
 Method : OECD Test Guideline 451
 Result : negative
 Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Mouse
 Application Route : Skin contact
 Exposure time : 78 weeks
 Method : OECD Test Guideline 451
 Result : negative

Talc:

Species : Mouse
 Application Route : inhalation (dust/mist/fume)
 Exposure time : 2 Years
 Result : negative

Quartz:

Species : Humans
 Application Route : inhalation (dust/mist/fume)
 Result : positive
 Remarks : IARC: (International Agency for Research on Cancer)
 These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

Reproductive toxicity

May damage fertility. May damage the unborn child.
 May cause harm to breast-fed children.

Components:**Lead:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study
 Species: Mouse

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Positive evidence of adverse effects on sexual function and fertility from human epidemiological studies., Positive evidence of adverse effects on development from human epidemiological studies., Studies indicating a hazard to babies during the lactation period

Distillates (petroleum), hydrotreated heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Talc:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

Dilithium azelate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
 Species: Rat
 Application Route: Skin contact
 Result: negative
 Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test
 Species: Rat
 Application Route: Skin contact
 Result: negative
 Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Kidney, Central nervous system, Blood) through prolonged or repeated exposure.

Components:**Lead:**

Target Organs : Kidney, Central nervous system, Blood
 Assessment : Causes damage to organs through prolonged or repeated exposure.

Quartz:

Routes of exposure : inhalation (dust/mist/fume)
 Target Organs : Lungs
 Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity**Components:****Lead:**

Species : Rat
 NOAEL : 0.0015 mg/kg
 LOAEL : 0.005 mg/kg
 Application Route : Ingestion
 Exposure time : 6 - 12 Months
 Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit
 NOAEL : 1,000 mg/kg
 Application Route : Skin contact
 Exposure time : 4 Weeks
 Method : OECD Test Guideline 410

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

Remarks : Based on data from similar materials

Species : Rat
 NOAEL : > 980 mg/m³
 Application Route : inhalation (dust/mist/fume)
 Exposure time : 4 Weeks

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rat
 NOAEL : > 0.98 mg/l
 Application Route : inhalation (dust/mist/fume)
 Exposure time : 28 Days
 Remarks : Based on data from similar materials

Dilithium azelate:

Species : Rat
 NOAEL : 1,089.75 mg/kg
 Application Route : Skin contact
 Exposure time : 28 Days
 Remarks : Based on data from similar materials

Quartz:

Species : Humans
 LOAEL : 0.053 mg/m³
 Application Route : inhalation (dust/mist/fume)
 Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Lead:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.107 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 0.029 mg/l
 Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.025 mg/l
 Exposure time: 72 h

EC10 (Pseudokirchneriella subcapitata (green algae)): 6.1 µg/l
 Exposure time: 72 h

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

Toxicity to fish (Chronic toxicity) : EC10 (Pimephales promelas (fathead minnow)): 20 µg/l
 Exposure time: 30 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Ceriodaphnia dubia (water flea)): 1.7 µg/l
 Exposure time: 7 d

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202
 Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211
 Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
 Exposure time: 10 min
 Method: DIN 38 412 Part 8
 Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
 Exposure time: 21 d
 Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l

SAFETY DATA SHEET



C-55

Version 8.2 Revision Date: 10/11/2018 SDS Number: 208373-00015 Date of last issue: 10/01/2018
Date of first issue: 07/09/2015

Exposure time: 10 min
Remarks: Based on data from similar materials

Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
Exposure time: 24 h

Graphite:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,012.5 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Dilithium azelate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h

SAFETY DATA SHEET



C-55

Version 8.2 Revision Date: 10/11/2018 SDS Number: 208373-00015 Date of last issue: 10/01/2018
Date of first issue: 07/09/2015

Remarks: Based on data from similar materials

Quartz:

Ecotoxicology Assessment

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Persistence and degradability

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Dilithium azelate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 30 d
Method: OECD Test Guideline 301D
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Dilithium azelate:

Partition coefficient: n-octanol/water : log Pow: -3.53

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 3077
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
 (Lead, Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony)
 Class : 9
 Packing group : III
 Labels : 9

IATA-DGR

UN/ID No. : UN 3077
 Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
 (Lead, Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony)
 Class : 9
 Packing group : III
 Labels : Miscellaneous
 Packing instruction (cargo aircraft) : 956
 Packing instruction (passenger aircraft) : 956
 Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
 (Lead, Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony)
 Class : 9
 Packing group : III
 Labels : 9
 EmS Code : F-A, S-F
 Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number : UN 3077
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
 (Lead, Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony)
 Class : 9
 Packing group : III
 Labels : 9

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

ERG Code : 171
 Marine pollutant : yes(Lead, Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**The ingredients of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL
 TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
 AICS : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
 CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
 CA BC OEL : Canada. British Columbia OEL
 CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
 CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
 ACGIH / TWA : 8-hour, time-weighted average
 CA AB OEL / TWA : 8-hour Occupational exposure limit
 CA AB OEL / STEL : 15-minute occupational exposure limit
 CA BC OEL / TWA : 8-hour time weighted average
 CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
 CA QC OEL / TWA EV : Time-weighted average exposure value
 CA QC OEL / STEV : Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization;

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
8.2	10/11/2018	208373-00015	Date of first issue: 07/09/2015

IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/11/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8