

COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : COPPER SUPREME SPECIAL BLEND®- WG

SDS-Identcode : 523G

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Industrial use, Thread Compound (Pipe Dope) and Jacking grease for use in Offshore industries, Mining, (without offshore industries)

Recommended restrictions on use : Do not use on oxygen lines or in oxygen enriched atmospheres.

1.3 Details of the supplier of the safety data sheet

Company : Bestolife Corporation INTERTEK FRANCE
2777 N. Stemmons Frwy 27400 HEUDEBOUVILLE
DALLAS, TX 75207, FRANCE

Telephone : 855-243-9164/972-865-8961 +33 385 991270

Telefax : 214-631-3047 +33 385 991288

E-mail address of person responsible for the SDS : www.bestolife.com/christian.gimenez@intertek.com/if.reach@intertek.com

1.4 Emergency telephone number

CHEMTREC: +(44)-870-8200418; Interntnl: +1-703-527-3887 NHS Drct: +44 0845 4647
(Medical only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

Hazard statements : H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear eye protection/ face protection.

Response:
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Additional Labelling

EUH208 Contains 2,5-Bis(octyldithio)-1,3,4-thiadiazole, Benzenesulphonic acid, propenated, calcium salts, overbased. May produce an allergic reaction.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Copper metal powder	7440-50-8 231-159-6 01-2119480154-42	Flam. Sol. 1; H228 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 10 - < 20
Dilithium azelate	38900-29-7 254-184-4	Acute Tox. 4; H302	>= 1 - < 10
Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1 240-130-7 051-003-00-9	Acute Tox. 4; H302 Acute Tox. 4; H332 Aquatic Chronic 1; H410	>= 1 - < 2.5
Antimony, dialkyl dithiocarbamate	15890-25-2 240-028-2 051-003-00-9	Acute Tox. 4; H302 Acute Tox. 4; H332 Aquatic Chronic 1; H410	>= 1 - < 2.5
Calcium oxide	1305-78-8 215-138-9	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	>= 1 - < 3
Quartz	14808-60-7 238-878-4	STOT RE 1; H372	>= 1 - < 10
2,5-Bis(octyldithio)-1,3,4-thiadiazole	13539-13-4 236-912-2	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 0.1 - < 1
Diocetyl disulphide	822-27-5 212-494-7	Acute Tox. 3; H301 Acute Tox. 3; H331	>= 0.1 - < 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

Benzenesulphonic acid, propenated, calcium salts, over-based	68610-84-4 271-877-7	Skin Sens. 1; H317 Aquatic Chronic 4; H413	>= 0.1 - < 0.25
Hydrogen sulfide	7783-06-4 231-977-3 016-001-00-4	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280 Acute Tox. 2; H330 STOT SE 3; H335 Aquatic Acute 1; H400	>= 0.025 - < 0.1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.

May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Metal oxides
Nitrogen oxides (NO_x)
Sulphur oxides
Silicon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.

COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents

7.3 Specific end use(s)

- Specific use(s) : No data available
-

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Graphite	7782-42-5	TWA (inhalable dust)	10 mg/m ³	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
 Date of first issue: 19.05.2015

	<p>COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			
		TWA (Respirable dust)	4 mg/m ³	GB EH40
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			
Copper metal powder	7440-50-8	TWA (Fumes)	0.2 mg/m ³ (Copper)	GB EH40
		TWA (Dusts and mists)	1 mg/m ³ (Copper)	GB EH40
		STEL (Dusts and mists)	2 mg/m ³ (Copper)	GB EH40
Talc	14807-96-6	TWA (Respirable dust)	1 mg/m ³	GB EH40
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, Talc is</p>			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
 Date of first issue: 19.05.2015

	defined as the mineral talc together with other hydrous phyllosilicates including chlorite and carbonate materials which occur with it, but excluding amphibole asbestos and crystalline silica., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1	TWA	0.5 mg/m3 (antimony)	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Antimony, dialkyl dithiocarbamate	15890-25-2	TWA	0.5 mg/m3 (antimony)	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Calcium oxide	1305-78-8	TWA	2 mg/m3	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
		TWA (Respirable fraction)	1 mg/m3	2017/164/EU
Further information	Indicative			
		STEL (Respirable fraction)	4 mg/m3	2017/164/EU
Further information	Indicative			
Quartz	14808-60-7	TWA (Respirable dust)	0.1 mg/m3 (Silica)	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

	of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Hydrogen sulfide	7783-06-4	TWA	5 ppm 7 mg/m ³	2009/161/EU
Further information	Indicative			
		STEL	10 ppm 14 mg/m ³	2009/161/EU
Further information	Indicative			
		TWA	5 ppm 7 mg/m ³	GB EH40
		STEL	10 ppm 14 mg/m ³	GB EH40

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Graphite	Consumers	Inhalation	Long-term local effects	0.3 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	813 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	1.2 mg/m ³
Copper metal powder	Workers	Inhalation	Acute systemic effects	20 mg/m ³
	Workers	Skin contact	Long-term systemic effects	137 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	237 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	20 mg/m ³
	Consumers	Inhalation	Long-term local effects	1 mg/m ³
	Consumers	Inhalation	Acute local effects	1 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	137 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	273 mg/kg bw/day
Dilithium azelate	Workers	Skin contact	Acute systemic effects	13.5 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

	Workers	Skin contact	Long-term systemic effects	13.5 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	13.5 mg/kg bw/day
	Workers	Skin contact	Long-term local effects	0.172 mg/kg bw/day
	Consumers	Skin contact	Long-term local effects	0.023 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	13.5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	13.5 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	27 mg/kg bw/day
Calcium oxide	Workers	Inhalation	Long-term local effects	1 mg/m ³
	Workers	Inhalation	Acute local effects	4 mg/m ³
	Consumers	Inhalation	Long-term local effects	1 mg/m ³
	Consumers	Inhalation	Acute local effects	4 mg/m ³
Benzenesulphonic acid, propenated, calcium salts, over-based	Workers	Inhalation	Long-term systemic effects	25.55 mg/m ³
	Workers	Inhalation	Acute systemic effects	668 mg/m ³
	Workers	Skin contact	Long-term systemic effects	8.33 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	100 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	11.8 mg/m ³
	Consumers	Inhalation	Acute systemic effects	267.2 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	4.17 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	50 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1.7 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	50 mg/kg bw/day
Hydrogen sulfide	Workers	Inhalation	Long-term systemic effects	7 mg/m ³
	Workers	Inhalation	Acute systemic effects	14 mg/m ³
	Workers	Inhalation	Long-term local effects	7 mg/m ³
	Workers	Inhalation	Acute local effects	14 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Distillates (petroleum), hy-	Oral (Secondary Poisoning)	9.33 mg/kg food

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

drotreated heavy paraffinic		
Copper metal powder	Fresh water	7.8 µg/l
	Marine water	5.2 µg/l
	Sewage treatment plant	230 µg/l
	Fresh water sediment	87 mg/kg
	Marine sediment	676 mg/kg
	Soil	65 mg/kg
Dilithium azelate	Fresh water	0.023 mg/l
	Marine water	0.002 mg/l
	Intermittent use/release	0.23 mg/l
Calcium oxide	Fresh water	0.37 mg/l
	Marine water	0.24 mg/l
	Intermittent use/release	0.37 mg/l
	Sewage treatment plant	2.27 mg/l
	Soil	817.4 mg/kg dry weight (d.w.)
Benzenesulphonic acid, propenated, calcium salts, over-based	Fresh water	1 mg/l
	Marine water	1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	1000 mg/l
	Fresh water sediment	43500 mg/kg
	Marine sediment	3480 mg/kg
	Soil	8850 mg/kg
	Oral (Secondary Poisoning)	33333 mg/kg food
Hydrogen sulfide	Fresh water	0.00005 mg/l
	Marine water	0.0149 mg/l
	Intermittent use/release	0.0005 mg/l
	Sewage treatment plant	1.33 mg/l

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety goggles

Hand protection
Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

Respiratory protection	:	Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc). Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	Viscous semi-solid
Colour	:	copper
Odour	:	Petroleum
Odour Threshold	:	No data available
pH	:	Not applicable (not an aqueous solution)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Relative density	:	1.2
Density	:	No data available
Solubility(ies)	:	
Water solubility	:	negligible
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight : No data available

Particle size : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

Method: Calculation method

Components:

Copper metal powder:

- Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 5.11 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Dilithium azelate:

- Acute oral toxicity : LD50 (Rat): > 300 - 2,000 mg/kg
Method: OECD Test Guideline 420
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony:

- Acute oral toxicity : Acute toxicity estimate: 2,000 mg/kg
Method: Expert judgement
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI
- Acute inhalation toxicity : Acute toxicity estimate: 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

- Acute oral toxicity : Acute toxicity estimate: 2,000 mg/kg
Method: Expert judgement
Remarks: Based on harmonised classification in EU regulation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

1272/2008, Annex VI

LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Calcium oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 425

Acute inhalation toxicity : (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Dioctyl disulphide:

Acute oral toxicity : LD50 (Rat): > 290 - 500 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 5.05 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

Remarks: Based on data from similar materials

Benzenesulphonic acid, propenated, calcium salts, overbased:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 402

Hydrogen sulfide:

Acute inhalation toxicity : LC50 (Rat): 444 ppm
Exposure time: 4 h
Test atmosphere: gas

Skin corrosion/irritation

Not classified based on available information.

Components:

Copper metal powder:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Dilithium azelate:

Method : OECD Test Guideline 439
Result : No skin irritation
Remarks : Based on data from similar materials

Calcium oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species : Rabbit
Result : Skin irritation

Benzenesulphonic acid, propenated, calcium salts, overbased:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

Components:

Copper metal powder:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Dilithium azelate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Calcium oxide:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Benzenesulphonic acid, propenated, calcium salts, overbased:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Copper metal powder:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Dilithium azelate:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

Calcium oxide:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Exposure routes : Skin contact
Species : Guinea pig
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Benzenesulphonic acid, propenated, calcium salts, overbased:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Copper metal powder:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: Directive 67/548/EEC, Annex V, B.12.
Result: negative
Remarks: Based on data from similar materials

Dilithium azelate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: equivocal

Calcium oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Benzenesulphonic acid, propenated, calcium salts, overbased:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Hydrogen sulfide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Rat
Application Route: inhalation (gas)
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Components:

Calcium oxide:

Species : Rat
Application Route : Ingestion
Exposure time : 104 weeks
Result : negative
Remarks : Based on data from similar materials

Quartz:

Species : Humans
Application Route : inhalation (dust/mist/fume)
Result : positive
Remarks : IARC: (International Agency for Research on Cancer)
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Reproductive toxicity

Not classified based on available information.

Components:

Copper metal powder:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Result: negative

Dilithium azelate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Skin contact
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Reproduction/Developmental toxicity screening test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

Species: Rat
Application Route: Skin contact
Result: negative
Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Calcium oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Hydrogen sulfide:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (gas)
Result: negative

STOT - single exposure

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

Components:

Calcium oxide:

Assessment : May cause respiratory irritation.

Hydrogen sulfide:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

Quartz:

Exposure routes : inhalation (dust/mist/fume)
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Copper metal powder:

Species : Rat
NOAEL : ≥ 2 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days

Dilithium azelate:

Species : Rat
NOAEL : 1,089.75 mg/kg
Application Route : Skin contact
Exposure time : 28 Days
Remarks : Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Species : Rat
NOAEL : $\geq 1,000$ mg/kg
Application Route : Ingestion
Exposure time : 54 Days

Calcium oxide:

Species : Rat
NOAEL : ≥ 0.399 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 90 Days
Method : OECD Test Guideline 413

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

Quartz:

Species	:	Humans
LOAEL	:	0.053 mg/m ³
Application Route	:	inhalation (dust/mist/fume)
Remarks	:	These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 10,250 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
------------------	---	---

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 15,470 mg/l Exposure time: 96 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
---	---	---

	:	EC50 (Daphnia magna (Water flea)): 30,940 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
--	---	---

Toxicity to algae	:	EC50 (Selenastrum capricornutum (green algae)): 70,100 mg/l Exposure time: 96 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
-------------------	---	--

	:	NOEC (Selenastrum capricornutum (green algae)): 60,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
--	---	--

Components:

Copper metal powder:

Toxicity to fish	:	LC50 : > 10 - 100 µg/l Exposure time: 96 h
------------------	---	---

M-Factor (Acute aquatic toxicity)	:	10
-----------------------------------	---	----

Toxicity to fish (Chronic tox-)	:	NOEC: > 1 - 10 µg/l
---------------------------------	---	---------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

icity)

M-Factor (Chronic aquatic toxicity) : 10

Dilithium azelate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.02 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Chronic aquatic toxicity : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Antimony, dialkyl dithiocarbamate:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.02 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Chronic aquatic toxicity : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Calcium oxide:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- EC10 (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC50 : > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 1 mg/l
Exposure time: 14 d
Species: Crangon crangon (shrimp)
Remarks: Based on data from similar materials

Quartz:

Ecotoxicology Assessment

- Acute aquatic toxicity : No toxicity at the limit of solubility
- Chronic aquatic toxicity : No toxicity at the limit of solubility

Benzenesulphonic acid, propenated, calcium salts, overbased:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials
- Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): 1,000 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

Exposure time: 72 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 10,000 mg/l
Exposure time: 3 h
Remarks: Based on data from similar materials

Hydrogen sulfide:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.0144 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (water flea)): 0.12 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Scenedesmus subspicatus): 1.87 mg/l
Exposure time: 24 h

M-Factor (Acute aquatic toxicity) : 10

Toxicity to microorganisms : EC50 : 29 mg/l
Method: ISO 8192

12.2 Persistence and degradability

Product:

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

Components:

Dilithium azelate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 30 d
Method: OECD Test Guideline 301D
Remarks: Based on data from similar materials

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony:

Biodegradability : Result: Not readily biodegradable.
Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 20 %
Exposure time: 28 d

Benzenesulphonic acid, propenated, calcium salts, overbased:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 12.5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Hydrogen sulfide:

Biodegradability : Result: rapidly degradable

12.3 Bioaccumulative potential

Components:

Dilithium azelate:

Partition coefficient: n-octanol/water : log Pow: -3.53

Benzenesulphonic acid, propenated, calcium salts, overbased:

Partition coefficient: n-octanol/water : log Pow: 5.8

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 3077
ADR : UN 3077

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version 5.4 Revision Date: 01.10.2018 SDS Number: 126783-00014 Date of last issue: 07.05.2018
Date of first issue: 19.05.2015

RID : UN 3077
IMDG : UN 3077
IATA : UN 3077

14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper metal powder, Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony)

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper metal powder, Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper metal powder, Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper metal powder, Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony)

IATA : Environmentally hazardous substance, solid, n.o.s.
(Copper metal powder, Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony)

14.3 Transport hazard class(es)

ADN : 9
ADR : 9
RID : 9
IMDG : 9
IATA : 9

14.4 Packing group

ADN
Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9

ADR
Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID
Packing group : III

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

Classification Code : M7
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 956
Packing instruction (LQ) : Y956
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 956
Packing instruction (LQ) : Y956
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL
TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
AICS : All ingredients listed or exempt.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H220 : Extremely flammable gas.
H228 : Flammable solid.
H280 : Contains gas under pressure; may explode if heated.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H330 : Fatal if inhaled.
H331 : Toxic if inhaled.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Gas : Flammable gases
Flam. Sol. : Flammable solids
Press. Gas : Gases under pressure
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2009/161/EU : Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
2017/164/EU : Commission Directive (EU) 2017/164 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
2009/161/EU / TWA : Limit Value - eight hours
2009/161/EU / STEL : Short term exposure limit
2017/164/EU / STEL : Short term exposure limit
2017/164/EU / TWA : Limit Value - eight hours
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



COPPER SUPREME SPECIAL BLEND®- WG

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2018
5.4	01.10.2018	126783-00014	Date of first issue: 19.05.2015

Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Eye Irrit. 2 H319

Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN