

SAFETY DATA SHEET



GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

SECTION 1. IDENTIFICATION

Product name : GGT-RSC HT
SDS-Identcode : 344G

Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation
Address : 2777 N. Stemmons Frwy Ste 1800
Dallas TX 75207,
Telephone : 855-243-9164/972-865-8961
Telefax : 214-631-3047
Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887
(24-hours/7 days)
E-mail address : www.bestolife.com

Recommended use of the chemical and restrictions on use


Recommended use : Industrial use
Thread Compound (Pipe Dope) and Jacking grease for use in
Offshore industries
Mining, (without offshore industries)
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-
pheres.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin sensitization : Category 1

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P272 Contaminated work clothing must not be allowed out of
the workplace.
P280 Wear protective gloves.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/
attention.
P363 Wash contaminated clothing before reuse.

SAFETY DATA SHEET



GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 20 - < 30
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	>= 20 - < 30
Talc	14807-96-6	>= 20 - < 30
Graphite	7782-42-5	>= 20 - < 30
Dolomite	16389-88-1	>= 5 - < 10
Dilithium azelate	38900-29-7	>= 1 - < 5
Quartz	14808-60-7	>= 1 - < 5
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	>= 1 - < 5
Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1	>= 1 - < 5
2,5-Bis(octyldithio)-1,3,4-thiadiazole	13539-13-4	>= 0.1 - < 1
Diocetyl disulphide	822-27-5	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms : May cause an allergic skin reaction.

SAFETY DATA SHEET



GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

and effects, both acute and delayed

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Metal oxides
Silicon oxides
Nitrogen oxides (NO_x)
Sulfur oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

SAFETY DATA SHEET



GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
 Date of first issue: 05/18/2015

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : Do not get on skin or clothing.
 Do not swallow.
 Avoid contact with eyes.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
 Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	2 mg/m ³	NIOSH REL
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
		TWA (Respirable)	2.5 mg/m ³	NIOSH REL
Graphite	7782-42-5	TWA (Respirable fraction)	2 mg/m ³	ACGIH
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
Dolomite	16389-88-1	TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL

SAFETY DATA SHEET



GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
 Date of first issue: 05/18/2015

Quartz	14808-60-7	TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	TWA (Inhalable fraction)	5 mg/m ³	ACGIH
Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1	TWA	0.5 mg/m ³ (antimony)	OSHA Z-1
		TWA	0.5 mg/m ³ (antimony)	ACGIH
		TWA	0.5 mg/m ³ (antimony)	NIOSH REL

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz

Engineering measures : Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

SAFETY DATA SHEET



GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

- Remarks : For prolonged or repeated contact use protective gloves. Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Viscous semi-solid
Color : black
Odor : Petroleum
Odor Threshold : No data available
- pH : Not applicable (not an aqueous solution)
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
Flash point : ≥ 392 °F / ≥ 200 °C
Method: ASTM D 92, Cleveland open cup
Distillates (petroleum), hydrotreated heavy naphthenic
- Evaporation rate : Not applicable
- Flammability (solid, gas) : Not classified as a flammability hazard
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapor pressure : Not applicable
- Relative vapor density : Not applicable
- Relative density : 1.3

SAFETY DATA SHEET



GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Density : No data available

Solubility(ies)
Water solubility : negligible

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l
Exposure time: 4 h
Test atmosphere: vapor

GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
 Date of first issue: 05/18/2015

Method: Calculation method

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Method: OECD Test Guideline 401
 Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: The substance or mixture has no acute inhalation toxicity
 Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
 Method: OECD Test Guideline 402
 Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Method: OECD Test Guideline 401
 Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: The substance or mixture has no acute inhalation toxicity
 Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
 Method: OECD Test Guideline 402
 Remarks: Based on data from similar materials

Talc:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Remarks: Based on data from similar materials

Graphite:

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 423
 Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403

GGT-RSC HT

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
11.0	10/11/2018	118106-00015	Date of first issue: 05/18/2015

Dolomite:

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 420
 Assessment: The substance or mixture has no acute oral toxicity
 Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: The substance or mixture has no acute inhalation toxicity
 Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: The substance or mixture has no acute dermal toxicity
 Remarks: Based on data from similar materials

Dilithium azelate:

- Acute oral toxicity : LD50 (Rat): > 300 - 2,000 mg/kg
 Method: OECD Test Guideline 420
 Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Remarks: Based on data from similar materials

Quartz:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Lubricating oils (petroleum), hydrotreated spent:

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
- Acute dermal toxicity : LD50 (Rabbit): > 4,480 mg/kg

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
 Remarks: Based on data from similar materials

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 3.08 mg/l
 Exposure time: 4 h

GGT-RSC HT

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
11.0	10/11/2018	118106-00015	Date of first issue: 05/18/2015

	Test atmosphere: dust/mist
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg
Diocetyl disulphide:	
Acute oral toxicity	: LD50 (Rat): > 290 - 500 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): 5.05 mg/l Exposure time: 4 h Test atmosphere: vapor Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species	: Rabbit
Result	: No skin irritation
Remarks	: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	: Rabbit
Result	: No skin irritation
Remarks	: Based on data from similar materials

Talc:

Species	: Rabbit
Result	: No skin irritation

Graphite:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Dolomite:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation
Remarks	: Based on data from similar materials

Dilithium azelate:

Method	: OECD Test Guideline 439
Result	: No skin irritation
Remarks	: Based on data from similar materials

GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species : Rabbit
Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Talc:

Species : Rabbit
Result : No eye irritation

Graphite:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Dolomite:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Dilithium azelate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

GGT-RSC HT

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
11.0	10/11/2018	118106-00015	Date of first issue: 05/18/2015

Respiratory sensitization

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative
Remarks	: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

Talc:

Routes of exposure	: Skin contact
Species	: Humans
Result	: negative

Graphite:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

Dolomite:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative
Remarks	: Based on data from similar materials

Dilithium azelate:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative
Remarks	: Based on data from similar materials

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: positive

GGT-RSC HT

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
11.0	10/11/2018	118106-00015	Date of first issue: 05/18/2015

Assessment : Probability or evidence of skin sensitization in humans

Germ cell mutagenicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
 Species: Mouse
 Application Route: Intraperitoneal injection
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
 Species: Mouse
 Application Route: Intraperitoneal injection
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Based on data from similar materials

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
 Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
 Species: Rat
 Application Route: Ingestion
 Result: negative

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Test Type: In vitro mammalian cell gene mutation test
 Method: OECD Test Guideline 476
 Result: negative

GGT-RSC HT

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
11.0	10/11/2018	118106-00015	Date of first issue: 05/18/2015

Test Type: Chromosome aberration test in vitro
 Method: OECD Test Guideline 473
 Result: negative

Dolomite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative
 Remarks: Based on data from similar materials

Dilithium azelate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Test Type: In vitro mammalian cell gene mutation test
 Method: OECD Test Guideline 476
 Result: negative
 Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
 Method: OECD Test Guideline 473
 Result: negative
 Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Components:**Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Mouse
 Application Route : Skin contact
 Exposure time : 78 weeks
 Method : OECD Test Guideline 451
 Result : negative

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Mouse
 Application Route : Skin contact
 Exposure time : 78 weeks
 Method : OECD Test Guideline 451
 Result : negative
 Remarks : Based on data from similar materials

SAFETY DATA SHEET



GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Talc:

Species : Mouse
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : negative

Quartz:

Species : Humans
Application Route : inhalation (dust/mist/fume)
Result : positive
Remarks : IARC: (International Agency for Research on Cancer)
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

IARC Group 1: Carcinogenic to humans
Quartz 14808-60-7
(Silica dust, crystalline)

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen
Quartz 14808-60-7
(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Talc:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion

GGT-RSC HT

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
11.0	10/11/2018	118106-00015	Date of first issue: 05/18/2015

		Result: negative
	Graphite:	
	Effects on fertility	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative
	Effects on fetal development	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative
	Dolomite:	
	Effects on fertility	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative Remarks: Based on data from similar materials
	Effects on fetal development	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative Remarks: Based on data from similar materials
	Dilithium azelate:	
	Effects on fertility	: Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Skin contact Result: negative Remarks: Based on data from similar materials
	Effects on fetal development	: Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Skin contact Result: negative Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

GGT-RSC HT

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
11.0	10/11/2018	118106-00015	Date of first issue: 05/18/2015

STOT-repeated exposure

Not classified based on available information.

Components:**Quartz:**

Routes of exposure	:	inhalation (dust/mist/fume)
Target Organs	:	Lungs
Assessment	:	Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species	:	Rat
NOAEL	:	> 0.98 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	28 Days
Remarks	:	Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	:	Rabbit
NOAEL	:	1,000 mg/kg
Application Route	:	Skin contact
Exposure time	:	4 Weeks
Method	:	OECD Test Guideline 410
Remarks	:	Based on data from similar materials

Species	:	Rat
NOAEL	:	> 980 mg/m ³
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	4 Weeks

Dolomite:

Species	:	Mouse
NOAEL	:	1,300 mg/kg
Application Route	:	Ingestion
Exposure time	:	28 Days
Remarks	:	Based on data from similar materials

Dilithium azelate:

Species	:	Rat
NOAEL	:	1,089.75 mg/kg
Application Route	:	Skin contact
Exposure time	:	28 Days
Remarks	:	Based on data from similar materials

Quartz:

Species	:	Humans
LOAEL	:	0.053 mg/m ³

SAFETY DATA SHEET



GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Application Route : inhalation (dust/mist/fume)
Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

SAFETY DATA SHEET



GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
Exposure time: 24 h

Graphite:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,012.5 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Dolomite:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 16.6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 16.6 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility.

GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

Based on data from similar materials

Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): 14 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Dilithium azelate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

Quartz:**Ecotoxicology Assessment**

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Lubricating oils (petroleum), hydrotreated spent:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 1,000 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony:

GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
 Date of first issue: 05/18/2015

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.02 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211
 Remarks: Based on data from similar materials

Ecotoxicology Assessment

Chronic aquatic toxicity : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and degradability**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 31 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F

Dilithium azelate:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 83 %
 Exposure time: 30 d
 Method: OECD Test Guideline 301D
 Remarks: Based on data from similar materials

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony:

Biodegradability : Result: Not readily biodegradable.
 Remarks: Based on data from similar materials

Bioaccumulative potential**Components:****Dilithium azelate:**

Partition coefficient: n-octanol/water : log Pow: -3.53

Mobility in soil

No data available

Other adverse effects

No data available

GGT-RSC HT

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
11.0	10/11/2018	118106-00015	Date of first issue: 05/18/2015

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.
 Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
 Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
 If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Hydrogen sulfide	7783-06-4	100	*
Ammonia	7664-41-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Hydrogen sulfide	7783-06-4	100	*
Ammonia	7664-41-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

SAFETY DATA SHEET



GGT-RSC HT

Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1	>= 1 - < 5 %
Antimony, dialkyl dithiocarbamate	15890-25-2	>= 0.1 - < 1 %

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Talc	14807-96-6
Graphite	7782-42-5
Dolomite	16389-88-1
Hydroxystearate sebacate lithium complexes	68815-49-6
Dilithium azelate	38900-29-7
Quartz	14808-60-7
Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1
Antimony, dialkyl dithiocarbamate	15890-25-2
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3
Hydrogen sulfide	7783-06-4
Ammonia	7664-41-7

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Talc	14807-96-6
Graphite	7782-42-5
Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1

California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Talc	14807-96-6
Graphite	7782-42-5
Quartz	14808-60-7
Tris[bis(2-ethylhexyl)dithiocarbamate-S,S'] antimony	15991-76-1

California Regulated Carcinogens

Quartz	14808-60-7
--------	------------

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed on the

SAFETY DATA SHEET



GGT-RSC HT


Version 11.0 Revision Date: 10/11/2018 SDS Number: 118106-00015 Date of last issue: 10/01/2018
Date of first issue: 05/18/2015

AICS : TSCA Inventory or are in compliance with a TSCA Inventory exemption.
: All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "/" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA : 8-hour, time-weighted average
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organiza-

SAFETY DATA SHEET



GGT-RSC HT

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
11.0	10/11/2018	118106-00015	Date of first issue: 05/18/2015

tion; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/11/2018

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8