

# SAFETY DATA SHEET



## GGT

Version 4.5      Revision Date: 10/09/2018      SDS Number: 130150-00012      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

### SECTION 1. IDENTIFICATION

Product name : GGT  
Other means of identification : No data available  
SDS-Identcode : 104G

#### Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation  
Address : 2777 N. Stemmons Frwy Ste 1800  
Dallas TX 75207,  
Telephone : 855-243-9164/972-865-8961  
Telefax : 214-631-3047  
E-mail address : www.bestolife.com

#### Recommended use of the chemical and restrictions on use

Recommended use : Industrial use  
Thread Compound (Pipe Dope) and Jacking grease for use in  
Offshore industries  
Mining, (without offshore industries)  
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-  
pheres.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

#### GHS label elements

Not a hazardous substance or mixture.

#### Other hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 30 - < 60
Talc	14807-96-6	>= 10 - < 30
Graphite	7782-42-5	>= 10 - < 30
Quartz	14808-60-7	>= 1 - < 5
12-Hydroxy lithium stearate	7620-77-1	>= 1 - < 5
Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	57855-77-3	>= 1 - < 5

Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

# SAFETY DATA SHEET



## GGT

Version 4.5      Revision Date: 10/09/2018      SDS Number: 130150-00012      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Metal oxides  
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.
-

# SAFETY DATA SHEET



## GGT

Version 4.5      Revision Date: 10/09/2018      SDS Number: 130150-00012      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on safe handling : Do not get on skin or clothing.  
Do not swallow.  
Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Mist)	1 mg/m <sup>3</sup>	CA BC OEL
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH
Talc	14807-96-6	TWAEV (respirable dust)	3 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable par-	2 mg/m <sup>3</sup>	CA AB OEL

# SAFETY DATA SHEET



## GGT

Version  
4.5

Revision Date:  
10/09/2018

SDS Number:  
130150-00012

Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

		ticulates)		
		TWA (Respirable)	2 mg/m <sup>3</sup>	CA BC OEL
		TWA	2 fibres per cubic centimeter	CA ON OEL
		TWA (Respirable fraction)	2 mg/m <sup>3</sup>	CA ON OEL
		TWA (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIH
Graphite	7782-42-5	TWA (Respirable)	2 mg/m <sup>3</sup>	CA BC OEL
		TWA (Respirable)	2 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (respirable dust)	2 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIH
Quartz	14808-60-7	TWA (Respirable particulates)	0.025 mg/m <sup>3</sup>	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m <sup>3</sup>	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable)	0.025 mg/m <sup>3</sup> (Silica)	CA BC OEL
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
12-Hydroxy lithium stearate	7620-77-1	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (Inhalable fraction)	10 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable fraction)	3 mg/m <sup>3</sup>	ACGIH

**These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.**

Quartz

**Engineering measures** : Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for

# SAFETY DATA SHEET



## GGT

Version 4.5      Revision Date: 10/09/2018      SDS Number: 130150-00012      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

Particulates Not Otherwise Regulated of 15 mg/m<sup>3</sup> - total dust, 5 mg/m<sup>3</sup> - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m<sup>3</sup> - respirable particles, 10 mg/m<sup>3</sup> - inhalable particles.

### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Combined particulates and organic vapor type
- Hand protection
- Material : Chemical-resistant gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:  
Safety glasses
- Skin and body protection : Skin should be washed after contact.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.
- 

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Viscous semi-solid
- Color : black
- Odor : Petroleum
- Odor Threshold : No data available
- pH : Not applicable (not an aqueous solution)
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Flash point :  $\geq 200$  °C
- Method: ASTM D 92, Cleveland open cup  
Distillates (petroleum), hydrotreated heavy naphthenic
- Evaporation rate : Not applicable
- Flammability (solid, gas) : Not classified as a flammability hazard
- Upper explosion limit / Upper flammability limit : No data available
-

# SAFETY DATA SHEET



## GGT

Version 4.5      Revision Date: 10/09/2018      SDS Number: 130150-00012      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 1.2

Density : No data available

Solubility(ies)  
Water solubility : negligible

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Skin contact  
Ingestion  
Eye contact

**GGT**

Version 4.5      Revision Date: 10/09/2018      SDS Number: 130150-00012      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

**Acute toxicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: Based on data from similar materials

**Talc:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

**Graphite:**

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 423  
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 2 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

**Quartz:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**12-Hydroxy lithium stearate:**

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

- Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg  
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: Based on data from similar materials

**GGT**

Version 4.5      Revision Date: 10/09/2018      SDS Number: 130150-00012      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

**Talc:**

Species : Rabbit  
Result : No skin irritation

**Graphite:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**12-Hydroxy lithium stearate:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**Talc:**

Species : Rabbit  
Result : No eye irritation

**Graphite:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405



**GGT**

Version 4.5      Revision Date: 10/09/2018      SDS Number: 130150-00012      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

**12-Hydroxy lithium stearate:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Remarks : Based on data from similar materials

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

**Talc:**

Routes of exposure : Skin contact  
Species : Humans  
Result : negative

**Graphite:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Result : negative

**12-Hydroxy lithium stearate:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Test Type : Human repeat insult patch test (HRIPT)  
Routes of exposure : Skin contact  
Result : negative

**GGT**

Version 4.5	Revision Date: 10/09/2018	SDS Number: 130150-00012	Date of last issue: 10/01/2018 Date of first issue: 05/27/2015
----------------	------------------------------	-----------------------------	---

---

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Talc:**

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro  
Species: Rat  
Application Route: Ingestion  
Result: negative

**Graphite:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**Product:**

Carcinogenicity - Assess- : Petroleum distillates have been classified as not carcinogenic

## GGT

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
4.5	10/09/2018	130150-00012	Date of first issue: 05/27/2015

---

ment based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Mouse  
 Application Route : Skin contact  
 Exposure time : 78 weeks  
 Method : OECD Test Guideline 451  
 Result : negative

**Talc:**

Species : Mouse  
 Application Route : inhalation (dust/mist/fume)  
 Exposure time : 2 Years  
 Result : negative

**Quartz:**

Species : Humans  
 Application Route : inhalation (dust/mist/fume)  
 Result : positive  
 Remarks : IARC: (International Agency for Research on Cancer)  
 These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

**Reproductive toxicity**

Not classified based on available information.

**Components:****Talc:**

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: Ingestion  
 Result: negative

**Graphite:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion

**GGT**

Version 4.5	Revision Date: 10/09/2018	SDS Number: 130150-00012	Date of last issue: 10/01/2018 Date of first issue: 05/27/2015
----------------	------------------------------	-----------------------------	---

---

Method: OECD Test Guideline 422

Result: negative

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**Components:****Quartz:**

Routes of exposure	:	inhalation (dust/mist/fume)
Target Organs	:	Lungs
Assessment	:	Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

**12-Hydroxy lithium stearate:**

Routes of exposure	:	Ingestion
Assessment	:	No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

**Repeated dose toxicity****Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species	:	Rat
NOAEL	:	> 0.98 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	28 Days
Remarks	:	Based on data from similar materials

**Quartz:**

Species	:	Humans
LOAEL	:	0.053 mg/m <sup>3</sup>
Application Route	:	inhalation (dust/mist/fume)
Remarks	:	These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

**12-Hydroxy lithium stearate:**

Species	:	Rat
NOAEL	:	> 88 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days

**Aspiration toxicity**

Not classified based on available information.

## GGT

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
4.5	10/09/2018	130150-00012	Date of first issue: 05/27/2015

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203  
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h  
 Remarks: Based on data from similar materials
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
 Exposure time: 21 d  
 Remarks: Based on data from similar materials
- Toxicity to microorganisms : NOEC: > 1.93 mg/l  
 Exposure time: 10 min  
 Remarks: Based on data from similar materials

**Talc:**

- Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l  
 Exposure time: 24 h

**Graphite:**

- Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l  
 Exposure time: 96 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
 Exposure time: 48 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 202
- Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 201
- NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l

**GGT**

Version 4.5	Revision Date: 10/09/2018	SDS Number: 130150-00012	Date of last issue: 10/01/2018 Date of first issue: 05/27/2015
----------------	------------------------------	-----------------------------	---

---

Exposure time: 72 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,012.5 mg/l  
 Exposure time: 3 h  
 Method: OECD Test Guideline 209

**Quartz:****Ecotoxicology Assessment**

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

**12-Hydroxy lithium stearate:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l  
 Exposure time: 96 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 203  
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
 Exposure time: 48 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 202  
 Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10: 110 mg/l  
 Exposure time: 3 h  
 Method: OECD Test Guideline 209  
 Remarks: Based on data from similar materials

**Persistence and degradability****Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : Result: Not readily biodegradable.

**GGT**

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
4.5	10/09/2018	130150-00012	Date of first issue: 05/27/2015

---

Biodegradation: 2 - 4 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B

**12-Hydroxy lithium stearate:**

Biodegradability : Result: Readily biodegradable.  
 Biodegradation: 78 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301C

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Biodegradability : Result: Not readily biodegradable.  
 Biodegradation: 16 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B  
 Remarks: Based on data from similar materials

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.  
 Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
 Empty containers retain residue and can be dangerous.  
 Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
 If not otherwise specified: Dispose of as unused product.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**GGT**

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
4.5	10/09/2018	130150-00012	Date of first issue: 05/27/2015

---

**Domestic regulation****TDG**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****The ingredients of this product are reported in the following inventories:**

DSL	:	All components of this product are on the Canadian DSL
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
AICS	:	All ingredients listed or exempt.

---

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -



# SAFETY DATA SHEET



## GGT

Version 4.5	Revision Date: 10/09/2018	SDS Number: 130150-00012	Date of last issue: 10/01/2018 Date of first issue: 05/27/2015
----------------	------------------------------	-----------------------------	---

---

No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/09/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8