

# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

### SECTION 1. IDENTIFICATION

Product name : MR. B  
Other means of identification : No data available  
SDS-Identcode : 028G

#### Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation  
Address : 2777 N. Stemmons Frwy Ste 1800  
Dallas TX 75207,  
Telephone : 855-243-9164/972-865-8961  
Telefax : 214-631-3047  
E-mail address : www.bestolife.com

#### Recommended use of the chemical and restrictions on use

Recommended use : Industrial use  
Thread Compound (Pipe Dope) and Jacking grease for use in  
Offshore industries  
Mining, (without offshore industries)  
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-  
pheres.


---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Carcinogenicity : Category 2  
Reproductive toxicity : Category 1A  
Effects on or via lactation  
Specific target organ systemic toxicity - repeated exposure : Category 1 (Kidney, Central nervous system, Blood)

#### GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H351 Suspected of causing cancer.  
H360FD May damage fertility. May damage the unborn child.  
H362 May cause harm to breast-fed children.  
H372 Causes damage to organs (Kidney, Central nervous system, Blood) through prolonged or repeated exposure.

# SAFETY DATA SHEET



**MR. B**

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
P263 Avoid contact during pregnancy and while nursing.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

**Storage:**  
P405 Store locked up.

**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

## Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 30 - < 60
Talc	14807-96-6	>= 30 - < 60
Lead	7439-92-1	>= 10 - < 30
12-Hydroxy lithium stearate	7620-77-1	>= 1 - < 5
Calcium bis(di C8-C10, branched, C9 rich, alkyl)naphthalenesulphonate)	57855-77-3	>= 1 - < 5
Quartz	14808-60-7	>= 1 - < 5

Actual concentration or concentration range is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.

# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

In case of eye contact : Wash clothing before reuse.  
Thoroughly clean shoes before reuse.  
: Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Suspected of causing cancer.  
May damage fertility. May damage the unborn child.  
May cause harm to breast-fed children.  
Causes damage to organs through prolonged or repeated exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Lead compounds  
Metal oxides  
Silicon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.

# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : Do not get on skin or clothing.  
Do not swallow.  
Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Organic peroxides  
Explosives  
Gases

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Mist)	1 mg/m <sup>3</sup>	CA BC OEL
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH
Talc	14807-96-6	TWAEV (respirable dust)	3 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable particulates)	2 mg/m <sup>3</sup>	CA AB OEL

# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
 Date of first issue: 05/27/2015

		TWA (Respirable)	2 mg/m <sup>3</sup>	CA BC OEL
		TWA	2 fibres per cubic centimeter	CA ON OEL
		TWA (Respirable fraction)	2 mg/m <sup>3</sup>	CA ON OEL
		TWA (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIH
Lead	7439-92-1	TWA	0.05 mg/m <sup>3</sup>	CA AB OEL
		TWA	0.05 mg/m <sup>3</sup>	CA BC OEL
		TWA	0.05 mg/m <sup>3</sup> (Lead)	CA ON OEL
		TWAEV	0.05 mg/m <sup>3</sup> (Lead)	CA QC OEL
		TWA	0.05 mg/m <sup>3</sup> (Lead)	ACGIH
12-Hydroxy lithium stearate	7620-77-1	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (Inhalable fraction)	10 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable fraction)	3 mg/m <sup>3</sup>	ACGIH
Quartz	14808-60-7	TWA (Respirable particulates)	0.025 mg/m <sup>3</sup>	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m <sup>3</sup>	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable)	0.025 mg/m <sup>3</sup> (Silica)	CA BC OEL
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH

**These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.**

Quartz

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Lead	7439-92-1	Lead (Lead)	In blood	Not critical	200 µg/l	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.  
 Dust formation may be relevant in the processing of this

# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m<sup>3</sup> - total dust, 5 mg/m<sup>3</sup> - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m<sup>3</sup> - respirable particles, 10 mg/m<sup>3</sup> - inhalable particles.

### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Combined particulates and organic vapor type
- Hand protection
- Material : Chemical-resistant gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:  
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.
- 

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Viscous semi-solid
- Color : black
- Odor : Petroleum
- Odor Threshold : No data available
- pH : Not applicable (not an aqueous solution)
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Flash point :  $\geq 200$  °C

Method: ASTM D 92, Cleveland open cup

# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

Distillates (petroleum), hydrotreated heavy naphthenic

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 1.5

Density : No data available

Solubility(ies)  
Water solubility : negligible

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : No data available  
Viscosity, kinematic : Not applicable

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available  
Particle size : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : Can react with strong oxidizing agents.  
Conditions to avoid : None known.  
Incompatible materials : Oxidizing agents  
Hazardous decomposition products : No hazardous decomposition products are known.

**MR. B**

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
5.2	10/11/2018	133860-00016	Date of first issue: 05/27/2015

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: Based on data from similar materials

**Talc:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

**Lead:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Remarks: Based on data from similar materials

**12-Hydroxy lithium stearate:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: Based on data from similar materials



# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

### **Quartz:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

### **Skin corrosion/irritation**

Not classified based on available information.

### **Components:**

#### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### **Talc:**

Species : Rabbit  
Result : No skin irritation

#### **Lead:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### **12-Hydroxy lithium stearate:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### **Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Components:**

#### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

#### **Talc:**

Species : Rabbit  
Result : No eye irritation

#### **Lead:**

Species : Rabbit  
Result : No eye irritation

# SAFETY DATA SHEET



**MR. B**

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

**12-Hydroxy lithium stearate:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Remarks : Based on data from similar materials

**Respiratory or skin sensitization**

**Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:**

**Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

**Talc:**

Routes of exposure : Skin contact  
Species : Humans  
Result : negative

**Lead:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative  
Remarks : Based on data from similar materials

**12-Hydroxy lithium stearate:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative

# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

### **Calcium bis(di C8-C10, branched, C9 rich, alkyl)naphthalenesulphonate):**

Test Type : Human repeat insult patch test (HRIPT)  
Routes of exposure : Skin contact  
Result : negative

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

#### **Talc:**

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro  
Species: Rat  
Application Route: Ingestion  
Result: negative

#### **Lead:**

Genotoxicity in vitro : Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Ingestion  
Result: positive  
Remarks: Based on data from similar materials

### **Calcium bis(di C8-C10, branched, C9 rich, alkyl)naphthalenesulphonate):**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

### **Carcinogenicity**

Suspected of causing cancer.

#### **Product:**

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

#### **Components:**

##### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 78 weeks  
Method : OECD Test Guideline 451  
Result : negative

##### **Talc:**

Species : Mouse  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Result : negative

##### **Lead:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : positive  
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

##### **Quartz:**

Species : Humans  
Application Route : inhalation (dust/mist/fume)  
Result : positive  
Remarks : IARC: (International Agency for Research on Cancer)  
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

### **Reproductive toxicity**

May damage fertility. May damage the unborn child.  
May cause harm to breast-fed children.

#### **Components:**

##### **Talc:**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat

# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

Application Route: Ingestion  
Result: negative

### Lead:

- Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Mouse  
Application Route: Ingestion  
Result: positive  
Remarks: Based on data from similar materials
- Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: positive  
Remarks: Based on data from similar materials
- Reproductive toxicity - Assessment : Positive evidence of adverse effects on sexual function and fertility from human epidemiological studies., Positive evidence of adverse effects on development from human epidemiological studies., Studies indicating a hazard to babies during the lactation period

### STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Causes damage to organs (Kidney, Central nervous system, Blood) through prolonged or repeated exposure.

### Components:

#### Lead:

- Target Organs : Kidney, Central nervous system, Blood  
Assessment : Causes damage to organs through prolonged or repeated exposure.

#### 12-Hydroxy lithium stearate:

- Routes of exposure : Ingestion  
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

#### Quartz:

- Routes of exposure : inhalation (dust/mist/fume)  
Target Organs : Lungs  
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

# SAFETY DATA SHEET



MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

## Repeated dose toxicity

### Components:

#### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rat  
NOAEL : > 0.98 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 28 Days  
Remarks : Based on data from similar materials

#### **Lead:**

Species : Rat  
NOAEL : 0.0015 mg/kg  
LOAEL : 0.005 mg/kg  
Application Route : Ingestion  
Exposure time : 6 - 12 Months  
Remarks : Based on data from similar materials

#### **12-Hydroxy lithium stearate:**

Species : Rat  
NOAEL : > 88 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

#### **Quartz:**

Species : Humans  
LOAEL : 0.053 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

## Aspiration toxicity

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d  
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l  
Exposure time: 10 min  
Remarks: Based on data from similar materials

### Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l  
Exposure time: 24 h

### Lead:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.107 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 0.029 mg/l  
Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.025 mg/l  
Exposure time: 72 h

EC10 (Pseudokirchneriella subcapitata (green algae)): 6.1 µg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : EC10 (Pimephales promelas (fathead minnow)): 20 µg/l  
Exposure time: 30 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Ceriodaphnia dubia (water flea)): 1.7 µg/l  
Exposure time: 7 d

### 12-Hydroxy lithium stearate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

### **Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

- Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC10: 110 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

### **Quartz:**

#### **Ecotoxicology Assessment**

- Acute aquatic toxicity : No toxicity at the limit of solubility.
- Chronic aquatic toxicity : No toxicity at the limit of solubility.

#### **Persistence and degradability**

##### **Components:**

#### **Distillates (petroleum), hydrotreated heavy naphthenic:**

- Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

#### **12-Hydroxy lithium stearate:**

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 78 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

### **Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

- Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 16 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B  
Remarks: Based on data from similar materials

#### **Bioaccumulative potential**

No data available



# SAFETY DATA SHEET



**MR. B**

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.  
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

**International Regulations**

**UNRTDG**

UN number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Lead)  
Class : 9  
Packing group : III  
Labels : 9

**IATA-DGR**

UN/ID No. : UN 3077  
Proper shipping name : Environmentally hazardous substance, solid, n.o.s. (Lead)  
Class : 9  
Packing group : III  
Labels : Miscellaneous  
Packing instruction (cargo aircraft) : 956  
Packing instruction (passenger aircraft) : 956  
Environmentally hazardous : yes

**IMDG-Code**

UN number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Lead)  
Class : 9  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : yes

---

# SAFETY DATA SHEET



## MR. B

Version 5.2      Revision Date: 10/11/2018      SDS Number: 133860-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/27/2015

---

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### TDG

UN number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Lead)  
Class : 9  
Packing group : III  
Labels : 9  
ERG Code : 171  
Marine pollutant : yes(Lead)

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

### The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL  
TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.  
AICS : All ingredients listed or exempt.

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
CA AB OEL / TWA : 8-hour Occupational exposure limit  
CA AB OEL / STEL : 15-minute occupational exposure limit  
CA BC OEL / TWA : 8-hour time weighted average  
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)  
CA QC OEL / TWAEV : Time-weighted average exposure value  
CA QC OEL / STEV : Short-term exposure value

---

# SAFETY DATA SHEET



## MR. B

Version	Revision Date:	SDS Number:	Date of last issue: 10/01/2018
5.2	10/11/2018	133860-00016	Date of first issue: 05/27/2015

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/11/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8