

STINGER® WATER WELL



5 Gallon Plastic Pail

PRODUCT CHARACTERISTICS

Color:	Copper
Penetration: (ASTM D217)	310-330
NLGI Grade:	1
Weight/Gallon:	10.2 pounds/gallon
Thickener:	Calcium
Fluid Type:	Petroleum
Dropping Point: (ASTM D2265)	≥300°F (≥149°C)
Flash Point:	≥325°F (≥162.8°C)
Brushable To:	-40°F (-40°C)
Service Rating:	400°F (204°C)
Shelf Life: (Unopened container)	4 years
Contains:	Copper, graphite, and other non metallic additives

*NSF Registration No. 156756 Category Code: H2

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

DESCRIPTION

STINGER® Water Well is a copper-based drilling compound designed for exceptional performance. It is especially effective in lower temperature environments but has the versatility to be used year-round. STINGER® Water Well is designed to provide galling and seizing protection on water well drill pipe and drill collars. NSF H2 registered.*

APPLICATIONS

Recommended for use on water well drill pipe. Low temperature field application is enhanced through the use of premium quality, low temperature base grease, making it an outstanding choice for environments reaching below 0°F.

TECHNICAL DATA

- Finely powdered copper, graphite and special non-metallic additives absorb stresses and enhance performance properties
- ALL SEASON formula allows for easier application in lower temperatures
- Premium thread protection
- Resistant to wash-off and will not harden or bleed excessively in storage

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
657010	1 gallon	10 pounds plastic
657025	3 ½ gallon	25 pounds plastic
657050	5 gallon	50 pounds plastic

Note: All package sizes are not listed. Call your sales representative for a complete listing.

