

DRILLING COMPOUND

WHITE COLLAR



5 Gallon Plastic Pail

PRODUCT CHARACTERISTICS

Color:	Light Gray
Penetration: (ASTM D217)	265-295
NLGI Grade:	2
Weight/Gallon:	11.4 pounds/gallon
Thickener:	Lithium
Fluid Type:	Petroleum
Dropping Point: (ASTM D2265)	≥350°F (≥177°C)
Flash Point:	≥392°F (≥200°C)
Brushable To:	10°F (-12°C)
Service Rating:	500°F (260°C)
Friction Factor:	1.0*
Shelf Life: (Unopened container)	4 years
Contains:	Zinc oxide, PTFE, and other nonmetallic additives

*NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

DESCRIPTION

BESTOLIFE® White Collar is a versatile, effective, and economical drill collar compound that combines zinc oxide and PTFE to enhance sealing and galling resistance for both new and worn connections. It resists extreme pressure and wear.

APPLICATIONS

Zinc/PTFE compound for drill collars.

TECHNICAL DATA

White Collar is an effective, yet economical drill collar compound that can be used in a wide range of drilling conditions. The combination of zinc oxide and a high percentage of PTFE provides both enhanced sealing and galling resistance in a compound that can be used on both new and worn connections. White Collar includes a high level of extreme pressure and anti-wear additives that will help to reduce collar wear and damage that results in expensive re-works. White Collar contains a high-quality lubricating base grease formulated with H₂S and oxidation inhibitors.

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
626050	5 gallon	50 pounds plastic

Note: All package sizes are not listed. Call your sales representative for a complete listing.

