

BESTOLIFE® ZN-18



5 Gallon Plastic Pail

PRODUCT CHARACTERISTICS

Color:	Gray
Penetration: (ASTM D217)	300-320
NLGI Grade:	1
Weight/Gallon:	12.5 pounds/gallon
Thickener:	Lithium
Fluid Type:	Petroleum
Dropping Point: (ASTM D2265)	≥350°F (≥177°C)
Flash Point:	≥392°F (≥200°C)
Brushable To:	10°F (-12°C)
Service Rating:	350°F (177°C)
Shelf Life: (Unopened container)	4 years
Contains:	Zinc and other nonmetallic additives

*NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

DESCRIPTION

BESTOLIFE® ZN-18 is a zinc-based thread compound designed to resist corrosion, pitting, and discoloration on threaded connections.

APPLICATIONS

Zinc-based compound for light duty drilling.

TECHNICAL DATA

ZN-18 will provide galling and seizing protection for threaded connections used in light duty applications. Contains 18% powdered metallic zinc, as well as H₂S, rust and corrosion inhibitors.

NOTES

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
620015	2 gallon	15 pounds plastic
620060	5 gallon	60 pounds plastic

Note: All package sizes are not listed. Call your sales representative for a complete listing.

