

BESTOLIFE ZN-60



5 Gallon Metal Pail

PRODUCT CHARACTERISTICS

Color:	Gray
Penetration: (ASTM D217)	290-310
NLGI Grade:	1.5
Weight/Gallon:	16.3 pounds/gallon
Thickener:	Lithium
Fluid Type:	Petroleum
Dropping Point: (ASTM D2265)	≥350°F (≥177°C)
Flash Point:	490°F (254°C)
Brushable To:	10°F (-12°C)
Service Rating:	350°F (177°C)
Friction Factor:	1.0*
Shelf Life: (Unopened container)	4 years
Contains:	Zinc and other nonmetallic additives

*API RP 7A1: "Recommended Practice for Testing of Thread Compound for Rotary-Shouldered Connections" NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

DESCRIPTION

BESTOLIFE ZN-60 is a zinc-based thread compound recommended for drilling, tool joints, drill collars, and coring bits. It contains 60% finely powdered metallic zinc, plus H₂S and oxidation inhibitors.

APPLICATIONS

Zinc-based thread compound recommended for drilling, tool joints, drill collars, and coring bits.

TECHNICAL DATA

ZN-60 is a zinc-based thread compound made with finely powdered metallic zinc. It contains 60% zinc as well as H₂S and oxidation inhibitors. Meets the requirements of API RP SPEC 7: "Specification for Rotary Drill Stem Elements".

NOTES

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
623340	3 1/2 gallon	40 pounds plastic
623370	5 gallon	70 pounds metal

Note: All package sizes are not listed. Call your sales representative for a complete listing.

