

TECHNICAL DATA SHEET

PSD Matte HN/RLD Imagesetting Film .004

Application	PSD Matte is a matte based imagesetting film designed for use in recorders with helium neon lasers and red laser diodes.
Features	<ul style="list-style-type: none">• Excellent sharpness• Wide exposure and development latitude• High practical density• Linear output for conventional screening• Approved for stochastic screening• Anti-static protection• Rapid, uniform vacuum drawdown
Spectral Sensitivity	633 - 670 NM
Exposure Guideline	Adjust image intensity to achieve a density of 4.8. Then run standard calibration software to achieve desired dot values in each step.
Processing:	
Developer	PSD Majestic 650 Developer 2:1, 95°F or 35°C for 20 - 40 sec.
Fixer	PSD URFC Fixer 3:1
Hardener	PSD Hardener 72 oz. to 20 gal.
Replenishment	PSD 650 Developer at .4 cc/sq. in. PSD URFC Fixer at .5 cc/sq. in.
Safelight Handling	EncapSulite T20/ND.75 dark green safelight, no closer than 4 feet.
Storage	Store in a cool, dry area below 70°F or 21°C and at 55% relative humidity.

PRINTING SUPPLIES DIRECT

50 Fernstead Lane - Berlin, CT, 06037 - Phone 877-799-0795

Email - contact@printingsuppliesdirect.com

www.printingsuppliesdirect.com