(Casterland

Light & General Duty



LIGHT & ENERAL DUT CASTERS



PNEUMATIC WHEEL CASTERS



LEVELLING CASTERS



HI-TEMPERATURE CASTERS





www.Casterland.com

C a s

e

S

GSTDK229 T516 CCTW50PLTPBR





PLASTIC TWIN WHEEL CASTERS

These twin nylon wheel casters are ideal for a wide variety of home and office uses. An assortment of mounting options are available to suit any application. Optional pedal brake available.

Model Number	Wheel Size	Type of Mount	Capacity	Additional Details
CCTW30PLTP	30mm	Top Plate	40 lbs	
GSTDK229 T516	37mm	5/16" x 5/8" Thread	40 lbs	Non-Hood
GSTDKF229 T516	37mm	5/16" x 5/8" Thread	40 lbs	Non-Hood, Brake
CCTW40PLTP	40mm	Top Plate	40 lbs	
CCTW40PLTPBR	40mm	Top Plate	40 lbs	Brake
CCTW40PLWS	40mm	Wood Stem	40 lbs	
CCTW40PLWSBR	40mm	Wood Stem	40 lbs	Brake
CCTW40PLUB	40mm	5/8" U-Bracket	40 lbs	
CCTW50PLTP	50mm	Top Plate	75 lbs	
CCTW50PLTPBR	50mm	Top Plate	75 lbs	Brake
CCTW50PLFR716X1	50mm	7/16" x 1" Friction Ring Stem	75 lbs	
CCTW50PLFR716X78 B	50mm	7/16" Friction Ring Stem	75 lbs	
CCTW50URFR716X78 B	50mm	7/16" Friction Ring Stem	75 lbs	Urethane
CCTW50PLFR716X1BR	50mm	7/16" x 1" Friction Ring Stem	75 lbs	Brake
CCTW50PLFR716 BLOFF	50mm	7/16" Friction Ring Stem	75 lbs	Sit down to unlock
CCTW50PLFR716 BLON	50mm	7/16" Friction Ring Stem	75 lbs	Sit down to lock
CCTW50PLTS14X34	50mm	1/4" Threaded Stem	75 lbs	
CCTW50PLTS14X34BR	50mm	1/4" Threaded Stem	75 lbs	Brake
CCTW50PLTS38X34	50mm	3/8" Threaded Stem	75 lbs	
CCTW50PLTS38X34BR	50mm	3/8" Threaded Stem	75 lbs	Brake
CCTW50PLTS516X34BR	50mm	5/16" Threaded Stem	75 lbs	
CCTW50PLTS516X34BR	50mm	5/16" Threaded Stem	75 lbs	Brake
CCTW50PLWS CCTW50PLWSBR	50mm	Wood Stem	75 lbs	
	50mm	Wood Stem	75 lbs	Brake

Helpful Hint...

Since all twin wheeled casters look alike, when selecting one it is best to bring a sample into a Casterland location so we can match the one that you need. You must bring in both the body and stem as stems are not interchangeable from one manufacturer to another.

For office chairs the 7/16" Friction Ring Stem is most common.

GSS10 T38X1

GSS10 SC10X22

GSS10 SC716x78

GSS10 SC38X1

EUROPEAN TWIN WHEEL CASTERS

Designed for our customers who use metric sizes, these German made twin-wheel casters can be mixed and matched with the stem types below to fit your needs.



3/8" x 1"

7/16" x 7/8"

10mm x 22mm

3/8" x 22mm

GSUKF96 24B (GSS10 FTP)



GSUKF96 24B (GSS10 FR10X22)

Model Number		Who Siz		Capacity			
GSUK97 24B GSUKF96 24B GSSUK132 24B		50m 50m 55m	im	75 lbs 75 lbs 120 lbs	1	Black, hooded, soft Black, hooded, soft Black, steelcase, no	, brake
STEM OPTIONS							
Plate style Threaded Stem	- -	GSS10 FTP GSS10 T10X15	-	38mm x 38mm 10mm x 15mm	Friction Ring	Threaded	Plate
Threaded Stem Threaded Stem	-	GSS10 T8X15 GSS10 T12X15	-	8mm x 15mm 12mm x 15mm	(7)		G 25mm 0
Threaded Stem Threaded Stem	-	GSS10 T14X1 GSS10 T516X1	-	1/4" x 1" 5/16" x 1"		THE STATE OF THE S	25mm

Threaded Stem

Friction Ring Stem Friction Ring Stem

Friction Ring Stem





"PACER" SERIES TWIN WHEEL CASTERS

These hooded die-cast twin wheel casters offer different finishes with an assortment of mounting stems. They also have optional urethane wheels to help prevent floors from getting scratched.

SHPA50000BC U

SHPA50000FB U

Model Number	Wheel Size	Wheel Material	Capacity	Colour
SHPA50000FB U	50mm	Polyurethane	75 lbs	Flat Black
SHPA50000BC U	50mm	Polyurethane	75 lbs	Bright Chrome
SHPA50000BR U	50mm	Polyurethane	75 lbs	Brass Plate
SHPA60000FB U	60mm	Polyurethane	100 lbs	Flat Black
SHPA60000BC U	60mm	Polyurethane	100 lbs	Bright Chrome
SHPA60000BR U	60mm	Polyurethane	100 lbs	Brass Plate
CTEM ORTIONS				

1	ST	EM	0	PT	10	NS

Wheel	Part #	Stem Type	<u>Size</u>				
	SHSE 101	Plate	1-1/2" x 1-1/2" Square Plate				
50mm	SHSE 223	Friction Ring	7/16" x 7x8"				
	SHSE 605	Threaded	3/8" x 3/4" UNC				
60mm	SHPL 101	Plate	1-1/2" x 1-1/2" Square Plate				
00111111	SHPL 302	Wood	5/16" x 1-1/2"				
	SHPL 525	Threaded	5/16" x 1-1/2" UNC				
	Many more stem sizes and styles available						

CCBC FTPB



HOODED BALL CASTERS

These rugged ball casters are an attractive compliment to any piece of office furniture or home application. The unique wide-tread design gives maximum mobility and carpet protection. Not suitable for wood or tile flooring.

Model Number	Wheel Size	Type of Mount	Capacity	Additional Details
CCBC FTP	50mm	Full Top Plate	75 lbs	Chrome
CCBC FTPB	50mm	Full Top Plate	75 lbs	Brass
CCBC SC	50mm	7/16" Friction Ring	75 lbs	Chrome
CCBC SC1B	50mm	7/16" x 1" Friction Ring	75 lbs	Brass
CCBC TS516	50mm	5/16" x 1" Threaded	75 lbs	Chrome
CCBC TS516B	50mm	5/16" x 1" Threaded	75 lbs	Brass
CCBC WS	50mm	Wood Stem	75 lbs	Chrome
CCBC WSB	50mm	Wood Stem	75 lbs	Brass

SHUT100000BK U





SHUT100000BK U B


"Ultima" SERIES TWIN WHEEL CASTERS

Shepherd Ultima series hoodless twin wheel casters. All nylon construction. Steel axle and fastening. These casters come with Urethane wheels to provide best non-marking protection for all floor surfaces and help provide a quiet smooth roll. There are a variety of sturdy mounting stems found below.

Model Number	Wheel Size	Capacity	Additional Details	
SHUT60000BK U	60mm	100 lbs	Black, non-hooded	
SHUT75000BK U	75mm	165 lbs	Black, non-hooded	
SHUT75000BK U B	75mm	165 lbs	Black, non-hooded, brake	
SHUT100000BK U	100mm	175 lbs	Black, non-hooded	
SHUT100000BK U B	100mm	175 lbs	Black, non-hooded, brake	

STEM OPTIONS

SIEW OPI	IONS		
Wheel Size	Part #		<u>Size</u>
50mm - 60mm	SHUT56 223	-	7/16" x 7/8" Friction Ring
75mm	SHUT75 101	-	1-1/2" x 1-1/2" Plate 1x 1" Bolt Hole
	SHUT75 116	-	2-9/16 x 2-3/16" Plate 2x 1-5/8" Bolt Holes
	SHUT75 223	-	7/16" x 7/8" Friction Ring
400	SHUT75 637	-	3/8" x 3/4" UNC Threaded Stem
100mm	SHUT100 211	-	7/16" x 1-7/16" Friction Ring
	SHUT100 116	-	2-9/16" x 2-3/16" Plate 2x 1-5/8" Bolt Holes
	SHLIT100 637		3/8" v 3/4" LINC Threaded



Light duty, zinc-plated casters with a urethane wheel. Ideal for light loads and where height limitations are a factor. Available in a variety of mounting types. Rigid casters available only with a





CCLC3078URSTS38X1.5SB

top plate mounting style.

Model Number	Wheel Size	Overall Height	Type of Mount	Capacity	Brake?	Swivel/ Rigid
CCLC2078URSLP	2"	2-5/8"	Large Top Plate	125 lbs	-	Swivel
CCLC2078URSLPSB	2"	2-5/8"	Large Top Plate	125 lbs	Yes	Swivel
CCLC2078URRLP	2"	2-5/8"	Large Top Plate	125 lbs	-	Rigid
CCLC2078URSSP	2"	2-5/8"	Small Top Plate	125 lbs	_	Swivel
CCLC2078URSSPSB	2"	2-5/8"	Small Top Plate	125 lbs	Yes	Swivel
CCLC2078URFR	2"	2-5/8"	7/16" x 1 3/8" Friction Ring	125 lbs	-	Swivel
CCLC2078URFR1	2"	2-5/8"	7/16" x 1" Friction Ring	125 lbs	_	Swivel
CCLC2078URFRSB	2"	2-5/8"	1-3/8" Friction Ring	125 lbs	Yes	Swivel
CCLC2078URSTS38X1	2"	2-5/8"	3/8" x 1" Threaded Stem	125 lbs	-	Swivel
CCLC2078URSTS38X1SB	2"	2-5/8"	3/8" x 1" Threaded Stem	125 lbs	Yes	Swivel
CCLC2078URSTS38X1.5	2"	2-5/8"	3/8" x 1-1/2" Threaded Stem	125 lbs	-	Swivel
CCLC2078URSTS38X1.5SB	2"	2-5/8"	3/8" x 1-1/2" Threaded Stem	125 lbs	Yes	Swivel
CCLC2078URSTS516	2"	2-5/8"	5/16" x 1" Threaded Stem	125 lbs	-	Swivel
CCLC2078URSTS516SB	2"	2-5/8"	5/16" x 1" Threaded Stem	125 lbs	Yes	Swivel
CCLC2078URSWS	2"	2-5/8"	5/16" Wood stem	125 lbs	163	Swivel
CCLC2078URSWSSB	2"	2-5/8"	5/16" Wood stem	125 lbs	Yes	Swivel
CCLCZ0760N3W33B	2	2-3/0	3/10 Wood stem	123 105	165	Swivei
CCLC2578URSLP	2.5"	3-1/8"	Large Top Plate	125 lbs	-	Swivel
CCLC2578URSLPSB	2.5"	3-1/8"	Large Top Plate	125 lbs	Yes	Swivel
CCLC2578URRLP	2.5"	3-1/8"	Large Top Plate	125 lbs	-	Rigid
CCLC2578URSSP	2.5"	3-1/8"	Small Top Plate	125 lbs	=	Swivel
CCLC2578URSSPSB	2.5"	3-1/8"	Small Top Plate	125 lbs	Yes	Swivel
CCLC2578URFR	2.5"	3-1/8"	7/16" Friction Ring	125 lbs	=	Swivel
CCLC2578URFRSB	2.5"	3-1/8"	7/16" Friction Ring	125 lbs	Yes	Swivel
CCLC2578URSTS38X1	2.5"	3-1/8"	3/8" x 1" Threaded Stem	125 lbs	-	Swivel
CCLC2578URSTS38X1SB	2.5"	3-1/8"	3/8" x 1" Threaded Stem	125 lbs	Yes	Swivel
CCLC2578URSTS38X1.5	2.5"	3-1/8"	3/8" x 1.5" Threaded Stem	125 lbs	-	Swivel
CCLC2578URSTS38X1.5SB	2.5"	3-1/8"	3/8" x 1.5" Threaded Stem	125 lbs	Yes	Swivel
CCLC2578URSTS516	2.5"	3-1/8"	5/16" x 1" Threaded Stem	125 lbs	-	Swivel
CCLC2578URSTS516SB	2.5"	3-1/8"	5/16" Threaded Stem	125 lbs	Yes	Swivel
CCLC2578URSWS	2.5"	3-1/8"	5/16" Wood stem	125 lbs	-	Swivel
CCLC2578URSWSSB	2.5"	3-1/8"	5/16" Wood stem	125 lbs	Yes	Swivel
CCLC3078URSLP	3"	3-11/16"	Large Top Plate	125 lbs	_	Swivel
CCLC3078URSLPSB	3"	3-11/16"	Large Top Plate	125 lbs	Yes	Swivel
CCLC3078URRLP	3"	3-11/16"	Large Top Plate	125 lbs	-	Rigid
CCLC3078URFR	3"	3-11/16"	7/16" Friction Ring	125 lbs	- -	Swivel
CCLC3078URFRSB	3"	3-11/16"	7/16 Friction Ring 7/16" Friction Ring	125 lbs 125 lbs	Yes	Swivel
CCLC3078URFRSB	3" 3"	3-11/16"	3/8x1.5" Threaded Stem	125 lbs 125 lbs	yes -	Swivel
CCLC3078URSTS38X1.5	3" 3"	3-11/16"	3/8x1.5 Threaded Stem 3/8x1.5" Threaded Stem	125 lbs 125 lbs	Yes	Swivel
	3"					
CCLC3078URSTS38X1		3-11/16"	3/8x1" Threaded Stem	125 lbs	<u>-</u>	Swivel
CCLC3078URSTS38X1SB	3"	3-11/16"	3/8x1" Threaded Stem	125 lbs	Yes	Swivel
CCLC3078URSWS	3" 3"	3-11/16"	5/16" Wood Stem	125 lbs	<u>-</u>	Swivel
CCLC3078URSWSSB	3 "	3-11/16"	5/16" Wood Stem	125 lbs	Yes	Swivel

LC Series mount types and specifications

Stem & **Threaded** Wood **Top Plate** Friction Stem Stem Ring

Large Top Plate (LP): 1-1/2" x 2-1/2" Mounting holes: 1" x 2-1/8" Small Top Plate (SP): 1-3/16" x 2" Mounting Holes: 13/16" x 1-9/16"

Threaded Stem (TS): 5/16"-18 x 1" or 3/8"-16 x 1"

Friction Ring (FR): 7/16" x 1-3/8" Friction Ring (FR1): 7/16" x 1" Wood Stem (WS): 5/16"

CCEP5125TPSPBTB





Top Plate: 3-3/4" x 3" **Mounting Holes:** 1-3/4" x 3" Slotted to 2-3/8" x 3-1/8"

EP SERIES 210 - 300 lbs

One of our series unique to Casterland. These casters have a plate style able to cover many different models of casters and come with precision ball bearings in the wheels.

Optional 2-5/8" x 3-3/4" top plate available. 1-3/4" x 2-7/8" mounting holes slotted to 1-3/4" x 3"

CCEP5125UNRPB

Also available in stainless steel.

Model Number	Wheel Size	Overall Height	Type of Wheel	Capacity	Brake?	Swivel/ Rigid
CCEP3125TPSPB	3"	4-1/4"	Thermal Plastic Rubber	210 lbs	_	Swivel
CCEP3125TPRPB	3"	4-1/4"	Thermal Plastic Rubber	210 lbs	_	Rigid
CCEP3125TPSPBSB	3"	4-1/4"	Thermal Plastic Rubber	210 lbs	Yes	Swivel
CCEP3125TPSPBTB	3"	4-1/4"	Thermal Plastic Rubber	210 lbs	Total	Swivel
CCEP3125UNSPB	3"	4-1/4"	Urethane/Nylon	250 lbs	-	Swivel
CCEP3125UNRPB	3"	4-1/4"	Urethane/Nylon	250 lbs	-	Rigid
CCEP3125UNSPBSB	3"	4-1/4"	Urethane/Nylon	250 lbs	Yes	Swivel
CCEP3125UNSPBTB	3"	4-1/4"	Urethane/Nylon	250 lbs	Total	Swivel
CCEP4125TPSPB	4"	5-1/4"	Thermal Plastic Rubber	250 lbs	_	Swivel
CCEP4125TPRPB	4"	5-1/4"	Thermal Plastic Rubber	250 lbs	_	Rigid
CCEP4125TPSPBSB	4"	5-1/4"	Thermal Plastic Rubber	250 lbs	Yes	Swivel
CCEP4125TPSPBTB	4"	5-1/4"	Thermal Plastic Rubber	250 lbs	Total	Swivel
CCEP4125UNSPB	4"	5-1/4"	Urethane/Nylon	300 lbs	_	Swivel
CCEP4125UNRPB	4"	5-1/4"	Urethane/Nylon	300 lbs	_	Rigid
CCEP4125UNSPBSB	4"	5-1/4"	Urethane/Nylon	300 lbs	Yes	Swivel
CCEP4125UNSPBTB	4"	5-1/4"	Urethane/Nylon	300 lbs	Total	Swivel
CCEP5125TPSPB	5"	6-1/4"	Thermal Plastic Rubber	300 lbs	_	Swivel
CCEP5125TPRPB	5"	6-1/4"	Thermal Plastic Rubber	300 lbs	_	Rigid
CCEP5125TPSPBSB	5"	6-1/4"	Thermal Plastic Rubber	300 lbs	Yes	Swivel
CCEP5125TPSPBTB	5"	6-1/4"	Thermal Plastic Rubber	300 lbs	Total	Swivel
CCEP5125UNSPB	5"	6-1/4"	Urethane/Nylon	300 lbs	_	Swivel
CCEP5125UNRPB	5"	6-1/4"	Urethane/Nylon	300 lbs	_	Rigid
CCEP5125UNSPBSB	5"	6-1/4"	Urethane/Nylon	300 lbs	Yes	Swivel
CCEP5125UNSPBTB	5"	6-1/4"	Urethane/Nylon	300 lbs	Total	Swivel

MEDIUM HEAVY DUTY 440 - 550 lbs

Part	Wheel	Weight	Additional
Number	Size	Capacity	Details
BLLK-PATH 100K-1-FI-FK	100MM X 32MM	440 lbs	Total lock plate caster, thermoplastic wheel, PB Swivel plate caster, thermoplastic wheel, PB Rigid plate caster, thermoplastic wheel, PB Total lock plate caster, thermoplastic wheel, PB Swivel plate caster, thermoplastic wheel, PB Rigid plate caster, thermoplastic wheel, PB
BLLK-PATH 100K-1-FK	100MM X 32MM	440 lbs	
BLBK-PATH 100K-1-FK	100MM X 32MM	440 lbs	
BLLK-PATH 125K-1-FI-FK	125MM X 32MM	550 lbs	
BLLK-PATH 125K-1-FK	125MM X 32MM	550 lbs	
BLBK-PATH 125K-1-FK	125MM X 32MM	550 lbs	





BLLK-PATH 100K-1-FK





CCMB3125UNSPBB

CCMB5125TPSPBTB

Medium duty bolthole caster designed for applications where top plate mounting is impractical. Using the same double ball raceway construction as our MS series, these swivel casters are able to be mounted with a nut & bolt or any of our standard and custom stems listed below.

Also available in stainless steel.

Model Number	Wheel Size	Wheel Type	Overall Height	Capacity	Brake?
CCMB3125TPSPB	3"	Thermal Plastic Rubber	4-1/4"	210 lbs	-
CCMB3125TPSPBSB	3"	Thermal Plastic Rubber	4-1/4"	210 lbs	Yes
CCMB3125TPSPBTB	3"	Thermal Plastic Rubber	4-1/4"	210 lbs	Total
CCMB3125UNSPB	3"	Urethane/Nylon	4-1/4"	250 lbs	=
CCMB3125UNSPBSB	3"	Urethane/Nylon	4-1/4"	250 lbs	Yes
CCMB3125UNSPBTB	3"	Urethane/Nylon	4-1/4"	250 lbs	Total
CCMB4125TPSPB	4"	Thermal Plastic Rubber	5-1/4"	250 lbs	-
CCMB4125TPSPBSB	4"	Thermal Plastic Rubber	5-1/4"	250 lbs	Yes
CCMB4125TPSPBTB	4"	Thermal Plastic Rubber	5-1/4"	250 lbs	Total
CCMB4125UNSPB	4"	Urethane/Nylon	5-1/4"	300 lbs	-
CCMB4125UNSPBSB	4"	Urethane/Nylon	5-1/4"	300 lbs	Yes
CCMB4125UNSPBTB	4"	Urethane/Nylon	5-1/4"	300 lbs	Total
CCMB5125TPSPB	5"	Thermal Plastic Rubber	6-1/4"	300 lbs	-
CCMB5125TPSPBSB	5"	Thermal Plastic Rubber	6-1/4"	300 lbs	Yes
CCMB5125TPSPBTB	5"	Thermal Plastic Rubber	6-1/4"	300 lbs	Total
CCMB5125UNSPB	5"	Urethane/Nylon	6-1/4"	300 lbs	-
CCMB5125UNSPBSB	5"	Urethane/Nylon	6-1/4"	300 lbs	Yes
CCMB5125UNSPBTB	5"	Urethane/Nylon	6-1/4"	300 lbs	Total


Stem Options

(All sizes measured using the inside dimension of the hole)

Expanding Inserts						
Round	i	Squar	е			
Model Number	O.D.	Model Number	O.D.			
CAEXR34 CAEXR78 CAEXR1 CAEXR118 CAEXR114 CAEXR138 CAEXR112	3/4" 7/8" 1" 1-1/8" 1-1/4" 1-3/8" 1-1/2"	CAEXS34 CAEXS78 CAEXS1 CAEXS138 CAEXS112	3/4" 7/8" 1" 1-3/8" 1-1/2"			

Threaded Stems						
Model Number	Threading Size	Length				
CATS12X112 CATS58X2 CATS34X2 CAPT34X1 CATS716X112	1/2" 5/8" 3/4" Pipe Thread 7/16"	1-1/2" 2" 2" 1" 1-1/2"				
The Report of the Party of the						





Square Stems					
Model Number	Stem Dimension	Length			
CASQ34X2 CASQ78X2 CASQ916X21516	3/4" 7/8" 6 9/16"	2" 2" 2-15/16"			





CCBP8200RMSRB

Top Plate: See below for options Mounting Holes: See below for options

BP SERIES 600 - 1000 lbs

This 2" wide caster is designed for easy swivelling and to take the abuse of rough, continuous service. It is constructed with a superior 5/8" nut and bolt kingpin with double ball raceways.

This caster is zinc plated for lasting wear and features a grease fitting in the swivel head for easy maintenance.

Also available in stainless steel.

Model Number	Wheel Size	Type of Wheel	Overall Height	Capacity	Swivel/ Rigid
CCBP3200UCRRB	3-1/4"	Urethane on Cast	4-1/2"	600 lbs	Swivel
CCBP3200UCSRB	3-1/4"	Urethane on Cast	4-1/2"	600 lbs	Swivel
CCBP3200PHRRB	3-1/4"	Phenolic	4-1/2"	700 lbs	Rigid
CCBP3200PHSRB	3-1/4"	Phenolic	4-1/2"	700 lbs	Swivel
CCBP4200RMRRB	4"	Rubber Moldon	5-5/8"	700 lbs	Swivel
CCBP4200RMSRB	4"	Rubber Moldon	5-5/8"	700 lbs	Rigid
CCBP4200UCRRB	4"	Urethane on Cast	5-5/8"	700 lbs	Swivel
CCBP4200UCSRB	4"	Urethane on Cast	5-5/8"	800 lbs	Swivel
CCBP4200PHRRB	4"	Phenolic	5-5/8"	800 lbs	Rigid
CCBP4200PHSRB	4"	Phenolic	5-5/8"	800 lbs	Swivel
CCBP5200RMRRB	5"	Rubber Moldon	6-1/2"	900 lbs	Swivel
CCBP5200RMSRB	5"	Rubber Moldon	6-1/2"	900 lbs	Rigid
CCBP5200UCRRB	5"	Urethane on Cast	6-1/2"	900 lbs	Swivel
CCBP5200UCSRB	5"	Urethane on Cast	6-1/2"	900 lbs	Swivel
CCBP5200PHRRB	5"	Phenolic	6-1/2"	900 lbs	Rigid
CCBP5200PHSRB	5"	Phenolic	6-1/2"	900 lbs	Swivel
CCBP6200RMRRB	6"	Rubber Moldon	7-1/2"	900 lbs	Swivel
CCBP6200RMSRB	6"	Rubber Moldon	7-1/2"	900 lbs	Rigid
CCBP6200UCRRB	6"	Urethane on Cast	7-1/2"	900 lbs	Swivel
CCBP6200UCSRB	6"	Urethane on Cast	7-1/2"	900 lbs	Swivel
CCBP6200PHRRB	6"	Phenolic	7-1/2"	900 lbs	Rigid
CCBP6200PHSRB	6"	Phenolic	7-1/2"	900 lbs	Swivel
CCBP8200RMRRB	8"	Rubber Moldon	9-1/2"	1000 lbs	Swivel
CCBP8200RMSRB	8"	Rubber Moldon	9-1/2"	1000 lbs	Rigid
CCBP8200UCRRB	8"	Urethane on Cast	9-1/2"	1000 lbs	Swivel
CCBP8200UCSRB	8"	Urethane on Cast	9-1/2"	1000 lbs	Swivel
CCBP8200PHRRB	8"	Phenolic	9-1/2"	1000 lbs	Rigid
CCBP8200PHSRB	8"	Phenolic	9-1/2"	1000 lbs	Swivel
	-	the model number - eg.			,
For Total Brakes add	"TB" at the end o	f the model number - eg.	CCBP4200RMSRBTB		

Locking Information

Side Brake (SB)

Stops the wheel from rolling.


Total Brake (TB)

Stops both the wheel and swivel from moving.

Helpful Hint...

To ensure correct bolt hole spacing, measure from the center of one hole to the center of the next.

Locking Options



Casterland **BP** Series (Standard Top Plate)





Floor Lock

Floor Locks are mounted separately from the casters for an even better

CAFL 6

braking option.

If it can be done, we can do it!

Looking for something different for a unique application? Or one of our normal series with a different wheel type, size or option? Let us know!

Unique Stem Sizes

Part	Wheel	Weight	Stem	
Number	Size	Capacity	Size	
DCLH 625 CI	2.5"	400 lbs	1/2" TS	DCLN 625 CI
DCLN 625 CI	2.5"	400 lbs	5/8" TS	
DCLR 625 CI	2.5"	400 lbs	3/4" TS	



Pallet Jack Wheels



Require something to be moved easily in any direction? Many threaded stem and plate style models available.




DC31 SL404 PSEL

Levelling Casters

Part	Wheel	Weight
Number	Size	Capacity
DRLV0300V4	3"	600 lbs
DRLV0600V4	3"	1,300 lbs

LV Series leveling casters have a die-cast aluminum frame with a steel swivel head, an internal leveling mechanism and dial, and a rubber foot pad. The foot pad can be adjusted to a level position and make the attached equipment completely stationary. A cast aluminum frame is powder coated in an ivory hue and the wheels are made of an ultra-strong, non-marking nylon.



Short But Tough Casters

Part	Wheel	Weight	Additional
Number	Size	Capacity	Details
BLLPA-VSTH-35K	35MM X 27MM	220 lbs	Swivel plate caster, urethane wheel, PB
BLLRA-VSTH-35K	35MM X 27MM	220 lbs	Swivel bolt hole caster, urethane wheel, PB
BLVSTH 35/6K (wheel only)	35MM X 27MM, 6MM	220 lbs	Yellow extrathane on cast iron core PB
		(Park)	

BLLPA-VSTH-35K





CASTER WHEELS

What makes one wheel better than the other? How you use it is the best answer. A hard wheel has less "rolling resistance" and as a result may be easier to push or pull. However, a softer wheel glides over debris easier and is less likely to damage floors. A choice that is in the middle is Urethane on Nylon (UN). There are also other determining factors and choices in wheels like; chemical conditions, wet environments, food workplace. Even bearing options are important factors when choosing a wheel. Speak with one of our staff to help you make the best choice!



Hi Temp (HT)

A wide selection of High Temperature wheels made in a variety of ways are available. These are generally best suited for dry heat applications such as powder coating, bakery ovens and autoclaves.

Capability ranges are up to 475° F for 30 minutes. Soft versions are an option as well.



Neoprene (XD)

These quiet and easy rolling wheels are good for all floor surfaces. Wear and oil resistant. Shock absorbing, non-marking. Will reject floor debris such as screws, metal filings and glass.



Solid Elastomer (PSE)

Quiet solid elastomer wheel. Ergonomically designed for medium loads (300-1800lbs). Excellent mobility and shock absorption. Ideal for continuous use and tow-lines. Tolerant of a wide range of chemicals.



Phenolic (PH)

Fibre filled impregnated with phenolic resin and molded with extreme heat and pressure. Provides a hard smooth wheel with good corrosion resistance.

High temperature (HT) available. Laminated Phenolic (LAM) available for better wear.



Ductile Iron(DU)

Heavy duty wheels for severe loads. Very resistant to breaking, cracking and chipping. Also referred to as malleable iron. Loads are distributed across the entire wheel for maximum floor protection. protection.



V-Groove (VG)

Made from Cast steel, these wheels are great for running along a piece of inverted angle iron or tubing as a guide. The load must still rest on the flat of the wheel tread.

Ductile Iron (VG-DU) available.



Flanged Wheel (FL)

Cast Steel or Ductile Iron wheel designed to operate on a steel track. This wheel minimizes rolling effort and aids guidance Superior wear factor to V-Groove wheels Excellent for use on boat cradles and similar tracked applications.



Thermal Plastic Rubber (TP)

New generation grey non-marking wheel bonded to thermoplastic core. Soft tread but high weight capacities. Clean running wheel with good chemical, oil, and acid resistance.



Rubber Moldon (RM)

Black solid cushion rubber tire bonded to cast steel wheel center. Provides an economical, quiet rolling wheel.



Urethane on Cast

Polyurethane formed on cast center. Good oil, chemical, and acid resistance. Will not take a compression set, and provides load ratings similar to steel wheels.



Swivel-EAZ (EZ)

Carries twice the load of standard size wheels. Maintenance free for longer life. Non-marking high performance elastomer treads



Urethane on Nylon (UN)

Polyurethane tread bonded to a polypropylene core for high strength and light weight. Non marking wheel designed to meet the stringent requirements of clinical environments.



PolyFlexon (UA)

PolyFlexon wheel offers a semi-cushioned ride and is non-marking. Great for tow-line applications. Requires less effort to start-up and maintain a rolling load. (85A durometer)



Reinforced Thermoplastic (RT)

High performance, durable and cost effective wheel generally suited for food processing, tool storage, sanitary maintenance and applications requiring heavy loads.

High temperature (HT) available.

Please note: Not all wheel sizes or bearings types are available in all wheel materials. Some materials are better suited for certain applications than others. Product may not be exactly as pictured.

*Replacement parts for most casters, including bearings, bolts, and seals, are also available.

Hi- Temperature						
	Model Number	Wheel Size	Capacity	Wheel Type	Bolt Spacing	
CCEP4150FVSPB STP CCBP4150FVSPB	CCNP4150FVSPB CCNP4150HTSRB BCHK4150HTRB FAA465W HT 4X112 CCEP4150FVSPB CCEP4150FVSPB STP CCBP4150FVSPB	4" x 1.5" 4" x 1.5" 4" x 1.5" 4" x 1.5" 4" X 1.5" 4" X 1.5" 4" X 1.5"	275 lbs 350 lbs 400 lbs 400 lbs 500 lbs 500 lbs 700 lbs	Green Epoxy Resin Pnenolic Phenolic Glass-filled Nylon Green Epoxy Resin Green Epoxy Resin Green Epoxy Resin	1-3/4" x 2-7/8" 1-3/4" x 2-7/8" 3" x 4" 3-13/32" x 2-3/8" 2-1/4" x 3" 3" x 3" 3" x 3"	

Model Number	Wheel Size	Capacity	Additional Details	Р	iano
FAEP759 2 FAEW759 2 DCOC 32 XD HWW98 Wood HWW98	Dual 2" Dual 2" Dual 2" - -	275 lbs 275 lbs 300 lbs - -	Plate, hard rubber (soft also avail.) C-clip, hard rubber (soft also avail.) C-clip, neoprene Piano caster socket for woodclip Piano caster socket for c-clip	FAW98	DCOC 32XD

Ladder/Gate	Model Number	Capacity
330 350 Manage 550 Man	G1 Series (SH9798)	(75-100 lbs range)
500 July 500	G2 Series (BCDC3)	(100-150 lbs range)
2000	G3 Series (BCGC6200RMCRB)	(180-700 lbs range)
GS Series Heavy Dury Gas Caner Heavy Dury Gas Caner Radet Annichts stoh Annichts stoh Annichts stoh Caner Series Control Ser	These series are designed specifically for rotating doors and provides a shock absorbed the compression spring helps support the in keeping it on an even or level plain.	orbing ride over uneven ground;

Model Number	Additional Details	Bed
SHBR2204WD SHBG2204WD SH9532 SH3696 SH9518 SHBG254P SHBG2204WD	3/8" wood stem roller, (brake available) 3/8" wood stem glide Adjustable to 10", 2/pkg, soft tread thermoplastic rubber 2-1/4" Slip n' grip woodgrain cups for bed casters, 4/pkg 2 bed rollers 54mm, soft tread, TPR wheel, 125lbs Plastic bed glide, adds 2-1/2" height Bed glide, 3/8" wood stem	SH3696 SHBR2204WD
Many more op	tions available in our Glides & Chair Accessories catalog!	see back page for details.

Creeper	Model Number	Wheel Size	Capacity	Additional Details







FAEY9C511 BCCCS300 HWJCN 516

3"

2-1/2"

80 lbs 150 lbs

Urethane/Nylon, 5/16" Threaded Steel wheel

Connector, 5/16" connection nut

Floor Cleaning	Model Number	Wheel Size	Capacity	Additional Details
CO2 2689 52	CO2 2689 52 DCCLA61675A DCW404PSE ALW800UG 38	2-1/2" 4" 4" 2-7/8"	175 lbs 400 lbs 1000 lbs 100 lbs	Lo-pro, swivel, polypropylene Small plate, swivel, custom made Elastomer (wheel only) Grey urethane, 3/8" x 1" hub length
DCCLA61675A				

Model Number	Additional Details	Appliances
SH9441 SH9601	Dual wheel appliance caster 5/16" threaded stem Fridge roller system	SH9601 SH9441

Scaffolds	Model Number	Wheel Size	Capacity	Stem Size	Additional Details
FAK421 5RB AGS08908-SCMR-RB	FAK421 5RB BCSC5150MP 125SQ AGS08908-SCMR-RB	5" 5" 8"	115 lbs 300 lbs 500 lbs	1"round 1-1/4" square 1-3/8" round	Rubber, brake 1-1/4" square stem, rubber Rubber, brake

Model Number	Wheel Size	Type of Mount	Capacity	Additional Details	Office
DCOB E2 XD SHOM30223VPR33 CCTW50URFR716X78 B GSF36BG	2" 3" 50mm -	7/16" x 13/16" C-Clip 7/16" x 7/8" C-Clip 7/16" x 7/8" C-Clip Requires GSS10 Stem	75 lbs 120 lbs 75 lbs -	Neoprene Chemical resistant Twin wheel, Uretha 2-1/8" x 2-3/8" blac	ne barrel
Chair Glide	М	any more options avail	able on pag	jes 1 & 2!	DCOB E2 XD

Misc.	Model Number	Wheel Size	Capacity	Additional Details
SH9442 FA156	SH9299 SH9442 FA156 ALS4125 PLY ALR4125 PLY	1" 2" 5/8" 1-1/4" 1-1/4"	200 lbs 300 lbs 110 lbs 40 lbs 40 lbs	Three wheel swivel dolly 6" diameter Three wheel swivel dolly 12" diameter Nylon, Rigid Swivel Rigid





PNEUMATIC CASTERS 8" - 16"

Top Plate: 4" x 4-1/2" **Mounting Holes:** 2-3/8" x 3-5/8" slotted to 3" x 3"

These casters are ideal when used for maneuvering over rough surfaces, shock situations (i.e. delicate instruments etc.) or anywhere that requires a smooth quiet operation of a wheeled unit.

		that requires a smooth quiet oper
CCPN8R	CCPN8S	

Model Number	Wheel Size	Overall Height	Capacity	Brake?	Swivel/ Rigid
CCPN8SWS	8"	9.75"	250 lbs	_	Swivel
CCPN8SWSSB	8"	9.75"	250 lbs	Yes	Swivel
CCPN8SWR	8"	9.75"	250 lbs	_	Rigid
CCPN10SWS	10"	12-3/16"	350 lbs	_	Swivel
CCPN10SWSSB	10"	12-3/16"	350 lbs	Yes	Swivel
CCPN10SWR	10"	12-3/16"	350 lbs	-	Rigid
CCPN12SWS	12"	15.75"	350 lbs	-	Swivel
CCPN12SWR	12"	15.75"	350 lbs	-	Rigid
CCPN16SWS	16"	19"	500 lbs	-	Swivel
CCPN16SWR	16"	19"	500 lbs	-	Rigid
		A Decition Leads to			

4 Position Lock is also an option

Caster Replacement Wheels



CWPN10SW3P L BB

Model Number	Wheel Size	Capacity	Hub Length
Pneumatic			
CWPN8L CWPN10SW3P L BB CWPN12 L BB CWPN164PNTT BB	8" 10" 12" 16"	300 lbs 460 lbs 460 lbs 590 lbs	3.25" 4" 4" 4"
Flat Free			
CWPN8FF CWPN8FF OFF CWPNFF8L CWPN10FFSW3P CWPN10FFSW3P OFF CWPN10FF L CFWA-12-6275-358J CFWA-12-6275-458J CWWA-15-83RR CWWA-15-84RR	8" 8" 10" 10" 10" 12" 12" 16"	300 lbs 300 lbs 300 lbs 350 lbs 350 lbs 350 lbs 450 lbs 450 lbs 670 lbs	2.5" 2-1/8" 3.25" 1-7/8" 2-5/16" 4" 3" 4" 3"



Looking for a smooth rolling pneumatic, but concerned about flats?

Flat Free wheels offer the same advantages of pneumatic wheels without the possibility of them going flat.

They provide a smooth cushioned ride, rolling easily over debris and small obstacles.

A saw-tooth tread design offers a combination of traction and maneuverability.

They are also available in casters and are perfect applications for hand trucks, dollies, carts and mobile equipment such as pressure washers, generators, etc.



CWPN10SW3P OFF BB

Model	Wheel	Capacity	Hub
Number	Size		Length
CWPN8 BB CWPN8OFF BB CWPN10SW3P BB CWPN10SW3P OFF BB CWPN12 BB CWPN12 OFF BB CWPN163PN4TT BB CWPN164PNTT BB	8"	250 lbs	2.5"
	8"	250 lbs	2-1/8"
	10"	350 lbs	1-7/8"
	10"	350 lbs	2-5/16"
	12"	460 lbs	3"
	12"	495 lbs	2-1/4"
	16"	500 lbs	3"
CWPN164HDPNTT BB	16"	590 lbs	4"

Bearing sizes Available: 1/2", 7/16", 5/8", 3/4" and 20mm

For long-hub and flat free wheel options see page # 11



atic	eels
neum	Wh.
ni-Pr	matic
, Ser	neu
Solid	and

Model	Wheel	Capacity	Additional
Number	Size		Details
MA104 MA104 OF MA615P OF MA615 R MA615 OF R MA715P OF MA715 R MA715 OF R MA875P OF MA875 R	5" x 1-1/4" 5" x 1-1/4" 6" x 1-1/2" 6" x 1-1/2" 6" x 1-1/2" 7" x 1-1/2" 7" x 1-1/2" 7" x 1-1/2" 8" x 1 3/4" 8" x 1-3/4"	30 lbs 30 lbs 50 lbs 50 lbs 50 lbs 55 lbs 55 lbs 60 lbs	White, ribbed White, ribbed, offset Plastic, diamond tread, offset White, ribbed White, ribbed, offset Plastic, diamond tread White, ribbed White, ribbed White, ribbed, offset Plastic, diamond tread
MA875 K MA875 58 HD MA875 58 OF HD DRSN80CO52 CSPH8175UNPBB MAZP83GW 251 MAZP83GW 21 MA110P MA110 MA110 OF MA110 58 HD MA110 58 OF HD DRSN10UO52 DRSN10UO53 MAZP121HD 3C1	8 x 1-3/4" 8" x 1-3/4" 8" x 2-3/8" 8" x 2-1/2" 8" x 2-1/2" 10" x 1-3/4" 10" x 1-3/4" 10" x 1-3/4" 10" x 1-3/4" 10" x 2-3/4" 10" x 2-3/4" 10" x 2-3/4" 10" x 2-3/4"	60 lbs 110 lbs 110 lbs 300 lbs 600 lbs 145 lbs 145 lbs 80 lbs 80 lbs 150 lbs 150 lbs 300 lbs 300 lbs	White, ribbed, heavy duty White, ribbed, heavy duty, offset Rubber, poly, offset Urethane, nylon Silver, ribbed Silver, ribbed, offset Plastic, ribbed White, ribbed White, ribbed, offset White, ribbed, heavy duty White, ribbed, heavy duty White, ribbed, heavy duty, offset Cushion rubber poly Silver, ribbed, heavy duty
MASPP 12HD 58BB	12" x 3/4"	175 lbs	Plastic, ribbed, spoked Rubber, poly, heavy duty Plastic, spoked, diamond tread Plastic, spoked, diamond tread
DR14300 P1	14" x 3"	800 lbs	
MASPP 16PSI 12BB	16" x 3/4"	200 lbs	
MASPP 20HD 58BB	20" x 3/4"	200 lbs	

Flat free wheels are also available on page # 11



MASP 20PSI 58BB



MA875P OF



DRSN80CO52

Lawnmower Wheels

Model	Wheel	Additional
Number	Size	Details
MAPL5275 CTR	5" x 2-3/4"	3-5/16" centered
MAPL5275 OF	5" x 2-3/4"	2-1/2" offset
MAPL530 JD MAPL538 JD MAPL638 JD	5" x 3" 5" x 1-3/8" 6" x 1-3/8"	2-1/2" offset (for John Deere mowers) 1/2" bushing (for John Deere mowers) 1/2" bushing (for John Deere mowers)





MAPL5275 OF

MAPL538 JD

Square Inserts

•		
Model Number	Size	l uge Fhickness)
Square Plastic Inserts		
HWRT620SQ	3/4"	16
HWRT650SQ	3/4"	18
HWRT0902SQ	1"	18
HWRT880SQ	1"	14
HWRT1010SQ	1-1/4"	11
HWRT1120SQ	1-1/4"	16
HWRT1150SQ	1-1/4"	18
HWRT1140SQ	1-1/2"	7
Square Steel Inserts		
HWSI SQ1 16GSC	1"	16-18
HWSI SQ125 16GSC	1-1/4"	16-18
HWSI SQ15 16GSC	1-1/2"	16-18
Square Threaded Steel Inse		
HWMI SQ1 T38	1" (3/8"thread)	16-18
HWMI SQ1 T516	1" (5/16" thread)	16-18
HWMI SQ125 T516	1-1/4" (5/16" thread)	
HWMI SQ1 T14	1" (1/4" thread)	16-18
HWMI SQ15 T38	1-1/2" (3/8" thread)	
HWMI SQ2 T38	2" (3/8" thread)	14-16
HWMI SQ2 T516 HWMI SQ34 T516	2" (5/16" thread) 3/4" (5/16" thread)	16-18 16-18



HWRT1010SQ



HWSI SQ1 16GSC



Round Inserts Model Gauge Diameter (Wall Thickness) Number **Round Plastic Inserts** HWRT120RD 7/8" 18 HWRT123RD 1" 16 1" HWRT125RD 18 1-5/16" HWRT126RD 11 HWRT127RD 1-1/4" 16 HWRT1310RD 1-1/2" 13 HWRT1370RD 1-1/2" 16 HWRT1495RD 1-5/8" 16 **Round Steel Inserts** HWSI RD1 16GSC 16-18 1-1/4" HWSI RD125 16GSC 16-18 HWSI RD2 16GSC 16-18 **Round Threaded Steel Inserts** HWMI RD1 T516 1" (5/16" thread) 16-18 1-1/4" (5/16" thread) 16-18 HWMI RD125 T516 1-1/2" (3/8" thread) HWMI RD15 T38 16-18 2" (5/16" thread) 1" (3/8" thread) HWMI RD2 T516 16-18 HWMI RD1 T38 16-18 **HWMI RD15 T516** 1-1/2" (5/16" Thread)16-18



HWSS LEG 158 LR

			Bull	Bullet Feet		
Model Number	Outside Diameter	Material	Weight Capacity	Shape		
HWSS LEG 112 HWSS LEG SQ112 HWPLASTIC LEG HWSS LEG 158	1-1/2" 1-1/2" 1-5/8" 1-5/8"	Stainless steel Stainless steel Thermoplastic Stainless steel	2000 lbs 2000 lbs 200 lbs 2000 lbs	Round Square Round Round		
HWSS LEG 158 LR	** Optional L	ocking Ring for HWSS	LEG 158 **			

Misc. sockets and brackets

Model Number	Description			
HWJCN 516	5/16" Nut for creeper casters			
FAGN505	3/4" Metal tooth wood socket			
HW701	.625" Plastic socket for wash bucket			
HW 48	7/16" Outside angle bracket			
HW 52	7/16" Inside angle bracket			
HW 81	7/16" Socket, flat bracket			
HWBR038	Outside "C" Bracket, 11 Guage, 3/8"nc tapped hole			
HWBRC038	Outside Corner Bracket, 14 Guage, 3/8"nc tapped hole			
HWBRC0516	Outside Corner Bracket. 14 Guage, 5/16"nc tapped hole			



HWGN505

HWJCN 516



10

HW 48

HW 52



Policies & Warranty Information

Product

Our full line of casters, wheels and glides are manufactured by some of the leading manufacturers in the industry. In addition to the products listed in this catalogue, many other products or special order items are available upon request. Please consult our order desk.

Limited Warranty: General Provisions

Casterland warrants to the original purchaser of it's product that the product will be free from defects in material and workmanship for a period of 90 days after the date of delivery to the original purchaser. This limited warranty is not effective with respect to products that are not properly installed or not used in the proper application based on loads, speeds and other factors. This warranty does not apply to products damaged or destroyed as a result of shipping.

Freight Policy

All goods ordered from this catalogue are FOB our original purchase point warehouses and shipped via freight collect. Orders over \$500.00 may be eligible for a freight reduction of half the original freight cost to a major centre by a carrier of our choice. Any large orders or O.E.M. customers may be eligible for prepaid orders to a major centre by a carrier of our choice.

Pricing

Prices are subject to change without notice. Casterland makes an effort to hold prices for a minimum of one year, however, occasionally circumstances arise which are beyond our control.

Terms

We accept Visa, MasterCard, American Express, Debit, and net 30 days on approved credit. First Time orders may be subject to COD terms or a maximum charge amount depending on credit approval.

Hours of Operation

Casterland is open from 8am to 5pm weekdays. Some locations are open from 9am to 2pm on Saturdays. Please call the location nearest you for applicable hours of operation.

Visit our webstore at **www.Casterland.com** for application tips and 24 hour access to our products.


Casterland.com Page 14


We'll make your world a better place with solutions for mobility


1-800-661-6600



Visit our Web Store at www.Casterland.com for our wide range of superior products to keep you rolling along







Our line up of catalogues to help you select the product you need!







Casterland Calgary 2600 Portland St SE Calgary, AB T2G 4M6

> Tel: 780 432 5575 infoedm@casterland.com info@casterland.com

Edmonton, AB T6E 4W8

Casterland Edmonton

9743 51 Ave NW.

Casterland Winnipeg 875 Century St. Winnipeg, MB R3H 0M3

Tel: 204 783 5500

Casterland Pitt Meadows

950-19800 Lougheed Hwy Pitt Meadows, BC V3Y 2W1

Tel: 604 543 7744 infobc@casterland.com **Casterland Sask**

Representative: Dean Fraser

Tel: 306 501 3954 dean f@casterland.com