

Model	AC Output/Capacity	Specifications	Highlight	Package Includes(Standard)
12100	12 V, 100 Ah LiFePo4 Battery	Case Style: Group 31 Voltage range: 10.8v - 14.4v Max Pulse Discharge (A): 100 Charge Voltage Cutoff (V): 14.6 Discharge Voltage Cutoff (V): 10 8 batteries can be connected BMS Communication: RS485, CAN L*W*H: 12.6" x 6.5" x 7.9"	 >6000 cycle life Self-Heating supported for cold environments Reliable Battery Management System (BMS) Auto-balanced LiFePO4 cells IP65 - Dust Tight 	K2 12100 LiFePO4 Battery Warrenty Card User Manual
12100 Basic	12 V, 100 Ah LiFePo4 Battery	Case Style: Group 31 Voltage range: 10v - 14.6v Max Pulse Discharge (A): ≤ 5 Sec 150 Max Continuous Discharge(A) : 100 Series Connection Allowed: 2 Parrallel Connection Allowed: 4 L*W*H: 12.87″ x 6.77″ x 8.66″	 2000 Cycle Life Simple K2 LiFePO4 Pack created for utilitarian battery usage (Upgrade to the 12100 for advanced features) Overcharge Protection Overdischarge Protection Overcurrent & Short Circut Proctection High & Low Temperture Protection 	K2 12100 Basic LiFePO4 Battery Warranty Card- 5 Year User Manual
12VG27-3	12 V, 111 Ah LiFePo4 Battery	Case Style: G27 Pulse Discharge (A): ≤ 30 sec 200 Charge Voltage Cutoff (V): 14.6 Discharge Voltage Cutoff (V): 10 High Operating Temp (°C): 65 Low Operating Temp (°C): -20 Series Connection Allowed: 4 L*W*H: 12.1" x 6.6" x 8.3"	 3000 Cycle Life Battery Fuel Gauge Full Battery Management System Short Circuit Protection Battery ON/OFF Button Shipping Mode Function Integrated Microprocessor Integrated Contactor Current Sensor Cell Ballancing 	K2 12vG27-3 LiFePO4 Battery Warranty Card User Manual
12VG24	12 V , 92 Ah LiFePo4 Battery	Case Style: G24 Pulse Discharge (A): \leq 30 sec 180 Charge Voltage Cutoff (V): 15.6V \pm 5% Discharge Voltage Cutoff (V): 10V High Operating Temp (°C): 60 Low Operating Temp (°C): -20 Series Connection Allowed: 4 L*W*H: 10.16" x 6.61" x 8.50"	1. 3000 Cycle Life 2. Battery Fuel Gauge 3. Full Battery Management System 4. Short Circuit Protection 5. Battery ON/OFF Button 6. Shipping Mode Function 7. IP-67 WaterProof 8.Integrated Microprocessor 9. Integrated Contactor 10. Current Censor 11. Advanced BMS 12. Cell Ballancing	K2 12VG24 LiFePO4 Battery Warranty Card User Manual
PPS - Ecox 3	300W, 231Wh Lithium-Ion Chemistry	K2 Energy Portable Power Station AC Ports: 1 AC Output: 300W Type C PD 3.0 Port: 60W USB-A QC 3.0 Ports: 2 DC Input: 48W Car Charging: 12V/10A L*W"H: 7.6" x 5.6" x 5.8"	 AC Outlet Cover 4 Output Ports 3 Charging Methods 7 Protections from Battery Safety Management System SOC Digital Display on LED Panel Flame Retardant Cover, V-0 Grade LCD Display SOS Flash Light 	K2 Ecox 3 Portable Power Station Warranty Card User Manual AC Charging Cable
PPS - Ecox 6	600W, 520Wh Lithium-Ion Chemistry	K2 Energy Portable Power Station AC Ports: 2 AC Output: 600W Type C PD 3.0 Port: 60W USB-A QC 3.0 Ports: 3 DC Input: 100W Car Charging: 12V/10A Wireless Charging: 10 W L*W*H: 11.4" x 7.9" x 7.9"	 1200W Continuous Output Applicable to Heaters 7 Output Ports 3 Charging Methods 7 Protections from Battery Safety Management System SOC Digital Display on LED Panel AC Outlet Cover Charging Simultaneously Discharging Flame Retardant Cover, V-0 Grade Eco Mode LED Light 	K2 Ecox 6 Portable Power Station Warranty Card User Manual AC Charging Cable
PPS - Ecox 10	1000W, 933Wh Lithium-Ion Chemistry	K2 Energy Portable Power Station AC Ports: 2 AC Output: 1000W Type C PD 3.0 Port: 60W USB-A QC 3.0 Ports: 3 DC Input: 150W Car Charging: 12V/10A Wireless Charging: 10 W L*W*H: 11.4" x 7.9" x 7.9"	 2000W Continuous Output Applicable to Heaters 7 Output Ports 3 Charging Methods 7 Protections from Battery Safety Management System AC Outlet Cover Charging Simultaneously Discharging Flame Retardant Cover, V-0 Grade Eco Mode LED Light 	K2 Ecox 10 Portable Power Station, Warranty Card User Manual AC Charging Cable
PPS - Ecox 18 Pro	1800W, 1466Wh Lithium-Ion Chemistry	K2 Energy Portable Power Station AC Ports: 3x Rated 1800W, Surge 3600W AC Output: 2x DC5525, 1X Cigarette Port Type C PD 3.0 Port: 60W USB-A QC 3.0 Ports: 2 Solar Panel Input: 12-60V, 800W Car Charging: 12V/10A Wireless Charging: 10 W L*W*H: 13.78" x 10.43" x 9.45"	 1. 1.5 Hours to 80%, Super Fast Charging 2. Uninterruptible Power Supply 3. Double Power 3600W & Capacity 29kWh with a Para Kit Box 4. 4000W Continuous Output Applicable to Heaters 4. 7 Protections from Battery Safety Management System 5. 8 Output Ports 6. Charging Simultaneously Discharging 7. Flame Retardant Cover, V-0 Grade 9. Eco Mode 10. LED Light 	K2 Ecox 18 Portable Power Station Solar Charging Y Splitter Cable Warranty Card User Manual AC Charging Cable