



GP Chafe Guard



FEATURES & BENEFITS

- Stealth® fibre single cover braid
- High UV resistance
- High abrasion resistance
- Solution dyed, will not fade in colour
- Protection of sheets and other ropes in high abrasion applications

RANGE/TECHNICAL

Code	Size	Colour	Unit	Construction	Stock Status
BRY05GPCG	5-8 mm	Black	Metre	32 Plait	Stocked*
BRY08GPCG	8-12 mm	Black	Metre	48 Plait	Stocked*
BRY10GPCG	10-14 mm	Black	Metre	48 Plait	Stocked*
BRY14GPCG	14-18 mm	Black	Metre	48 Plait	Stocked*

* Stocked in Australia. Made to order in New Zealand.

FIBRE CHARACTERISTICS

Fibre Type	Description	Specific Gravity	Sensitive to	Resistant to	Heat Reaction	Strength & Elongation
Stealth® Ultra High Molecular Weight Polyethylene (UHMWPE)	Continuous Filament	0.97 g/cm ³	Strong oxidising agents, Chlorosulfonic & Nitric acids at high temperatures. Slightly affected by Sodium Hydroxide (pH>14)	Most acids & alkalis, cold alcohols, ethers, esters, ketones & bleaches	Softens 144°C Melts 152°C	Equivalent wet/dry strength ratio. Elongation 4% at Break