

**A**


Turning

## WN\*\* holder (external) **M-Clamping**

MWLNR/L Kr: 95°



Right hand style



**B**

Milling

Article	*	Stock		Dimensions [mm]						Inserts
		R	L	a	b	L	h	s	e	
MWLNR/L2020K06	•	•		20	20	125	20	25	30	WN**0604**
MWLNR/L2525M06	•	•		25	25	150	25	32	30	WN**0604**
MWLNR/L2020K08	•	•		20	20	125	20	25	30	WN**0804**
MWLNR/L2525M08	•	•		25	25	150	25	32	35	WN**0804**
	○			25	25	170	25	32	35	WN**0804**
MWLNR/L3232P08	•	•		32	32	170	32	40	35	WN**0804**

● Ex stock ○ On demand

\* With internal cooling

**C**

Drilling

Spare parts		WN**0604**		WN**0804**	
	Insert h	20	25	20	25-32
	Clamp	C1RD	C1RD	C1RD	C1RD
	Dowel pin	TM5×13	TM5×13	TM6×17	TM6×17
	Screw (clamp)	DM6×25 (7.0 Nm)	DM6×30 (7.0 Nm)	DM6×25 (7.0 Nm)	DM6×30 (7.0 Nm)
	Shim	W06BM	W06BM	W08BM	W08BM
	Wrench (clamp)	WH30L	WH30L	WH30L	WH30L
	Wrench (dowel pin)	WH20L	WH20L	WH30L	WH30L

**D**

Technical Information

Insert					
<b>Wiper</b> A106	<b>Finishing</b> A107	<b>Medium Cut</b> A107	<b>Roughing</b> A109	<b>Cast Iron</b> A111	<b>PCBN/PCD</b> A165

**E**

Index

System code > A228

Grade selection > A42

Technical info > A501

Cutting data > A366