



CHASSIS[®] ADVANTAGE

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 177.8 mm x 1219.2 mm (Plank) (nom)
Overall Thickness*	0.08" / 2.0 mm
Wear Layer	12 mil / 0.30 mm, featuring Stiff Shield finish
Edge	Square
Standard Colors	8 standard planks
Installation Method	Glue Down
Wear Limited Warranty	30 Year Residential / 20-Year Light Commercial
Recycled Content	This product contains recycled content. 100% recyclable post-use
Packaging	PLANK 32.72 ft ² (3.04 m ²) per carton 14 pieces per carton 85 cartons per pallet 17 pallets per 20' container
Weight Per Carton	25.57 lbs / 11.60 kg



Armature CAD-8920 (Heavy Shade Variation)

Product Testing


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
+STC Sound Testing	ASTM E 492-09	+STC 61
+IIC Sound Testing	ASTM E 989-06	+IIC 64
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed




BETTER | WEAR LIMITED WARRANTY



SCS Certified




Spitfire CAD 8917 - Heavy Shade Variation




Motorcoach CAD 8921




Backbone CAD 8918 - Heavy Shade Variation




Suspension CAD 8922




Caspas CAD 8919



Farnham CAD 8923



Armature CAD 8920 - Heavy Shade Variation



Shepherd CAD 8924

*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images. Visit www.earthwerks.com for full product and warranty details.